

		For medium-temperature application.												For low-temperature application.														
Outdoor unit	Indoor unit	Medium-temperature application			Low-temperature application			Medium-temperature application			Low-temperature application			Medium-temperature application			Low-temperature application			Medium-temperature application			Low-temperature application					
		3	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28		
		Water heating energy efficiency class	Seasonal space heating energy efficiency class	Water heating energy efficiency class	Rated heat output under average climate conditions	For space heating, annual energy consumption under average climate conditions	For water heating, annual electricity consumption under average climate conditions	Seasonal space heating energy efficiency under average climate conditions	Water heating energy efficiency under average climate conditions	Work only during off-peak hours	Rated heat output under warmer climate conditions	Rated heat output under colder climate conditions	For space heating, annual energy consumption under warmer climate conditions	For water heating, annual electricity consumption under warmer climate conditions	Seasonal space heating energy efficiency under warmer climate conditions	Water heating energy efficiency under warmer climate conditions	Work only during off-peak hours	Rated heat output under average climate conditions	For space heating, annual energy consumption under average climate conditions	For water heating, annual electricity consumption under average climate conditions	Seasonal space heating energy efficiency under average climate conditions	Water heating energy efficiency under average climate conditions	Work only during off-peak hours	Rated heat output under warmer climate conditions	For space heating, annual energy consumption under warmer climate conditions	For water heating, annual electricity consumption under warmer climate conditions	Seasonal space heating energy efficiency under warmer climate conditions	
EAHV-P900YA-(N)-(BS)	-	✓	A+	-	63.8	45562	-	113	-	-	96.7	71.1	94146	26247	-	-	98	142	-	77	✓	A+	-	67.6	38093	-	143	-
EAHV-P900YA-H-(N)-(BS)	-	✓	A+	-	63.8	46627	-	110	-	-	96.7	71.1	94786	27528	-	-	97	135	-	77	✓	A+	-	67.6	39158	-	139	-

	English	Deutsch	Français	Italiano	Español
	Nederlands suomi	Svenska Čeština	Dansk Български	Português Polski	Ελληνικό
1	Outdoor unit buitenunit Ulkojksikkö	Außengerät Utomhusenhet Venkovní jednotka	unità esteriore unità esterna външно тяло	unità esterna unidade exterior jednostka zewnętrzna	unidad exterior Εξωτερική μονάδα
2	Indoor unit binnenunit Sisäyskisko	Innengerät	unità intérieure Indnders enhed Вътрешно тяло	unità interna unidade interior jednostka wewnętrzna	unidad interior Εσωτερική μονάδα
3	Medium-temperature application middentemperatur-toepassing keskilämpötilan sovellus	Mitteltemperaturanwendung mediumtemperaturapplikation středněteplotní aplikace	l'application à moyenne température mediumtemperaturanvendelsen středněteplotní aplikace	le applicazione a media temperatura a aplicação a média temperatura zastosowania w średnich temperaturach	la aplicación de media temperatura η εφαρμογή σε μέση θερμοκρασία -
4	Low-temperature application lagetemperatur-toepassing matalalämpötilan sovellus	Niedertemperaturanwendung lägetemperaturapplikation nízkoteplovní aplikace	l'application à basse température lavtemperaturanvendelsen niskotemperaturní aplikace	le applicazione a bassa temperatura a aplicação a baixa temperatura zastosowania w niskich temperaturach	la aplicación de baja temperatura η εφαρμογή σε χαμηλή θερμοκρασία
5	Seasonal space heating energy efficiency class de seizoensgebonden energie-efficiëntieklas voor ruimteverwarming tilalämmitysken kausittainen energiatehokkuusluokka	die Klasse für die jahreszeitbedingte Raumheizungs-Energieeffizienz säsongsrelaterade energieeffektivitetsklass vid rumsuppvärming třída sezonní energetické účinnosti vytápění	la classe d'efficacité énergétique saisonnière, pour le chauffage des locaux klassen för årsvarningsgrad ved rumopvarming klasť na sezónnata ohrevna energijna efektivnost	la classe di efficienza energetica stagionale del riscaldamento d'ambiente A classe de eficiencia energética do aquecimento ambiente sazonal klasa sezonowej efektywności energetycznej ogrzewania pomieszczeń	la clase de eficiencia energética estacional de calefacción η τάξη ενεργειακής απόδοσης της εποχιακής θέρμανσης χώρου
6	Water heating energy efficiency class de energie-efficiëntieklass voor waterverwarming vedenlämmityksen energiatehokkuusluokka	die Klasse für die Warmwasserbereitungs-Energieeffizienz energieeffektivitetsklass vid vattenuppvärming třída energetické účinnosti ohřevu vody	la classe d'efficacité énergétique, pour le chauffage de l'eau klassen för årsvarningsgrad ved vandopvarming klasť na energeticku efektivnosti pri podhrávanie na vodu	la classe di efficienza energetica del riscaldamento dell'acqua A classe de eficiencia energética do aquecimento de água klasa efektywnosci energetycznej podgrzewania wody	la clase de eficiencia energética del caldeo de agua η τάξη ενεργειακής απόδοσης νερού
7	Rated heat output under average climate conditions de nominale warmteafgifte (onder gemiddelde klimaatomstandigheden) nimelislämpöteho(keskimäärisissä ilmasto-olosuhteissa)	die Wärmennenleistung bei durchschnittlichen Klimaverhältnissen Den nominelle avgivne värmeeffekten (under genomsnittliga klimatförhållanden) menovitý tepelný výkon (za průměrných klimatických podmínek)	la puissance thermique nominale dans les conditions climatiques moyennes den nominelle nyttieffekt (under gennemsnitlige klimaforhold) nominalnata topilnina možnost (pri sredni klimatichni uslovija)	la potenza termica nominale (in condizioni climatiche medie) A potência calorifica nominal(em condições climáticas médias) znamionowa moccieplna (warunkach klimatu umiarkowanego)	la potencia calorifica nominal(en condiciones climáticas medias) η ονομαστική θερμική ισχύς (υπό μέσες κλιματικές συνθήκες)
8	For space heating, annual energy consumption under average climate conditions voor ruimteverwarming, het jaarlijkse energieverbruik (onder gemiddelde klimaatomstandigheden) tilalämmityskestä vuotuinen energiankulutus (keskimäärisissä ilmasto-olosuhteissa)	für die Raumheizung, den jährlichen Energieverbrauch bei durchschnittlichen Klimaverhältnissen För rumsuppvärming, årlig energiförbrukning (vid genomsnittliga klimatförhållanden)	pour le chauffage des locaux, la consommation annuelle d'énergie (dans les conditions climatiques moyennes)	per il riscaldamento d'ambiente, il consumo annuo di energia (in condizioni climatiche medie)	para calentar espacios, el consumo anual de energía(en condiciones climáticas medias)
9	For water heating, annual electricity consumption under average climate conditions voor waterverwarming, het jaarlijkse elektriciteitsverbruik (onder gemiddelde klimaatomstandigheden) vedenlämmityksetä vuotuinen sähkökulutus (keskimäärisissä ilmasto-olosuhteissa)	für die Warmwasserbereitung, den jährlichen Stromverbrauch bei durchschnittlichen Klimaverhältnissen För vattenuppvärming, årlig elforbrukning (vid genomsnittliga klimatförhållanden)	pour le chauffage de l'eau, la consommation annuelle d'électricité (dans les conditions climatiques moyennes)	per il riscaldamento dell'acqua, il consumo annuo di energia (in condizioni climatiche medie)	para calentar agua, el consumo anual de electricidad(en condiciones climáticas medias)
10	Seasonal space heating energy efficiency under average climate conditions de seizoensgebonden energie-efficiëntie voor ruimteverwarming (onder gemiddelde klimaatomstandigheden) tilalämmitysken kausittainen energiatehokkuus (keskimäärisissä ilmasto-olosuhteissa)	die Jahreszeitbedingte Raumheizungs-Energieeffizienz bei durchschnittlichen Klimaverhältnissen Säsongsmedelverkningsgrad för rumsuppvärming (vid genomsnittliga klimatförhållanden)	l'efficacité énergétique saisonnière pour le chauffage des locaux (dans les conditions climatiques moyennes)	l'efficienza energetica stagionale di riscaldamento d'ambiente (in condizioni climatiche medie)	la eficiencia energética estacional de calefacción(en condiciones climáticas medias)
11	Water heating energy efficiency under average climate conditions de energie-efficiëntie voor waterverwarming (onder gemiddelde klimaatomstandigheden) vedenlämmityksen energiatehokkuus (keskimäärisissä ilmasto-olosuhteissa)	die Warmwasserbereitungs-Energieeffizienz bei durchschnittlichen Klimaverhältnissen Energieeffektivitet vid vattenuppvärming (vid genomsnittliga klimatförhållanden)	l'efficacité énergétique pour le chauffage de l'eau (dans les conditions climatiques moyennes)	l'efficienza energetica di riscaldamento dell'acqua (in condizioni climatiche medie)	la eficiencia energética del caldeo de agua(en condiciones climáticas medias)
12	Sound power level L _{WA} , indoor het geluidsvermogensniveau L _{WA} binnen äänitehtoato L _{WA} sisällä	der Schallleistungsspeigel L _{WA} in Gebäuden Ljudeffektnivå L _{WA} i inomhus hiilina akustického výkonu L _{WA} ve vnitřním prostoru	le niveau de puissance acoustique L _{WA} , à l'intérieur l'effecktniveaut L _{WA} i inde nívoto na zvukovatá možnost L _{WA} na zakrito	il livello di potenza sonora L _{WA} , all'interno O nível de potência sonora L _{WA} no interior poziom moc akustycznej L _{WA} w pomieszczeniu	el nivel de potencia acústica L _{WA} en interiores η στάθμη ηχητικής ισχύος L _{WA} εσωτερικού χώρου
13	Work only during off-peak hours werken uitsluitend in de dauren	dass ein ausschließlicher Betrieb des Kombiheizgerätes zu Schwachlastzeiten	fonctionner qu'en heures creuses	funcionar solamente durante las horas de morte	funcionar solamente durante las horas de baja demanda
14	Sound power level L _{WA} , outdoor Rated heat output under colder climate conditions de nominale warmteafgifte, onder koudere klimaatomstandigheden	drives utesluitande under perioder med låg belastning die Wärmennenleistung bei kälteren Klimaverhältnissen Nominell avgiven värmeeffekt vid kallare klimatförhållanden	fungere uden for spidsbelastningsperioder la puissance thermique nominale, dans les conditions climatiques plus froides	de funcionar únicamente fora das horas de pico la potenza termica nominale, in condizioni climatiche più fredde	λειτουργία μόνο εκτός των ωρών αιχμής η επιχειρησιακή απόδοση της εποχιακής θέρμανσης υπό μέσες κλιματικές συνθήκες
15	Rated heat output under warmer climate conditions de nominale warmteafgifte, onder warmer klimaatomstandigheden nimelislämpöteho, lämpimissä ilmasto-olosuhteissa	energetický účinost ohřevu vody za průměrných klimatických podmínek jmenovitý tepelný výkon za chladnějších klimatických podmínek	den nominelle nyttieffekt under koldere klimaforhold nominalnata topilnina možnost pri po-studeni klimatichni uslovija	a potencia calorifica nominal em condições climáticas mais frias la potenza termica nominale, in condizioni climatiche più fredde	η ονομαστική θερμική ισχύς υπό ψυχρότερες κλιματικές συνθήκες
16	For space heating, annual energy consumption under colder climate conditions voor ruimteverwarming, het jaarlijkse energieverbruik onder koudere klimaatomstandigheden	für die Raumheizung, der kälteren Klimaverhältnissen	pour le chauffage des locaux, la consommation annuelle d'énergie, dans les conditions climatiques plus froides	per il riscaldamento d'ambiente, il consumo annuo di energia, in condizioni climatiche più fredde	para calentar espacios, el consumo anual de energía en condiciones climáticas más frías
17	For space heating, annual energy consumption under warmer climate conditions voor ruimteverwarming, het jaarlijkse energieverbruik onder warmere klimaatomstandigheden	pro vytápění – roční spotřeba energie za chladnějších klimatických podmínek	za otoplenie, годишното потребление на енергия при по-студени климатични условия	w odniesieniu do ogrzewania pomieszczeń, roczne zużycie energii w warunkach klimatu chłodnego	η θέρμανση υερού, η επίσημη κατανάλωση ενέργειας υπό ψυχρότερες κλιματικές συνθήκες
18	For space heating, annual energy consumption under warmer climate conditions voor waterverwarming, het jaarlijkse elektriciteitsverbruik onder koudere klimaatomstandigheden vedenlämmityksetä vuotuinen sähkökulutus (keskimäärisissä ilmasto-olosuhteissa)	für die Raumheizung, der kälteren Klimaverhältnissen För vattenuppvärming, årlig elforbrukning under kallare klimatförhållanden pro ohřev vody – roční spotřeba elektrické energie za chladnějších klimatických podmínek	pour le chauffage des locaux, la consommation annuelle d'électricité, dans les conditions climatiques plus froides	per il riscaldamento dell'acqua, il consumo annuo di energia, in condizioni climatiche più fredde	para calentar agua, el consumo anual de electricidad en condiciones climáticas más frías
19	For water heating, annual energy consumption under warmer climate conditions voor waterverwarming, het jaarlijkse elektriciteitsverbruik onder warmere klimaatomstandigheden vedenlämmityksetä vuotuinen sähkökulutus (keskimäärisissä ilmasto-olosuhteissa)	für die Warmwasserbereitung, der kälteren Klimaverhältnissen För vattenuppvärming, årlig elforbrukning under varmare klimatförhållanden pro ohřev vody – roční spotřeba elektrické energie za teplějších klimatických podmínek	pour le chauffage de l'eau, la consommation annuelle d'électricité, dans les conditions climatiques plus chaudes	per il riscaldamento dell'acqua, il consumo annuo di energia, in condizioni climatiche più fredde e più calde	para calentar agua, el consumo anual de electricidad en condiciones climáticas más cálidas
20	Seasonal space heating energy efficiency under colder climate conditions de seizoensgebonden energie-efficiëntie voor ruimteverwarming onder koudere klimaatomstandigheden tilalämmitysken kausittainen energiatehokkuus (keskimäärisissä ilmasto-olosuhteissa)	die Jahreszeitbedingte Raumheizungs-Energieeffizienz bei kälteren Klimaverhältnissen Säsongsmedelverkningsgrad för rumsuppvärming under kallare klimatförhållanden sezonní energetická účinnost vytápění za chladnějších klimatických podmínek	l'efficacité énergétique saisonnière pour le chauffage des locaux, dans les conditions climatiques plus froides	l'efficienza energetica stagionale di riscaldamento d'ambiente in condizioni climatiche più fredde	la eficiencia energética estacional de calefacción en condiciones climáticas más frías
21	Seasonal space heating energy efficiency under warmer climate conditions de seizoensgebonden energie-efficiëntie voor ruimteverwarming onder warmere klimaatomstandigheden tilalämmitysken kausittainen energiatehokkuus (keskimäärisissä ilmasto-olosuhteissa)	die Jahreszeitbedingte Raumheizungs-Energieeffizienz bei wärmeren Klimaverhältnissen Säsongsmedelverkningsgrad för rumsuppvärming under varmare klimatförhållanden sezonní energetická účinnost vytápění za teplějších klimatických podmínek	l'efficacité énergétique saisonnière pour le chauffage des locaux, dans les conditions climatiques plus chaudes	l'efficienza energetica stagionale di riscaldamento d'ambiente in condizioni climatiche più calde	la eficiencia energética estacional de calefacción en condiciones climáticas más cálidas
22	Water heating energy efficiency under colder climate conditions de energie-efficiëntie voor waterverwarming onder koudere klimaatomstandigheden vedenlämmityksen energiatehokkuus (keskimäärisissä ilmasto-olosuhteissa)	die Warmwasserbereitungs-Energieeffizienz bei kälteren Klimaverhältnissen Energieeffektivitet vid vattenuppvärming under kallare klimatförhållanden energetický účinost ohřevu vody za chladnějších klimatických podmínek	l'efficacité énergétique pour le chauffage de l'eau, dans les conditions climatiques plus froides	l'efficienza energetica di riscaldamento dell'acqua in condizioni climatiche più fredde	la eficiencia energética de caldeo de agua en condiciones climáticas más frías
23	Water heating energy efficiency under warmer climate conditions de energie-efficiëntie voor waterverwarming onder warmere klimaatomstandigheden vedenlämmityksen energiatehokkuus (keskimäärisissä ilmasto-olosuhteissa)	die Warmwasserbereitungs-Energieeffizienz bei wärmeren Klimaverhältnissen Energieeffektivitet vid vattenuppvärming under varmare klimatförhållanden energetický účinost ohřevu vody za teplějších klimatických podmínek	l'efficacité énergétique pour le chauffage de l'eau, dans les conditions climatiques plus chaudes	l'efficienza energetica di riscaldamento dell'acqua in condizioni climatiche più fredde e più calde	la eficiencia energética de caldeo de agua en condiciones climáticas más cálidas
24	Sound power level L _{WA} , outdoor het geluidsvormgensniveau L _{WA} buiten äänitehtoato L _{WA} ulkona	der Schallleistungsspeigel L _{WA} im Freien Ljudeffektnivå L _{WA} i utomhus hiilina akustického výkonu L _{WA} ve venkovním prostoru	le niveau de puissance acoustique L _{WA} à l'extérieur l'effecktniveaut L _{WA} i ude nívoto na zvukovatá možnost L _{WA} na zewnątrz	il livello di potenza sonora L _{WA} all'esterno O nível de potência sonora L _{WA} no exterior poziom moc akustycznej L _{WA} na zewnątrz	el nivel de potencia acústica L _{WA} en exteriores η στάθμη ηχητικής ισχύος L _{WA} εξωτερικού χώρου

Model(s):	Outdoor unit:	EAHV-P900YA(-N)(-BS)	
	Indoor unit:	-	
Air-to-water heat pump:	yes		
Water-to-water heat pump:	no		
Brine-to-water heat pump:	no		
Low-temperature heat pump:	no		
Equipped with a supplementary heater:	no		
Heat pump combination heater:	no		
Parameters for	medium-temperature application.		
Parameters for	average climate conditions.		

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	63.8	kW	Seasonal space heating energy efficiency	ηs	113	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj							
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj							
Tj= - 7 °C	Pdh	56.4	kW	Tj= - 7 °C	COPd	1.83	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= + 2 °C	COPd	2.96	-
Tj= + 2 °C	Pdh	34.3	kW	Tj= + 7 °C	COPd	3.73	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= +12 °C	COPd	3.87	-
Tj= + 7 °C	Pdh	22.1	kW	Tj= bivalent temperature	COPd	1.83	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= operation limit temperature	COPd	1.75	-
Tj= +12 °C	Pdh	9.8	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient (**)	Cdh	0.9	-	Operation limit temperature	TOL	-8	°C
Tj= bivalent temperature	Pdh	56.4	kW	Heating water operating limit temperature	WTOL	55	°C
Tj= operation limit temperature	Pdh	54.7	kW				
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	-7	°C				
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.200	kW	Rated heat output (*)	P _{sup}	63.8	kW
Thermostat-off mode	P _{TO}	0.200	kW	Type of energy input			
Standby mode	P _{SB}	0.200	kW				
Crankcase heater mode	P _{CK}	0.090	kW				
Other items							
Capacity control	variable		Rated air flow rate, outdoors		-	27720	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-77	dBA				
Annual energy consumption	Q _{HE}	45562	kWh				

For heat pump combination heater:

Declared load profile	-		Water heating energy efficiency	ηwh	-	%
Daily electricity consumption	Qelec	-	kWh/h			
Annual electricity consumption	AEC	-	kWh/h			

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

Model(s):	Outdoor unit:	EAHV-P900YA(-N)(-BS)	
	Indoor unit:	-	
Air-to-water heat pump:	yes		
Water-to-water heat pump:	no		
Brine-to-water heat pump:	no		
Low-temperature heat pump:	no		
Equipped with a supplementary heater:	no		
Heat pump combination heater:	no		
Parameters for	low-temperature application.		
Parameters for	average climate conditions.		

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	67.6	kW	Seasonal space heating energy efficiency	ηs	143	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj							
Tj= - 7 °C							
Pdh	59.8	kW		Tj= - 7 °C	COPd	2.58	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= + 2 °C	COPd	3.70	-
Tj= + 2 °C	Pdh	38.7	kW	Tj= + 7 °C	COPd	4.96	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= +12 °C	COPd	5.64	-
Tj= + 7 °C	Pdh	45.0	kW	Tj= bivalent temperature	COPd	2.58	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= operation limit temperature	COPd	2.14	-
Tj= +12 °C	Pdh	45.0	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient (**)	Cdh	0.9	-	Operation limit temperature	TOL	-15	°C
Tj= bivalent temperature	Pdh	59.8	kW	Heating water operating limit temperature	WTOL	55	°C
Tj= operation limit temperature	Pdh	49.4	kW				
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	-7	°C				
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.200	kW	Rated heat output (*)	P _{sup}	11.7	kW
Thermostat-off mode	P _{TO}	0.200	kW	Type of energy input			
Standby mode	P _{SB}	0.200	kW				
Crankcase heater mode	P _{CK}	0.090	kW				
Other items							
Capacity control	variable			Rated air flow rate, outdoors	-	27720	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-77	dBA				
Annual energy consumption	Q _{HE}	38093	kWh				

For heat pump combination heater:	Declared load profile	-	Water heating energy efficiency	ηwh	-	%
	Daily electricity consumption	Q _{elec}	-	kWh/h		
	Annual electricity consumption	AEC	-	kWh/h		

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating P_{designh}, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

Model(s):	Outdoor unit:	EAHV-P900YA(-N)(-BS)	
	Indoor unit:	-	
Air-to-water heat pump:	yes		
Water-to-water heat pump:	no		
Brine-to-water heat pump:	no		
Low-temperature heat pump:	no		
Equipped with a supplementary heater:	no		
Heat pump combination heater:	no		
Parameters for	medium-temperature application.		
Parameters for	colder climate conditions.		

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	96.7	kW	Seasonal space heating energy efficiency	ηs	98	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj							
Tj= - 7 °C	Pdh	58.5	kW	Tj= - 7 °C	COPd	2.16	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= + 2 °C	COPd	3.37	-
Tj= + 2 °C	Pdh	35.6	kW	Tj= + 7 °C	COPd	4.20	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= +12 °C	COPd	4.20	-
Tj= + 7 °C	Pdh	22.9	kW	Tj= bivalent temperature	COPd	2.16	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= operation limit temperature	COPd	1.64	-
Tj= +12 °C	Pdh	10.2	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient (**)	Cdh	0.9	-	Operation limit temperature	TOL	-15	°C
Tj= bivalent temperature	Pdh	58.5	kW	Heating water operating limit temperature	WTOL	50	°C
Tj= operation limit temperature	Pdh	40.8	kW				
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	-7	°C				
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.200	kW	Rated heat output (*)	P _{sup}	97.0	kW
Thermostat-off mode	P _{TO}	0.200	kW	Type of energy input			
Standby mode	P _{SB}	0.200	kW				
Crankcase heater mode	P _{CK}	0.090	kW				
Other items							
Capacity control	variable			Rated air flow rate, outdoors	-	27720	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-77	dBA				
Annual energy consumption	Q _{HE}	94146	kWh				

For heat pump combination heater:

Declared load profile	-		Water heating energy efficiency	ηwh	-	%
Daily electricity consumption	Q _{elec}	-	kWh/h			
Annual electricity consumption	AEC	-	kWh/h			

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating P_{designh}, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

Model(s):	Outdoor unit:	EAHV-P900YA(-N)(-BS)	
	Indoor unit:	-	
Air-to-water heat pump:	yes		
Water-to-water heat pump:	no		
Brine-to-water heat pump:	no		
Low-temperature heat pump:	no		
Equipped with a supplementary heater:	no		
Heat pump combination heater:	no		
Parameters for	low-temperature application.		
Parameters for	colder climate conditions.		

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	98.8	kW	Seasonal space heating energy efficiency	ηs	110	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj							
Tj= - 7 °C							
Pdh	59.8	kW		Tj= - 7 °C	COPd	2.58	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= + 2 °C	COPd	3.70	-
Tj= + 2 °C	Pdh	38.7	kW	Tj= + 7 °C	COPd	4.96	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= +12 °C	COPd	5.64	-
Tj= + 7 °C	Pdh	45.0	kW	Tj= bivalent temperature	COPd	2.58	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= operation limit temperature	COPd	2.14	-
Tj= +12 °C	Pdh	45.0	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient (**)	Cdh	0.9	-	Operation limit temperature	TOL	-15	°C
Tj= bivalent temperature	Pdh	59.8	kW	Heating water operating limit temperature	WTOL	55	°C
Tj= operation limit temperature	Pdh	49.4	kW				
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	-7	°C				
Power consumption in modes other than active mode							
Off mode	P _{OFF}	0.200	kW	Supplementary heater			
Thermostat-off mode	P _{TO}	0.200	kW	Rated heat output (*)	P _{sup}	98.8	kW
Standby mode	P _{SB}	0.200	kW	Type of energy input			
Crankcase heater mode	P _{CK}	0.090	kW				
Other items							
Capacity control	variable			Rated air flow rate, outdoors	-	27720	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-77	dBA				
Annual energy consumption	Q _{HE}	86153	kWh				

For heat pump combination heater:	Declared load profile	-	Water heating energy efficiency	ηwh	-	%
	Daily electricity consumption	Q _{elec}	-	kWh/h		
	Annual electricity consumption	AEC	-	kWh/h		

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating P_{designh}, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

Model(s):	Outdoor unit:	EAHV-P900YA(-N)(-BS)	
	Indoor unit:	-	
Air-to-water heat pump:	yes		
Water-to-water heat pump:	no		
Brine-to-water heat pump:	no		
Low-temperature heat pump:	no		
Equipped with a supplementary heater:	no		
Heat pump combination heater:	no		
Parameters for	medium-temperature application.		
Parameters for	warmer climate conditions.		

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	71.1	kW	Seasonal space heating energy efficiency	ηs	142	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj							
Tj= - 7 °C							
Pdh	-		kW	Tj= - 7 °C	COPd	-	-
Degradation co-efficient (**)	Cdh	-	-	Tj= + 2 °C	COPd	2.12	-
Tj= + 2 °C	Pdh	71.1	kW	Tj= + 7 °C	COPd	3.60	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= +12 °C	COPd	3.99	-
Tj= + 7 °C	Pdh	45.7	kW	Tj= bivalent temperature	COPd	2.12	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= operation limit temperature	COPd	1.75	-
Tj= +12 °C	Pdh	20.3	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient (**)	Cdh	0.9	-	Operation limit temperature	TOL	-8	°C
Tj= bivalent temperature	Pdh	71.1	kW	Heating water operating limit temperature	WTOL	55	°C
Tj= operation limit temperature	Pdh	54.7	kW				
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	2	°C				
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.200	kW	Rated heat output (*)	P _{sup}	0.0	kW
Thermostat-off mode	P _{TO}	0.200	kW	Type of energy input			
Standby mode	P _{SB}	0.200	kW				
Crankcase heater mode	P _{CK}	0.090	kW				
Other items							
Capacity control	variable			Rated air flow rate, outdoors	-	27720	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-77	dBA				
Annual energy consumption	Q _{HE}	26247	kWh				

For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	ηwh	-	%
Daily electricity consumption	Q _{elec}	-	kWh				
Annual electricity consumption	AEC	-	kWh/h				

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating P_{designh}, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

Model(s):	Outdoor unit:	EAHV-P900YA(-N)(-BS)	
	Indoor unit:	-	
Air-to-water heat pump:	yes		
Water-to-water heat pump:	no		
Brine-to-water heat pump:	no		
Low-temperature heat pump:	no		
Equipped with a supplementary heater:	no		
Heat pump combination heater:	no		
Parameters for	low-temperature application.		
Parameters for	warmer climate conditions.		

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	75.3	kW	Seasonal space heating energy efficiency	ηs	189	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj							
Tj= - 7 °C							
Pdh	-		kW	Tj= - 7 °C	COPd	-	-
Degradation co-efficient (**)	Cdh	-	-	Tj= + 2 °C	COPd	3.16	-
Tj= + 2 °C	Pdh	75.3	kW	Tj= + 7 °C	COPd	4.96	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= +12 °C	COPd	5.64	-
Tj= + 7 °C	Pdh	48.4	kW	Tj= bivalent temperature	COPd	3.16	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= operation limit temperature	COPd	2.14	-
Tj= +12 °C	Pdh	45.0	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient (**)	Cdh	0.9	-	Operation limit temperature	TOL	-15	°C
Tj= bivalent temperature	Pdh	75.3	kW	Heating water operating limit temperature	WTOL	55	°C
Tj= operation limit temperature	Pdh	49.4	kW				
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	2	°C				
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.200	kW	Rated heat output (*)	P _{sup}	0.0	kW
Thermostat-off mode	P _{TO}	0.200	kW	Type of energy input			
Standby mode	P _{SB}	0.200	kW				
Crankcase heater mode	P _{CK}	0.090	kW				
Other items							
Capacity control	variable			Rated air flow rate, outdoors	-	27720	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-77	dBA				
Annual energy consumption	Q _{HE}	20901	kWh				

For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	ηwh	-	%
Daily electricity consumption	Q _{elec}	-	kWh				
Annual electricity consumption	AEC	-	kWh/h				

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating P_{designh}, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

Model(s):	Outdoor unit:	EAHV-P900YA-H(-N)(-BS)	
	Indoor unit:	-	
Air-to-water heat pump:	yes		
Water-to-water heat pump:	no		
Brine-to-water heat pump:	no		
Low-temperature heat pump:	no		
Equipped with a supplementary heater:	no		
Heat pump combination heater:	no		
Parameters for	medium-temperature application.		
Parameters for	average climate conditions.		

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	63.8	kW	Seasonal space heating energy efficiency	ηs	110	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj							
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj							
Tj= - 7 °C	Pdh	56.4	kW	Tj= - 7 °C	COPd	1.83	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= + 2 °C	COPd	2.96	-
Tj= + 2 °C	Pdh	34.3	kW	Tj= + 7 °C	COPd	3.73	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= +12 °C	COPd	3.87	-
Tj= + 7 °C	Pdh	22.1	kW	Tj= bivalent temperature	COPd	1.83	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= operation limit temperature	COPd	1.75	-
Tj= +12 °C	Pdh	9.8	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient (**)	Cdh	0.9	-	Operation limit temperature	TOL	-8	°C
Tj= bivalent temperature	Pdh	56.4	kW	Heating water operating limit temperature	WTOL	55	°C
Tj= operation limit temperature	Pdh	54.7	kW				
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	-7	°C				
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.200	kW	Rated heat output (*)	P _{sup}	63.8	kW
Thermostat-off mode	P _{TO}	0.200	kW	Type of energy input			
Standby mode	P _{SB}	0.200	kW				
Crankcase heater mode	P _{CK}	0.090	kW				
Other items							
Capacity control	variable		Rated air flow rate, outdoors		-	27720	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-77	dBA				
Annual energy consumption	Q _{HE}	46627	kWh				

For heat pump combination heater:	Declared load profile	-	Water heating energy efficiency	ηwh	-	%
	Daily electricity consumption	Q _{elec}	-	kWh/h		
	Annual electricity consumption	AEC	-	kWh/h		

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating P_{designh}, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

Model(s):	Outdoor unit:	EAHV-P900YA-H(-N)(-BS)	
	Indoor unit:	-	
Air-to-water heat pump:	yes		
Water-to-water heat pump:	no		
Brine-to-water heat pump:	no		
Low-temperature heat pump:	no		
Equipped with a supplementary heater:	no		
Heat pump combination heater:	no		
Parameters for	low-temperature application.		
Parameters for	average climate conditions.		

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	67.6	kW	Seasonal space heating energy efficiency	ηs	139	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj							
Tj= - 7 °C							
Pdh	59.8	kW		Tj= - 7 °C	COPd	2.58	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= + 2 °C	COPd	3.70	-
Tj= + 2 °C	Pdh	38.7	kW	Tj= + 7 °C	COPd	4.96	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= +12 °C	COPd	5.64	-
Tj= + 7 °C	Pdh	45.0	kW	Tj= bivalent temperature	COPd	2.58	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= operation limit temperature	COPd	2.14	-
Tj= +12 °C	Pdh	45.0	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient (**)	Cdh	0.9	-	Operation limit temperature	TOL	-15	°C
Tj= bivalent temperature	Pdh	59.8	kW	Heating water operating limit temperature	WTOL	55	°C
Tj= operation limit temperature	Pdh	49.4	kW				
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	-7	°C				
Power consumption in modes other than active mode							
Off mode	P _{OFF}	0.200	kW	Supplementary heater			
Thermostat-off mode	P _{TO}	0.200	kW	Rated heat output (*)	P _{sup}	11.7	kW
Standby mode	P _{SB}	0.200	kW	Type of energy input			
Crankcase heater mode	P _{CK}	0.090	kW				
Other items							
Capacity control	variable			Rated air flow rate, outdoors	-	27720	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-77	dBA				
Annual energy consumption	Q _{HE}	39158	kWh				

For heat pump combination heater:	Declared load profile	-	Water heating energy efficiency	ηwh	-	%
	Daily electricity consumption	Q _{elec}	-	kWh/h		
	Annual electricity consumption	AEC	-	kWh/h		

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating P_{designh}, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

Model(s):	Outdoor unit:	EAHV-P900YA-H(-N)(-BS)	
	Indoor unit:	-	
Air-to-water heat pump:	yes		
Water-to-water heat pump:	no		
Brine-to-water heat pump:	no		
Low-temperature heat pump:	no		
Equipped with a supplementary heater:	no		
Heat pump combination heater:	no		
Parameters for	medium-temperature application.		
Parameters for	colder climate conditions.		

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	96.7	kW	Seasonal space heating energy efficiency	ηs	97	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj							
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj							
Tj= - 7 °C	Pdh	58.5	kW	Tj= - 7 °C	COPd	2.16	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= + 2 °C	COPd	3.37	-
Tj= + 2 °C	Pdh	35.6	kW	Tj= + 7 °C	COPd	4.20	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= +12 °C	COPd	4.20	-
Tj= + 7 °C	Pdh	22.9	kW	Tj= bivalent temperature	COPd	2.16	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= operation limit temperature	COPd	1.64	-
Tj= +12 °C	Pdh	10.2	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient (**)	Cdh	0.9	-	Operation limit temperature	TOL	-15	°C
Tj= bivalent temperature	Pdh	58.5	kW	Heating water operating limit temperature	WTOL	50	°C
Tj= operation limit temperature	Pdh	40.8	kW				
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	-7	°C				
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.200	kW	Rated heat output (*)	P _{sup}	97.0	kW
Thermostat-off mode	P _{TO}	0.200	kW	Type of energy input			
Standby mode	P _{SB}	0.200	kW				
Crankcase heater mode	P _{CK}	0.090	kW				
Other items							
Capacity control	variable		Rated air flow rate, outdoors		-	27720	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-77	dBA				
Annual energy consumption	Q _{HE}	94786	kWh				

For heat pump combination heater:

Declared load profile	-		Water heating energy efficiency	ηwh	-	%
Daily electricity consumption	Qelec	-	kWh/h			
Annual electricity consumption	AEC	-	kWh/h			

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

Model(s):	Outdoor unit:	EAHV-P900YA-H(-N)(-BS)	
	Indoor unit:	-	
Air-to-water heat pump:	yes		
Water-to-water heat pump:	no		
Brine-to-water heat pump:	no		
Low-temperature heat pump:	no		
Equipped with a supplementary heater:	no		
Heat pump combination heater:	no		
Parameters for	low-temperature application.		
Parameters for	colder climate conditions.		

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	98.8	kW	Seasonal space heating energy efficiency	ηs	109	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj							
Tj= - 7 °C							
Pdh	59.8	kW		Tj= - 7 °C	COPd	2.58	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= + 2 °C	COPd	3.70	-
Tj= + 2 °C	Pdh	38.7	kW	Tj= + 7 °C	COPd	4.96	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= +12 °C	COPd	5.64	-
Tj= + 7 °C	Pdh	45.0	kW	Tj= bivalent temperature	COPd	2.58	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= operation limit temperature	COPd	2.14	-
Tj= +12 °C	Pdh	45.0	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient (**)	Cdh	0.9	-	Operation limit temperature	TOL	-15	°C
Tj= bivalent temperature	Pdh	59.8	kW	Heating water operating limit temperature	WTOL	55	°C
Tj= operation limit temperature	Pdh	49.4	kW				
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	-7	°C				
Power consumption in modes other than active mode							
Off mode	P _{OFF}	0.200	kW	Supplementary heater			
Thermostat-off mode	P _{TO}	0.200	kW	Rated heat output (*)	P _{sup}	98.8	kW
Standby mode	P _{SB}	0.200	kW	Type of energy input			
Crankcase heater mode	P _{CK}	0.090	kW				
Other items							
Capacity control	variable			Rated air flow rate, outdoors	-	27720	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-77	dBA				
Annual energy consumption	Q _{HE}	86793	kWh				
For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	ηwh	-	%
Daily electricity consumption	Q _{elec}	-	kWh				
Annual electricity consumption	AEC	-	kWh/h				

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

Model(s):	Outdoor unit:	EAHV-P900YA-H(-N)(-BS)	
	Indoor unit:	-	
Air-to-water heat pump:	yes		
Water-to-water heat pump:	no		
Brine-to-water heat pump:	no		
Low-temperature heat pump:	no		
Equipped with a supplementary heater:	no		
Heat pump combination heater:	no		
Parameters for	medium-temperature application.		
Parameters for	warmer climate conditions.		

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	71.1	kW	Seasonal space heating energy efficiency	ηs	135	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj							
Tj= - 7 °C							
Pdh	-		kW	Tj= - 7 °C	COPd	-	-
Degradation co-efficient (**)	Cdh	-	-	Tj= + 2 °C	COPd	2.12	-
Tj= + 2 °C	Pdh	71.1	kW	Tj= + 7 °C	COPd	3.60	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= +12 °C	COPd	3.99	-
Tj= + 7 °C	Pdh	45.7	kW	Tj= bivalent temperature	COPd	2.12	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= operation limit temperature	COPd	1.75	-
Tj= +12 °C	Pdh	20.3	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Degradation co-efficient (**)	Cdh	0.9	-	Operation limit temperature	TOL	-8	°C
Tj= bivalent temperature	Pdh	71.1	kW	Heating water operating limit temperature	WTOL	55	°C
Tj= operation limit temperature	Pdh	54.7	kW				
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	2	°C				
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.200	kW	Rated heat output (*)	P _{sup}	0.0	kW
Thermostat-off mode	P _{TO}	0.200	kW	Type of energy input			
Standby mode	P _{SB}	0.200	kW				
Crankcase heater mode	P _{CK}	0.090	kW				
Other items							
Capacity control	variable			Rated air flow rate, outdoors	-	27720	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-77	dBA				
Annual energy consumption	Q _{HE}	27528	kWh				
For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	ηwh	-	%
Daily electricity consumption	Q _{elec}	-	kWh				
Annual electricity consumption	AEC	-	kWh/h				

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

Model(s):	Outdoor unit:	EAHV-P900YA-H(-N)(-BS)	
	Indoor unit:	-	
Air-to-water heat pump:	yes		
Water-to-water heat pump:	no		
Brine-to-water heat pump:	no		
Low-temperature heat pump:	no		
Equipped with a supplementary heater:	no		
Heat pump combination heater:	no		
Parameters for	low-temperature application.		
Parameters for	warmer climate conditions.		

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	75.3	kW	Seasonal space heating energy efficiency	ηs	179	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj							
Tj= - 7 °C							
Tj= - 7 °C	Pdh	-	kW	Tj= - 7 °C	COPd	-	-
Degradation co-efficient (**)	Cdh	-	-	Tj= + 2 °C	COPd	3.16	-
Tj= + 2 °C	Pdh	75.3	kW	Tj= + 2 °C	COPd	4.96	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= + 7 °C	COPd	5.64	-
Tj= + 7 °C	Pdh	48.4	kW	Tj= + 12 °C	COPd	3.16	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= bivalent temperature	COPd	2.14	-
Tj= +12 °C	Pdh	45.0	kW	Tj= operation limit temperature	COPd	-	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-15	°C
Tj= bivalent temperature	Pdh	75.3	kW	Operation limit temperature	TOL	55	°C
Tj= operation limit temperature	Pdh	49.4	kW	Heating water operating limit temperature	WTOL		
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	2	°C				
Power consumption in modes other than active mode							
Off mode	P _{OFF}	0.200	kW	Supplementary heater			
Thermostat-off mode	P _{TO}	0.200	kW	Rated heat output (*)	P _{sup}	0.0	kW
Standby mode	P _{SB}	0.200	kW	Type of energy input			
Crankcase heater mode	P _{CK}	0.090	kW				
Other items							
Capacity control	variable			Rated air flow rate, outdoors	-	27720	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-77	dBA				
Annual energy consumption	Q _{HE}	22181	kWh				
For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	ηwh	-	%
Daily electricity consumption	Q _{elec}	-	kWh				
Annual electricity consumption	AEC	-	kWh/h				

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.