



ENERG
енергия · ενέργεια

Y IJA
IE IA



MITSUBISHI
ELECTRIC

Model

Indoor unit
Outdoor unit

PKA-M60KAL
PUZ-ZM60VHA

SEER



A++

A+++

A++

A+

A

B

C

D

kW 6,1

SEER 6,8

kWh/annum 313

SCOP



A+

A+++

A++

A+

A

B

C

D

kW X

SCOP X

kWh/annum X

4,4

X

4,2

X

1460

X



64dB



67dB



ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

626/2011

Ⓐ Model	Ⓑ Indoor unit	PKA-M35HAL	PKA-M50HAL	PKA-M60KAL	PKA-M71KAL
		Ⓒ Outdoor unit	PUZ-ZM35VKA	PUZ-ZM50VKA	PUZ-ZM60VHA
Ⓓ Sound power levels on cooling mode	Ⓔ Inside dB	60	60	64	64
	Ⓕ Outside dB	65	65	67	67
Ⓖ Refrigerant	R32 GWP 550 *1				
Ⓗ Cooling	SEER	6,3	6,4	6,8	6,8
	Ⓛ Energy efficiency class	A++	A++	A++	A++
Ⓜ Heating (Average season)	Ⓚ Annual electricity consumption *2 kWh/a	200	251	313	364
	Ⓛ Design load kW	3,6	4,6	6,1	7,1
Ⓜ Heating (Average season)	SCOP	4,0	4,1	4,2	4,3
	Ⓛ Energy efficiency class	A+	A+	A+	A+
	Ⓚ Annual electricity consumption *2 kWh/a	839	1115	1460	1523
	Ⓛ Design load kW	2,4	3,3	4,4	4,7
	⑨ Declared capacity at reference design temperature kW	2,4 (-10°C)	3,3 (-10°C)	4,4 (-10°C)	4,7 (-10°C)
	⑩ Declared capacity at bivalent temperature kW	2,4 (-10°C)	3,3 (-10°C)	4,4 (-10°C)	4,7 (-10°C)
	⑪ Declared capacity at operation limit temperature kW	2,2 (-11°C)	3,2 (-11°C)	2,8 (-20°C)	3,5 (-20°C)
	⑫ Back up heating capacity kW	0	0	0	0

Deutsch	Italiano	Svenska	Polski	Eesti	Malti	Русский
Français	Ελληνικά	Česky	Slovensko	Gaeilge	Suomi	Norsk
Nederlands	Português	Slovensky	Български	Latviski	Türkçe	Українська
Español	Dansk	Magyar	Română	Lietuvių k.	Hrvatski	
Model	Modello	Modell	Model	Model	Model	Модель
Modèle	Модéло	Model	Model	Déanamh	Malli	Modell
Model	Modelo	Model	Model	Modelis	Model	Модель
Modelo	Model	Modell	Model	Modelis	Model	Модель
Innengerät	Unità interna	Inomhusenhet	Jednostka wewnętrzna	Siseseade	Unità għal ġewwa	Внутренний прибор
Appareil intérieur	Εσωτερική μονάδα	Vnitřní jednotka	Notranja enota	Aonad laistigh	Sisáksikkó	Innendørsenhet
Binnenunit	Unidade interior	Vnútorná jednotka	Вътрешно тяло	Iekšelpu ierīce	İç ünite	Внутрішній блок
Unidad interior	Indendørsenhet	Beltéri egység	Unitate de interior	Patalpoje montuojamas irenginys	Unutarnja jedinica	
Außengerät	Unità esterna	Utomhusenhet	Jednostka zewnętrzna	Välisseade	Unità għal barra	Наружный прибор
Modèle extérieur	Εξωτερική μονάδα	Vnější jednotka	Zunanja enota	Aonad lasmuigh	Ulkoysikkö	Utendørsenhet
Buitenunit	Unidade exterior	Vonkajšia jednotka	Външно тяло	Ārtelpas ierīce	Dış ünite	Зовнішній блок
Unidad exterior	Udendørsenhet	Kültéri egység	Unitate de exterior	Lauke montuojamas irenginys	Vanjska jedinica	
Schalleistungspegel im Kühl-modus	Livelli di potenza sonora in modalità di raffreddamento	Bullernivå i nedkyllningsläget	Poziom moczy dźwięku w trybie chłodzenia	Mūratasemed jahutusrežiimis	Livelli tal-qawwa tal-hsejjes fil-modalità tat-kessieħ	Значения уровня звуковой мощности в режиме охлаждения
Niveaux de puissance corrects en mode de refroidissement	Επίπεδα ισχύος ρήχου στην κατάσταση ψύξης	Úrovně hlučnosti v režimu chlazení	Ravni zvočne moči v načinu hlajenja	Leibhéil chumhacha fuaime ar mhodh fuaralhe	Äänenvoimakkuustasot viilen-nystilassa	Lydrykknivär i avkjölingsmodus
Geluidsniveaus in koelstand	Níveis de potência sonora em modo de arrefecimento	Hladiny akustického výkonu v režime chladenia	Нива на звуковата мощност в режим на охлаждане	Akustiskās jaudas līmenis dzesēšanas režīmā	Soğutma modunda ses güç düzeyleri	Рівні звукової потужності у режимі охолодження
Niveles de potencia del sonido en el modo de refrigeración	Lydstyrkeniveauer i kølefunktion	Hangnyomásszintek hűtés üzem-módban	Nivel sonor în modul de răcire	Garso galios lygis vésinimo režimu	Razine zvučnog tlaka pri hlađenju	
Innen	Interno	Insida	Wewnätrz	Sees	Gewwa	Внутри
À l'intérieur	Εσωτερικό	Uvnitř	Znotraj	Laistigh	Sisäpuoli	Innwendig
Binnenkant	Interior	Vo vnútri	Вътре	Iekštelpās	İç taraf	Усередині
Interior	Indvendig	Bent	Interior	Vidinis	Unutra	
Außen	Externo	Utsida	Na zewnätrz	Väljas	Barra	Снаружи
À l'extérieur	Εξωτερικό	Venu	Zunaj	Lasmuigh	Ulkopuoli	Utwendig
Buitenkant	Exterior	Vonku	На открыто	Ārtelpā	Dış taraf	Назовні
Exterior	Udvendig	A szabadban	Exterior	İsorinis	Vani	
Kühlmittel	Refrigerante	Köldmedel	Czynnik chłodniczy	Külmutsagens	Refrigerant	Хладагент
Réfrigérant	Ψυκτικό	Chladivo	Hladilno sredstvo	Cuisnéan	Kylmääine	Kjølemedium
Koelmiddel	Refrigerante	Chladivo	Xladilen agent	Aukstumaǵents	Soğutucu	Холодаагент
Refrigerante	Kølemiddel	Hütöközeg	Refrigerent	Şaldalas	Rashladno sredstvo	

Deutsch	Italiano	Svenska	Polski	Eesti	Malti	Русский
Français	Ελληνικά	Česky	Slovensko	Gaeilge	Suomi	Norsk
Nederlands	Português	Slovensky	Български	Latviski	Türkçe	Українська
Español	Dansk	Magyar	Română	Lietuvių k.	Hrvatski	
Kühlen	Raffreddamento	Kyla	Chłodzenie	Jahutus	Tkessiħ	Охлаждение
Refroidissement	Ψύξη	Chlazení	Hlajenie	Fuarú	Vilennys	Avkjøling
Koelen	Arrefecimento	Chladenie	Oxhľadzanie	Dzesēšana	Soğutma	Охолодження
Refrigeración	Köling	Hűtés	Răcire	Vésinimas	Hlađenje	
Energieeffizienzklasse	Classe di efficienza energetica	Energiklass	Klasa energetyczna	Energiatħosuhuse klass	Klassi tal-effiċjenza fl-użu tal-enerġija	Класс эффективности использования энергии
Classe d'efficacité énergétique	Κλάση ενέργειακής απόδοσης	Třída energetické účinnosti	Razred energetiske učinkovitosti	Aicme ēifeachtulachha fuinnimh	Energiatehokkuusluokka	Energieffektivitetsklasse
Energie-efficiëntiekklasse	Classe de eficiència energética	Trieda energetickej účinnosti	Klasc na energetyna efektywnost	Energoefektyvitātes klase	Enerji verimlilik sıñi	Клас ефективності енергоспоживання
Clase de eficiencia energética	Energieeffektivitetsklasse	Energiahátekonyásig osztály	Clasă de eficiență energetică	Enerģijos vartojimo efektyvumo klasė	Klasa energetiske učinkovitosti	
Jahresstromverbrauch *2	Consumo annuale di energia elettrica *2	Årlig strömforbrukning *2	Zużycie prądu w skali roku *2	Aastane voolutarbirbus *2	Konsum annwali tal-elettriku *2	Годовое потребление электроэнергии *2
Consommation d'électricité annuelle *2	Ετήσια κατανάλωση πεύματος *2	Roční spotřeba elektrické energie *2	Letna poraba elektrike *2	Ídiu leictreachais bhliantúl *2	Vuotuinen sähkökulutus *2	Årlig strømforbruk *2
Jaarlijks elektriciteitsverbruik *2	Consumo anual de electricidadade *2	Ročná spotreba elektriny *2	Годишка консумация на електроенергия *2	Gada elektroenerģijas patēriņš *2	Yıllık elektrik tüketimi *2	Річне споживання електроенергії *2
Consumo anual de electricidad *2	Årligt elforbrug *2	Éves áramfogyasztás *2	Consum anual de electricitate *2	Metinis elektros energijos suvar-tojimas *2	Godišnja potrošnja električne energije *2	
Lastauslegung	Carico nominale	Dimensionerande belastning	Maksymalne obciążenie	Projekteeritud koormus	Tagħbija tad-disinn	Расчетная нагрузка
Charge de calcul	Σχεδιασμός, φόρτωσης	Jmenovité zatížení	Nazivna obremenitev	Lód deartha	Laskettu kuormitus	Uformningsbelastning
Ontwerpbelasting	Carga nominal	Projektované zaťaženie	Проектен товар	Aprēķina slodze	Tasarim yükü	Розрахункове навантаження
Carga de diseño	Brugslast	Méretezési terhelés	Sarcină nominală	Projektinė apkrova	Težina uređaja	
Heizen (Jahresdurchschnitt / wärmes Welter)	Riscaldamento (Stagione media / calda)	Värme (Genomsnittlig/varmare årsid)	Ogrzewanie (Sezon umiarkowany/ciepły)	Kütmine (keskmene/soojaperiood)	Tishin (Staġun Medju / Aktar Shun)	Харев (средний/теплый сезон)
Chauffage (moyenne saison / saison chaude)	Θέρμανση (Εποχή με μέσες / υψηλότερες θερμοκρασίες)	Topení (průměrná/teplá sezóna)	Ogrevanje (Povprečni/toplejši letni čas)	Téamh (Séasúr Meánach / Níos teo)	Lämmitys (Normaalii / Lämpimämpi kausi)	Oppvarming (gjennomsnittlig / varmere årsid)
Verwärmen (gemiddeld / warmer seizoen)	Aquecimento (Média estação / estação mais quente)	Vykurovanie (Priemerné/teplejšie obdobie)	Отопление (Средно / Топъл сезон)	Sildišana (Vidēji siltā/siltā gadalaikā)	İsıtma (Ortalama / İlik mevsim)	Опалення (у середній/теплий сезон)
Calefacción (Promedio / temperatura más cálida)	Varme (gennemsnittlig/varmre sæson)	Fűtés (Átlagos/meleg évszak)	Încălzire (Anotimp normal/mai cald)	Šildymas (vidutinis / šiltuoju sezonu)	Zagrijavanje (Prosječ / toplica sezona)	
Nennkapazität	Capacità dichiarata	Deklarerad kapacitet	Deklarowana pojemność	Deklareritudo vőimsus	Kapacità ddikjarata	Гарантированная мощность
Capacité déclarée	Δηλωμένη χωρητικότητα	Udávaná kapacita	Prijavljena zmogljivost	Toileadħi fógartha	Ilmoitettu teho	Erklært kapasitet
Aangegeven capaciteit	Capacidade declarada	Deklarovaný výkon	Обявена мощност	Deklarētā jauda	Beyan edilen kapasite	Гарантована потужність
Capacidad declarada	Erkläret kapacitet	Névleges teljesítmény	Capacitate declarată	Deklaruotas pajęgumas	Deklarirani kapacitet	
bei angegebener Referenztemperatur	alla temperatura di progetto di riferimento	vid dimensionerande referenstemperatur	w znamionowej temperaturze odniesienia	projekteerimise vörðlustemperaturu juures	f'temperatura tad-disinn ta' referenza	при эталонной расчетной температуре
à la température de calcul de référence	σε θερμοκρασία σχεδιασμού αναφοράς	při referenční výpočtové teplotě	ob referenční nazivní temperaturi	ag teocht deartha tagartha	perusmittoituslämpötillässä	ved referansetemperatur for utforming
bij referentieontwerptemperatuur	à températura nominal de referência	pri referenčnej výpočtové teplotě	pri izčislitelna projektna temperatūra	aprēķina references temperatūrā	referans tasaram sicaklığında	При етапной розрахунковій температурі
a temperatura de diseño de referencia	ved brugsafhængig referencetemperatur	tervezési referencia-hőmérsékleten	la temperatura de referință nominală	esant norminei projektinei temperatură	pri referentnoj temperaturi	
bei bivalenter Temperatur	alla temperaturla bivalente	vid bivalent temperatur	w temperaturze biwalentnej	bivalentse temperatuuri juures	f'temperatura bivalenti	при бивалентной температуре
à température bivalente	σε θερμοκρασία δισθενούς λειτουργίας	při bivalentní teplotě	pri bivalentní temperaturi	ag teocht dhéfiúsach	kaksiarvoisessa lämpötillässä	ved bivalent temperatur
bij						

PRODUCT INFORMATION (*)

PACKAGED AIR CONDITIONER	INDOOR MODEL OUTDOOR MODEL	PKA-M60KAL PUZ-ZM60VHA	
Function (indicate if present)		If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season	
cooling	Y	Average (mandatory) Y	
heating	Y	Warmer (if designated) N	
Colder (if designated)		Colder (if designated) N	
Item	symbol	value	unit
Design load			
cooling	Pdesignc	6.1	kW
heating/Average	Pdesignh	4.4	kW
heating/Warmer	Pdesignh	x	kW
heating/Colder	Pdesignh	x	kW
Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C	Pdc	6.10	kW
Tj=30°C	Pdc	4.40	kW
Tj=25°C	Pdc	2.80	kW
Tj=20°C	Pdc	2.70	kW
Declared capacity for heating/Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	3.80	kW
Tj=2°C	Pdh	2.30	kW
Tj=7°C	Pdh	1.70	kW
Tj=12°C	Pdh	2.00	kW
Tj=bivalent temperature	Pdh	4.40	kW
Tj=operating limit	Pdh	2.80	kW
Declared capacity for heating/Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	Pdh	x	kW
Tj=7°C	Pdh	x	kW
Tj=12°C	Pdh	x	kW
Tj=bivalent temperature	Pdh	x	kW
Tj=operating limit	Pdh	x	kW
Declared capacity for heating/Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	x	kW
Tj=2°C	Pdh	x	kW
Tj=7°C	Pdh	x	kW
Tj=12°C	Pdh	x	kW
Tj=bivalent temperature	Pdh	x	kW
Tj=operating limit	Pdh	x	kW
Tj=-15°C	Pdh	x	kW
Bivalent temperature			
heating/Average	Tbiv	-10	°C
heating/Warmer	Tbiv	x	°C
heating/Colder	Tbiv	x	°C
Cycling interval capacity			
for cooling	Pcycc	x	kW
for heating	Pcych	x	kW
Degradation co-efficient cooling	Cdc	0.25	-
Degradation co-efficient heating	Cdh	0.25	-
Electric power input in power modes other than 'active mode'			
off mode	POFF	17	W
standby mode	PSB	17	W
thermostat - off mode	PTO(c/h)	7/42	W
crankcase heater mode	PCK	0	W
Capacity control (indicate one of three options)			
fixed		N	
staged		N	
variable		Y	
Contact details for obtaining more information		Name and address of the manufacturer or of its authorized representative.	

(*) This information is based on the "product information requirement" in COMMISSION REGULATION (EU) No206/2012.

TECHNICAL DOCUMENTATION (¹)

PACKAGED AIR CONDITIONER	INDOOR MODEL OUTDOOR MODEL	PKA-M60KAL PUZ-ZM60VHA	365H1170W295D (mm) 943H950W330D (mm)
--------------------------	-------------------------------	---------------------------	---

Function	
cooling	Y
heating	Y

The heating season	
Average (mandatory)	Y
Warmer (if designated)	N
Colder (if designated)	N

Capacity control	
fixed	N
staged	N
variable	Y

Item	symbol	value	unit
Seasonal efficiency (²)			
cooling	SEER	6.8	-
heating/Average	SCOP/A	4.2	-
heating/Warmer	SCOP/W	x	-
heating/Colder	SCOP/C	x	-

Energy efficiency class			
cooling	SEER	A++	-
heating/Average	SCOP/A	A+	-
heating/Warmer	SCOP/W	x	-
heating/Colder	SCOP/C	x	-

Other items			
Sound power level (indoor/outdoor)	LWA	64/67	dB(A)
Refrigerant	-	R32	-
Global warming potential	GWP	550	kgCO ₂ eq.

identification and signature of the person empowered to bind the supplier	 Atsushi Edayoshi Manager, Packaged Air Conditioners Quality Control Section MITSHUBISHI ELECTRIC CORPORATION SHIZUOKA WORKS
---	--

(1) This information is based on COMMISSION DELEGATED REGULATION (EU)No626/2011.

(2) SEER/SCOP values are measured based on FprEN 14825:2011: Testing and rating at part load conditions and calculation of seasonal performance.