

		For medium-temperature application.																				For low-temperature application.																							
1	2	3	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24		
Outdoor unit	Indoor unit	Medium-temperature application	Seasonal space heating energy efficiency class	Water heating energy efficiency class	Rated heat output under average climate conditions	For space heating, annual energy consumption under average climate conditions	For water heating, annual electricity consumption under average climate conditions	Seasonal space heating energy efficiency under average climate conditions	Water heating energy efficiency under average climate conditions	Sound power level L _{WA} indoor	Work only during off-peak hours	Rated heat output under colder climate conditions	Rated heat output under warmer climate conditions	For space heating, annual energy consumption under colder climate conditions	For space heating, annual energy consumption under warmer climate conditions	For water heating, annual energy consumption under colder climate conditions	For water heating, annual energy consumption under warmer climate conditions	Seasonal space heating energy efficiency under colder climate conditions	Seasonal space heating energy efficiency under warmer climate conditions	Water heating energy efficiency under colder climate conditions	Water heating energy efficiency under warmer climate conditions	Sound power level L _{WA} outdoor	Low-temperature application	Seasonal space heating energy efficiency class	Water heating energy efficiency class	Rated heat output under average climate conditions	For space heating, annual energy consumption under average climate conditions	For water heating, annual electricity consumption under average climate conditions	Seasonal space heating energy efficiency under average climate conditions	Water heating energy efficiency under average climate conditions	Sound power level L _{WA} indoor	Work only during off-peak hours	Rated heat output under colder climate conditions	Rated heat output under warmer climate conditions	For space heating, annual energy consumption under colder climate conditions	For space heating, annual energy consumption under warmer climate conditions	For water heating, annual energy consumption under colder climate conditions	For water heating, annual energy consumption under warmer climate conditions	Seasonal space heating energy efficiency under colder climate conditions	Seasonal space heating energy efficiency under warmer climate conditions	Water heating energy efficiency under colder climate conditions	Water heating energy efficiency under warmer climate conditions	Sound power level L _{WA} outdoor		
					kW	kWh	kWh	%	%	dB		kW	kW	kWh	kWh	kWh	kWh	%	%	%	%	dB				kW	kWh	kWh	%	%	dB		kW	kW	kWh	kWh	kWh	kWh	%	%	%	%	dB		
					A+	-	129.9	93223	-	112	-	-	-	200.4	68.2	199129	28227	-	-	96	126	-	-	83	✓	A+	-	143.0	89193	-	129	-	-	209.0	77.0	192947	25256	-	-	104	160	-	-	83	
					A+	-	129.9	93223	-	112	-	-	-	200.4	68.2	199129	28227	-	-	96	126	-	-	85	✓	A+	-	143.0	89193	-	129	-	-	209.0	77.0	192947	25256	-	-	104	160	-	-	85	
EAHV-M1500YCL(-N)(-BS)	-	✓	A+	-	129.9	93223	-	112	-	-	-	200.4	68.2	199129	28227	-	-	96	126	-	-	83	✓	A+	-	143.0	89193	-	129	-	-	209.0	77.0	192947	25256	-	-	104	160	-	-	83			
EAHV-M1800YCL(-N)(-BS)	-	✓	A+	-	129.9	93223	-	112	-	-	-	200.4	68.2	199129	28227	-	-	96	126	-	-	85	✓	A+	-	143.0	89193	-	129	-	-	209.0	77.0	192947	25256	-	-	104	160	-	-	85			
EAHV-M2000YCL(-N)(-BS)	-	✓	A+	-	147.5	107047	-	111	-	-	-	229.8	75.4	231772	31826	-	-	95	124	-	-	87	✓	A+	-	144.0	86151	-	135	-	-	209.9	77.3	201955	26809	-	-	99	151	-	-	87			

	English	Deutsch	Français	Italiano	Español
	Nederlands	Svenska	Dansk	Português	Ελληνικά
	suomi	Čeština	Български	Polski	-
1	Outdoor unit	Außengerät	unité extérieure	unità esterna	unidad exterior
	buitenunit	Utomhusenhet	Udendørs enhed	unidade exterior	Εξωτερική μονάδα
2	Indoor unit	Imnengerät	unité intérieure	unità interna	unidad interior
	binnenunit	Innomhusenhet	Indendørs enhed	unidade interior	Εσωτερική μονάδα
3	Medium-temperature application	Mitteltemperaturanwendung	l'application à moyenne température	le applicazioni a media temperatura	la aplicación de media temperatura
	midientemperatuur-toepassing	midientemperatuurapplicaton	midientemperatuurvendelsen	a aplicação a média temperatura	η εφαρμογή σε μέση θερμοκρασία
4	Low-temperature application	Niedertemperaturanwendung	l'application à basse température	le applicazioni a bassa temperatura	la aplicación de baja temperatura
	lagtemperatuur-toepassing	lagtemperaturapplikation	lavtemperaturavvendelsen	a aplicação a baixa temperatura	η εφαρμογή σε χαμηλή θερμοκρασία
5	Seasonal space heating energy efficiency class	die Klasse für die jahreszeitbedingte Raumheizungs-Energieeffizienz	la classe d'efficacité énergétique saisonnière, pour le chauffage des locaux	la classe di efficienza energetica stagionale del riscaldamento d'ambiente	la clase de eficiencia energética estacional de calefacción
	de seizoensgebonden energie-efficiëntieklasse voor ruimteverwarming	säsönsrelaterade energieeffektivitetsklass vid rumsuppvärmning	klassen for årsvirkningsgrad ved rumopvarmning	A classe de eficiência energética do aquecimento ambiente sazonal	η τάξη ενεργειακής απόδοσης της εποχιακής θέρμανσης χώρου
6	Water heating energy efficiency class	die Klasse für die Warmwasserbereitungs-Energieeffizienz	la classe d'efficacité énergétique, pour le chauffage de l'eau	la classe di efficienza energetica del riscaldamento dell'acqua	la clase de eficiencia energética del caldeo de agua
	de energie-efficiëntieklasse voor waterverwarming	energieeffektivitetsklass vid vattenuppvärmning	klassen for årsvirkningsgrad ved vandopvarmning	A classe de eficiência energética do aquecimento de água	η τάξη ενεργειακής απόδοσης θέρμανσης νερού
7	Rated heat output under average climate conditions	die Wärmenennleistung bei durchschnittlichen Klimaverhältnissen	la puissance thermique nominale dans les conditions climatiques moyennes	la potenza termica nominale(in condizioni climatiche medie)	la potencia calorífica nominal(en condiciones climáticas medias)
	de nominale warmteafgifte(onder gemiddelde klimaatomstandigheden)	Den nominelle avgivna värmeeffekten(under genomsnittliga klimatförhållanden)	den nominelle nytteeffekt(under gennemsnitlige klimaforhold)	A potência calorífica nominal(em condições climáticas médias)	η ονομαστική θερμική ισχύς(υπό μέσες κλιματικές συνθήκες)
8	For space heating, annual energy consumption under average climate conditions	für die Raumheizung, den jährlichen Energieverbrauch bei durchschnittlichen Klimaverhältnissen	pour le chauffage des locaux, la consommation annuelle d'énergie(dans les conditions climatiques moyennes)	per il riscaldamento d'ambiente, il consumo annuo di energia(in condizioni climatiche medie)	para calentar espacios, el consumo anual de energía(en condiciones climáticas medias)
	voor ruimteverwarming, het jaarlijkse energieverbruik(onder gemiddelde klimaatomstandigheden)	För rumsuppvärmning, årlig energiförbrukning(vid genomsnittliga klimatförhållanden)	for rumopvarmning det årlige energiforbrug(under gennemsnitlige klimaforhold)	Para o aquecimento ambiente, o consumo anual de energia(em condições climáticas médias)	για τη θέρμανση χώρου, η ετήσια κατανάλωση ενέργειας(υπό μέσες κλιματικές συνθήκες)
9	For water heating, annual electricity consumption under average climate conditions	für die Warmwasserbereitung, den jährlichen Stromverbrauch bei durchschnittlichen Klimaverhältnissen	pour le chauffage de l'eau, la consommation annuelle d'électricité(dans les conditions climatiques moyennes)	per il riscaldamento dell'acqua, il consumo annuo di energia(in condizioni climatiche medie)	para calentar agua, el consumo anual de electricidad(en condiciones climáticas medias)
	voor waterverwarming, het jaarlijkse elektriciteitsverbruik(onder gemiddelde klimaatomstandigheden)	För vattenuppvärmning, årlig elförbrukning(vid genomsnittliga klimatförhållanden)	for vandopvarmning det årlige elforbrug(under gennemsnitlige klimaforhold)	para o aquecimento de água, o consumo anual de electricidade(em condições climáticas médias)	για την θέρμανση νερού, η ετήσια κατανάλωση ηλεκτρικής ενέργειας(υπό μέσες κλιματικές συνθήκες)
10	Seasonal space heating energy efficiency under average climate conditions	die jahreszeitbedingte Raumheizungs-Energieeffizienz bei durchschnittlichen Klimaverhältnissen	l'efficacité énergétique saisonnière pour le chauffage des locaux(dans les conditions climatiques moyennes)	l'efficienza energetica stagionale di riscaldamento d'ambiente(in condizioni climatiche medie)	la eficiencia energética estacional de calefacción(en condiciones climáticas medias)
	de seizoensgebonden energie-efficiëntie voor ruimteverwarming(onder gemiddelde klimaatomstandigheden)	Säsönsmedelverkningsgrad för rumsuppvärmning(vid genomsnittliga klimatförhållanden)	årsvirkningsgraden ved rumopvarmning(under gennemsnitlige klimaforhold)	A eficiência energética do aquecimento ambiente sazonal(em condições climáticas médias)	η ενεργειακή απόδοση της εποχιακής θέρμανσης χώρου(υπό μέσες κλιματικές συνθήκες)
11	Water heating energy efficiency under average climate conditions	die Warmwasserbereitungs-Energieeffizienz bei durchschnittlichen Klimaverhältnissen	l'efficacité énergétique pour le chauffage de l'eau(dans les conditions climatiques moyennes)	l'efficienza energetica di riscaldamento dell'acqua(in condizioni climatiche medie)	la eficiencia energética del caldeo de agua(en condiciones climáticas medias)
	de energie-efficiëntie voor waterverwarming(onder gemiddelde klimaatomstandigheden)	Energieeffektivitet ved vattenuppvärmning(vid genomsnittliga klimatförhållanden)	energieeffektiviteten ved vandopvarmning(under gennemsnitlige klimaforhold)	a eficiência energética do aquecimento de água(em condições climáticas médias)	η ενεργειακή απόδοση θέρμανσης νερού(υπό μέσες κλιματικές συνθήκες)
12	Sound power level L _{WA} indoor	der Schalleistungspegel L _{WA} in Gebäuden	le niveau de puissance acoustique L _{WA} à l'intérieur	il livello di potenza sonora L _{WA} all'interno	el nivel de potencia acústica L _{WA} en interiores
	het geluidsvermogensniveau L _{WA} binnen	Ljudeffektivitá L _{WA} i inomhus	lydeeffektiviveauet L _{WA} i inde	O nível de potência sonora L _{WA} no interior	η στάθμη ηχητικής ισχύος L _{WA} εσωτερικού χώρου
13	Work only during off-peak hours	arbeiten ausschließlich während der Schwachlastzeiten	fonctionner qu'en heures creuses	funzionare soltanto durante le ore morte	funcionar solamente durante las horas de baja demanda
	werken uitsluitend in de daluren	drives uteslutende under perioder med låg belastning	fungere uden for spidsbelastningsperioder	de funcionar unicamente fora das horas de pico	λειτουργία μόνο εκτός των ωρών αιχμής
14	Rated heat output under colder climate conditions	die Wärmenennleistung bei kälteren Klimaverhältnissen	la puissance thermique nominale, dans les conditions climatiques plus froides	la potenza termica nominale, in condizioni climatiche più fredde	la potencia calorífica nominal en condiciones climáticas más frías
	de nominale warmteafgifte, onder koudere klimaatomstandigheden	Nominell avgiven värmeeffekt vid kallare klimatförhållanden	den nominelle nytteeffekt under koldere klimaforhold	A potência calorífica nominal em condições climáticas mais frias	η ονομαστική θερμική ισχύς υπό ψυχρότερες κλιματικές συνθήκες
15	Rated heat output under warmer climate conditions	die Wärmenennleistung bei wärmeren Klimaverhältnissen	la puissance thermique nominale, dans les conditions climatiques plus chaudes	la potenza termica nominale, in condizioni climatiche più calde	la potencia calorífica nominal en condiciones climáticas más cálidas
	de nominale warmteafgifte, onder warmere klimaatomstandigheden	Nominell avgiven värmeeffekt vid varmare klimatförhållanden	den nominelle nytteeffekt under varmere klimaforhold	A potência calorífica nominal em condições climáticas mais quentes	η ονομαστική θερμική ισχύς υπό θερμότερες κλιματικές συνθήκες
16	For space heating, annual energy consumption under colder climate conditions	für die Raumheizung, der jährliche Energieverbrauch bei kälteren Klimaverhältnissen	pour le chauffage des locaux, la consommation annuelle d'énergie, dans les conditions climatiques plus froides	per il riscaldamento d'ambiente, il consumo annuo di energia, in condizioni climatiche più fredde	para calentar espacios, el consumo anual de energía en condiciones climáticas más frías
	voor ruimteverwarming, het jaarlijkse energieverbruik onder koudere klimaatomstandigheden	För rumsuppvärmning, årlig energiförbrukning under kallare klimatförhållanden	for rumopvarmning det årlige energiforbrug under koldere klimaforhold	Para o aquecimento ambiente, o consumo anual de energia em condições climáticas mais frias	για θέρμανση χώρου, η ετήσια κατανάλωση ενέργειας υπό ψυχρότερες κλιματικές συνθήκες
17	For space heating, annual energy consumption under warmer climate conditions	für die Raumheizung, der jährliche Energieverbrauch bei wärmeren Klimaverhältnissen	pour le chauffage des locaux, la consommation annuelle d'énergie, dans les conditions climatiques plus chaudes	per il riscaldamento d'ambiente, il consumo annuo di energia, in condizioni climatiche più calde	para calentar espacios, el consumo anual de energía en condiciones climáticas más cálidas
	voor ruimteverwarming, het jaarlijkse energieverbruik onder warmere klimaatomstandigheden	För rumsuppvärmning, årlig energiförbrukning under varmare klimatförhållanden	for rumopvarmning det årlige energiforbrug under varmere klimaforhold	Para o aquecimento ambiente, o consumo anual de energia em condições climáticas mais quentes	για θέρμανση χώρου, η ετήσια κατανάλωση ενέργειας υπό θερμότερες κλιματικές συνθήκες
18	For water heating, annual energy consumption under colder climate conditions	für die Warmwasserbereitung, der jährliche Stromverbrauch bei kälteren Klimaverhältnissen	pour le chauffage de l'eau, la consommation annuelle d'électricité, dans les conditions climatiques plus froides	per il riscaldamento dell'acqua, il consumo annuo di energia, in condizioni climatiche più fredde e più calde	para calentar agua, el consumo anual de electricidad en condiciones climáticas más frías
	voor waterverwarming, het jaarlijkse elektriciteitsverbruik onder koudere klimaatomstandigheden	För vattenuppvärmning, årlig elförbrukning under kallare klimatförhållanden	for vandopvarmning det årlige elforbrug under koldere klimaforhold	para o aquecimento de água, o consumo anual de electricidade em condições climáticas mais frias	για θέρμανση νερού, η ετήσια κατανάλωση ηλεκτρικής ενέργειας υπό ψυχρότερες κλιματικές συνθήκες
19	For water heating, annual energy consumption under warmer climate conditions	für die Warmwasserbereitung, der jährliche Stromverbrauch bei wärmeren Klimaverhältnissen	pour le chauffage de l'eau, la consommation annuelle d'électricité, dans les conditions climatiques plus chaudes	per il riscaldamento dell'acqua, il consumo annuo di energia, in condizioni climatiche più fredde e più calde	para calentar agua, el consumo anual de electricidad en condiciones climáticas más cálidas
	voor waterverwarming, het jaarlijkse elektriciteitsverbruik onder warmere klimaatomstandigheden	För vattenuppvärmning, årlig elförbrukning under varmare klimatförhållanden	for vandopvarmning det årlige elforbrug under varmere klimaforhold	para o aquecimento de água, o consumo anual de electricidade em condições climáticas mais quentes	για θέρμανση νερού, η ετήσια κατανάλωση ηλεκτρικής ενέργειας υπό θερμότερες κλιματικές συνθήκες
20	Seasonal space heating energy efficiency under colder climate conditions	die jahreszeitbedingte Raumheizungs-Energieeffizienz bei kälteren Klimaverhältnissen	l'efficacité énergétique saisonnière pour le chauffage des locaux, dans les conditions climatiques plus froides	l'efficienza energetica stagionale di riscaldamento d'ambiente in condizioni climatiche più fredde	la eficiencia energética estacional de calefacción en condiciones climáticas más frías
	de seizoensgebonden energie-efficiëntie voor ruimteverwarming onder koudere klimaatomstandigheden	Säsönsmedelverkningsgrad för rumsuppvärmning under kallare klimatförhållanden	årsvirkningsgraden ved rumopvarmning under koldere klimaforhold	A eficiência energética do aquecimento ambiente sazonal em condições climáticas mais frias	η ενεργειακή απόδοση της εποχιακής θέρμανσης χώρου υπό ψυχρότερες κλιματικές συνθήκες
21	Seasonal space heating energy efficiency under warmer climate conditions	die jahreszeitbedingte Raumheizungs-Energieeffizienz bei wärmeren Klimaverhältnissen	l'efficacité énergétique saisonnière pour le chauffage des locaux, dans les conditions climatiques plus chaudes	l'efficienza energetica stagionale di riscaldamento d'ambiente in condizioni climatiche più calde	la eficiencia energética estacional de calefacción en condiciones climáticas más cálidas
	de seizoensgebonden energie-efficiëntie voor ruimteverwarming onder warmere klimaatomstandigheden	Säsönsmedelverkningsgrad för rumsuppvärmning under varmare klimatförhållanden	årsvirkningsgraden ved rumopvarmning under varmere klimaforhold	A eficiência energética do aquecimento ambiente sazonal em condições climáticas mais quentes	η ενεργειακή απόδοση της εποχιακής θέρμανσης χώρου υπό θερμότερες κλιματικές συνθήκες
22	Water heating energy efficiency under colder climate conditions	die Warmwasserbereitungs-Energieeffizienz bei kälteren Klimaverhältnissen	l'efficacité énergétique pour le chauffage de l'eau, dans les conditions climatiques plus froides	l'efficienza energetica di riscaldamento dell'acqua in condizioni climatiche più fredde	la eficiencia energética de caldeo de agua en condiciones climáticas más frías
	de energie-efficiëntie voor waterverwarming onder koudere klimaatomstandigheden	Energieeffektivitet ved vattenuppvärmning under kallare klimatförhållanden	energieeffektiviteten ved vandopvarmning under koldere klimaforhold	a eficiência energética do aquecimento de água em condições climáticas mais frias	η ενεργειακή απόδοση της θέρμανσης νερού υπό ψυχρότερες κλιματικές συνθήκες
23	Water heating energy efficiency under warmer climate conditions	die Warmwasserbereitungs-Energieeffizienz bei wärmeren Klimaverhältnissen	l'efficacité énergétique pour le chauffage de l'eau, dans les conditions climatiques plus chaudes	l'efficienza energetica di riscaldamento dell'acqua in condizioni climatiche più calde	la eficiencia energética de caldeo de agua en condiciones climáticas más cálidas
	de energie-efficiëntie voor waterverwarming onder warmere klimaatomstandigheden	Energieeffektivitet ved vattenuppvärmning under varmare klimatförhållanden	energieeffektiviteten ved vandopvarmning under varmere klimaforhold	a eficiência energética do aquecimento de água em condições climáticas mais quentes	η ενεργειακή απόδοση της θέρμανσης νερού υπό θερμότερες κλιματικές συνθήκες
24	Sound power level L _{WA} outdoor	der Schalleistungspegel L _{WA} im Freien	le niveau de puissance acoustique L _{WA} à l'extérieur	il livello di potenza sonora L _{WA} all'esterno	el nivel de potencia acústica L _{WA} en exteriores
	het geluidsvermogensniveau L _{WA} buiten	Ljudeffektivitá L _{WA} i utomhus	lydeeffektiviveauet L _{WA} i ude	O nível de potência sonora L _{WA} na exterior	η στάθμη ηχητικής ισχύος L _{WA} εξωτερικού χώρου

Model(s):	Outdoor unit:	EAHV-M2000YCL (-N) (-BS)
	Indoor unit:	-
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		no
Heat pump combination heater:		no
Parameters for		low-temperature application.
Parameters for		average climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	144.0	kW	Seasonal space heating energy efficiency	η_s	135	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj= - 7 °C	Pdh	127.4	kW	Tj= - 7 °C	COPd	2.56	-
Degradation co-efficient (**)	Cdh	0.9	-				
Tj= + 2 °C	Pdh	77.4	kW	Tj= + 2 °C	COPd	3.11	-
Degradation co-efficient (**)	Cdh	0.9	-				
Tj= + 7 °C	Pdh	49.8	kW	Tj= + 7 °C	COPd	4.48	-
Degradation co-efficient (**)	Cdh	0.9	-				
Tj= +12 °C	Pdh	22.3	kW	Tj= +12 °C	COPd	6.20	-
Degradation co-efficient (**)	Cdh	0.9	-				
Tj= bivalent temperature	Pdh	127.4	kW	Tj= bivalent temperature	COPd	2.56	-
Tj= operation limit temperature	Pdh	120.2	kW	Tj= operation limit temperature	COPd	2.43	-
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Bivalent temperature	Tbiv	-7	°C	Operation limit temperature	TOL	-10	°C
				Heating water operating limit temperature	WTOL	55	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.209	kW	Rated heat output (*)	Psup	144.0	kW
Thermostat-off mode	P _{TO}	0.426	kW				
Standby mode	P _{SB}	0.209	kW	Type of energy input			
Crankcase heater mode	P _{CK}	0.209	kW				

Other items							
Capacity control	Variable			Rated air flow rate, outdoor	-	64800	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-/87	dBA				
Annual energy consumption	Q _{HE}	86151	kWh				

For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Qelec	-	kW/h				
Annual electricity consumption	AEC	-	kW/h				

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS	5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan
--	--

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Model(s):	Outdoor unit:	EAHV-M2000VCL (-N) (-BS)
	Indoor unit:	—
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		no
Heat pump combination heater:		no
Parameters for		low-temperature application.
Parameters for		colder climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	209.9	kW	Seasonal space heating energy efficiency	η_s	99	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj= - 7 °C	Pdh	127.0	kW	Tj= - 7 °C	COPd	2.49	—
Degradation co-efficient (**)	Cdh	0.9	—				
Tj= + 2 °C	Pdh	77.3	kW	Tj= + 2 °C	COPd	2.88	—
Degradation co-efficient (**)	Cdh	0.9	—				
Tj= + 7 °C	Pdh	49.7	kW	Tj= + 7 °C	COPd	3.63	—
Degradation co-efficient (**)	Cdh	0.9	—				
Tj= +12 °C	Pdh	22.2	kW	Tj= +12 °C	COPd	4.38	—
Degradation co-efficient (**)	Cdh	0.9	—				
Tj= bivalent temperature	Pdh	127.0	kW	Tj= bivalent temperature	COPd	2.49	—
Tj= operation limit temperature	Pdh	92.3	kW	Tj= operation limit temperature	COPd	1.98	—
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	—	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	—	—
Bivalent temperature	Tbiv	-7	°C	Operation limit temperature	TOL	-20	°C
				Heating water operating limit temperature	WTOL	55	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.209	kW	Rated heat output (*)	Psup	209.9	kW
Thermostat-off mode	P _{TO}	0.426	kW				
Standby mode	P _{SB}	0.209	kW	Type of energy input			
Crankcase heater mode	P _{CK}	0.209	kW				

Other items							
Capacity control	Variable			Rated air flow rate, outdoor	—	64800	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-/87	dBA				
Annual energy consumption	Q _{HE}	201955	kWh				

For heat pump combination heater:							
Declared load profile	—			Water heating energy efficiency	η_{wh}	—	%
Daily electricity consumption	Q _{elec}	—	kW/h				
Annual electricity consumption	AEC	—	kW/h				

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

Model(s):	Outdoor unit:	EAHV-M2000VCL (-N) (-BS)
	Indoor unit:	-
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		no
Heat pump combination heater:		no
Parameters for		low-temperature application.
Parameters for		warmer climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	77.3	kW	Seasonal space heating energy efficiency	η_s	151	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj= - 7 °C	Pdh	-	kW	Tj= - 7 °C	COPd	-	-
Degradation co-efficient (**)	Cdh	-	-				
Tj= + 2 °C	Pdh	77.3	kW	Tj= + 2 °C	COPd	2.88	-
Degradation co-efficient (**)	Cdh	0.9	-				
Tj= + 7 °C	Pdh	49.7	kW	Tj= + 7 °C	COPd	3.63	-
Degradation co-efficient (**)	Cdh	0.9	-				
Tj= +12 °C	Pdh	22.2	kW	Tj= +12 °C	COPd	4.38	-
Degradation co-efficient (**)	Cdh	0.9	-				
Tj= bivalent temperature	Pdh	-	kW	Tj= bivalent temperature	COPd	-	-
Tj= operation limit temperature	Pdh	92.3	kW	Tj= operation limit temperature	COPd	1.98	-
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Bivalent temperature	Tbiv	-7	°C	Operation limit temperature	TOL	2	°C
				Heating water operating limit temperature	WTOL	55	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.209	kW	Rated heat output (*)	Psup	77.3	kW
Thermostat-off mode	P _{TO}	0.426	kW				
Standby mode	P _{SB}	0.209	kW	Type of energy input			
Crankcase heater mode	P _{CK}	0.209	kW				

Other items				Rated air flow rate, outdoor			
Capacity control	Variable			-	64800	m ³ /h	
Sound power level, indoors/outdoors	L _{WA}	-/87	dBA				
Annual energy consumption	Q _{HE}	26809	kWh				

For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	-			η_{wh}	-	%	
Daily electricity consumption	Q _{elec}	-	kW/h				
Annual electricity consumption	AEC	-	kW/h				

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Model(s):	Outdoor unit:	EAHV-M2000VCL (-N) (-BS)
	Indoor unit:	-
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		no
Heat pump combination heater:		no
Parameters for		medium-temperature application.
Parameters for		average climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	147.5	kW	Seasonal space heating energy efficiency	η_s	111	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj= - 7 °C	Pdh	130.5	kW	Tj= - 7 °C	COPd	1.96	-
Degradation co-efficient (**)	Cdh	0.9	-				
Tj= + 2 °C	Pdh	79.5	kW	Tj= + 2 °C	COPd	2.62	-
Degradation co-efficient (**)	Cdh	0.9	-				
Tj= + 7 °C	Pdh	51.1	kW	Tj= + 7 °C	COPd	3.70	-
Degradation co-efficient (**)	Cdh	0.9	-				
Tj= +12 °C	Pdh	22.7	kW	Tj= +12 °C	COPd	5.22	-
Degradation co-efficient (**)	Cdh	0.9	-				
Tj= bivalent temperature	Pdh	130.5	kW	Tj= bivalent temperature	COPd	1.96	-
Tj= operation limit temperature	Pdh	124.5	kW	Tj= operation limit temperature	COPd	1.88	-
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Bivalent temperature	Tbiv	-7	°C	Operation limit temperature	TOL	-10	°C
				Heating water operating limit temperature	WTOL	55	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.209	kW	Rated heat output (*)	Psup	147.5	kW
Thermostat-off mode	P _{TO}	0.426	kW				
Standby mode	P _{SB}	0.209	kW	Type of energy input			
Crankcase heater mode	P _{CK}	0.209	kW				

Other items							
Capacity control	Variable			Rated air flow rate, outdoor	-	64800	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	-/87	dBA				
Annual energy consumption	Q _{HE}	107047	kWh				

For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Q _{elec}	-	kW/h				
Annual electricity consumption	AEC	-	kW/h				

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Model(s):	Outdoor unit:	EAHV-M2000YCL(-N) (-BS)
	Indoor unit:	-
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		no
Heat pump combination heater:		no
Parameters for		medium-temperature application.
Parameters for		colder climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	229.8	kW	Seasonal space heating energy efficiency	η_s	95	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj= - 7 °C	Pdh	139.1	kW	Tj= - 7 °C	COPd	2.19	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= + 2 °C	COPd	2.81	-
Tj= + 2 °C	Pdh	84.7	kW	Tj= + 7 °C	COPd	3.96	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= +12 °C	COPd	5.45	-
Tj= + 7 °C	Pdh	54.5	kW	Tj= bivalent temperature	COPd	2.19	-
Degradation co-efficient (**)	Cdh	0.9	-	Tj= operation limit temperature	COPd	1.72	-
Tj= +12 °C	Pdh	24.3	kW	Tj = - 15 °C (if TOL < - 20 °)	COPd	-	-
Degradation co-efficient (**)	Cdh	0.9	-	Operation limit temperature	TOL	-20	°C
Tj= bivalent temperature	Pdh	139.1	kW	Heating water operating limit temperature	WTOL	55	°C
Tj= operation limit temperature	Pdh	100.0	kW	Supplementary heater			
Tj = - 15 °C (if TOL < - 20 °)	Pdh	-	kW	Rated heat output (*)	Psup	229.8	kW
Bivalent temperature	Tbiv	-7	°C	Type of energy input			
Power consumption in modes other than active mode							
Off mode	P _{OFF}	0.209	kW				
Thermostat-off mode	P _{TO}	0.426	kW				
Stanby mode	P _{SB}	0.209	kW				
Crankcase heater mode	P _{CK}	0.209	kW				

Other items							
Capacity control	Variable			Rated air flow rate, outdoor	-	64800	m³/h
Sound power level, indoors/outdoors	L _{WA}	-/87	dBA				
Annual energy consumption	Q _{HE}	231772	kWh				

For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Q _{elec}	-	kW/h				
Annual electricity consumption	AEC	-	kW/h				

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS
 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).
 (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Model(s):	Outdoor unit:	EAHV-M2000VCL (-N) (-BS)
	Indoor unit:	-
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		no
Heat pump combination heater:		no
Parameters for		medium-temperature application.
Parameters for		warmer climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	75.4	kW	Seasonal space heating energy efficiency	η_s	124	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj= -7 °C	Pdh	-	kW	Tj= -7 °C	COPd	-	-
Degradation co-efficient (**)	Cdh	-	-				
Tj= +2 °C	Pdh	75.5	kW	Tj= +2 °C	COPd	1.89	-
Degradation co-efficient (**)	Cdh	0.9	-				
Tj= +7 °C	Pdh	48.6	kW	Tj= +7 °C	COPd	2.81	-
Degradation co-efficient (**)	Cdh	0.9	-				
Tj= +12 °C	Pdh	21.7	kW	Tj= +12 °C	COPd	4.47	-
Degradation co-efficient (**)	Cdh	0.9	-				
Tj= bivalent temperature	Pdh	-	kW	Tj= bivalent temperature	COPd	-	-
Tj= operation limit temperature	Pdh	124.5	kW	Tj= operation limit temperature	COPd	1.81	-
Tj = -15 °C (if TOL < -20 °C)	Pdh	-	kW	Tj = -15 °C (if TOL < -20 °C)	COPd	-	-
Bivalent temperature	Tbiv	-7	°C	Operation limit temperature	TOL	2	°C
				Heating water operating limit temperature	WTOL	55	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.209	kW	Rated heat output (*)	Psup	75.4	kW
Thermostat-off mode	P _{TO}	0.426	kW				
Standby mode	P _{SB}	0.209	kW	Type of energy input			
Crankcase heater mode	P _{CK}	0.209	kW				

Other items				Rated air flow rate, outdoor			
Capacity control	Variable			-	64800	m ³ /h	
Sound power level, indoors/outdoors	L _{WA}	-/87	dBA				
Annual energy consumption	Q _{HE}	31826	kWh				

For heat pump combination heater:

Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Q _{elec}	-	kW/h				
Annual electricity consumption	AEC	-	kW/h				

Contact details

MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66, Tebira, 6-Chome, Wakayama City 640-8686, Japan

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.