

Information requirements for comfort chillers

Model(s): Information to identify the model(s) to which the information relates:

EACV-M1800YCL(-N)(-BS)

Outdoor side heat exchanger of chiller: air

Indoor side heat exchanger chiller: water

Type: compressor driven vapour compression

if applicable: driver of compressor: electric motor

Information requirements for high temperature process chillers

Information to identify the model(s) to which the information relates:			
EACV-M1800YCL(-N)(-BS)			
Type of condensing: air-cooled			
Refrigerant fluid(s):R32			
Item	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	6.36	[-]
Annual electricity consumption	Q	206223	kWh/a
Parameters at full load and reference ambient temperature at ration point A			
Rated refrigeration capacity	P _A	178.80	kW
Rated power input	D _A	58.22	kW
Rated energy efficiency ratio	EER _{DC,A}	3.07	[-]
Parameters at rating point B			
Declared refrigeration capacity	P _B	166.88	kW
Declared power input	D _B	39.05	kW
Declared energy efficiency ratio	EER _{DC,B}	4.27	[-]
Parameters at rating point C			
Declared refrigeration capacity	P _C	154.96	kW
Declared power input	D _C	26.50	kW
Declared energy efficiency ratio	EER _{DC,C}	5.85	[-]
Parameters at rating point D			
Declared refrigeration capacity	P _D	143.04	kW
Declared power input	D _D	17.12	kW
Declared energy efficiency ratio	EER _{DC,D}	8.36	[-]
Other items			
Capacity control	Variable		
Degradation co-efficient chillers*	C _{dc}	0.9	[-]
GWP of the refrigerant		675	kg CO ₂ eq (100years)
Contact details	MITSUBISHI ELECTRIC CORPORATION AIR-CONDITIONING & REFRIGERATION SYSTEMS WORKS 5-66,Tebira 6 Chome,Wakayama-City 640-8686,Japan		

* If Cdc is not determined by measurement then the default degradation coefficient of chillers shall be 0,9.