

| Ⓐ Model | Ⓑ Cooling Capacity (kW) | | Ⓔ Heating Capacity (kW) P _{rated, h} | Ⓕ Total electric power input (kW) P _{elec} | Ⓖ Sound power level (per speed setting, if applicable) (dBA) L _{WA} |
|------------------|----------------------------------|--------------------------------|--|--|---|
| | Ⓒ Sensible P _{rated, c} | Ⓓ Latent P _{rated, c} | | | |
| PEFY-WL40VMHS-A | 3.60 | 0.90 | 5.00 | 0.055 | 51 - 49 - 48 |
| PEFY-WL50VMHS-A | 4.50 | 1.10 | 6.30 | 0.077 | 54 - 51 - 51 |
| PEFY-WL63VMHS-A | 5.30 | 1.80 | 8.00 | 0.095 | 55 - 54 - 53 |
| PEFY-WL71VMHS-A | 6.10 | 1.90 | 9.00 | 0.075 | 56 - 55 - 54 |
| PEFY-WL80VMHS-A | 6.80 | 2.20 | 10.00 | 0.090 | 57 - 56 - 56 |
| PEFY-WL100VMHS-A | 9.20 | 2.00 | 12.00 | 0.160 | 60 - 58 - 58 |
| PEFY-WL125VMHS-A | 10.60 | 3.40 | 16.00 | 0.160 | 61 - 60 - 60 |

(EU)2016/2281