

Ⓐ Model	Ⓑ Cooling Capacity (kW)		Ⓔ Heating Capacity (kW) P _{rated, h}	Ⓕ Total electric power input (kW) P _{elec}	Ⓖ Sound power level (per speed setting, if applicable) (dBA) L _{WA}
	Ⓒ Sensible P _{rated, c}	Ⓓ Latent P _{rated, c}			
PEAD-M35JA2	3.06	0.54	4.10	0.05	54 - 52 - 50
PEAD-M50JA2	4.20	0.80	6.00	0.07	58 - 57 - 54
PEAD-M60JA2	5.06	1.04	7.00	0.08	56 - 54 - 52
PEAD-M71JA2	5.68	1.42	8.00	0.09	58 - 56 - 54
PEAD-M100JA2	7.79	1.71	11.20	0.14	62 - 60 - 59
PEAD-M125JA2	9.75	2.75	14.00	0.20	66 - 65 - 63
PEAD-M140JA2	10.32	3.08	16.00	0.21	66 - 65 - 63
PEAD-M35JAL2	3.06	0.54	4.10	0.05	54 - 52 - 50
PEAD-M50JAL2	4.20	0.80	6.00	0.07	58 - 57 - 54
PEAD-M60JAL2	5.06	1.04	7.00	0.08	56 - 54 - 52
PEAD-M71JAL2	5.68	1.42	8.00	0.09	58 - 56 - 54
PEAD-M100JAL2	7.79	1.71	11.20	0.14	62 - 60 - 59
PEAD-M125JAL2	9.75	2.75	14.00	0.20	66 - 65 - 63
PEAD-M140JAL2	10.32	3.08	16.00	0.21	66 - 65 - 63
PEAD-SM35JA	3.06	0.54	4.10	0.05	54 - 52 - 50
PEAD-SM50JA	4.20	0.80	6.00	0.07	58 - 57 - 54
PEAD-SM60JA	5.06	1.04	7.00	0.08	56 - 54 - 52
PEAD-SM71JA2	5.68	1.42	8.00	0.09	58 - 56 - 54
PEAD-SM100JA2	7.79	1.71	11.20	0.14	62 - 60 - 59
PEAD-SM125JA2	9.75	2.75	14.00	0.20	66 - 65 - 63
PEAD-SM140JA2	10.32	3.08	16.00	0.21	66 - 65 - 63
PEAD-SM35JAL	3.06	0.54	4.10	0.05	54 - 52 - 50
PEAD-SM50JAL	4.20	0.80	6.00	0.07	58 - 57 - 54
PEAD-SM60JAL	5.06	1.04	7.00	0.08	56 - 54 - 52
PEAD-SM71JAL2	5.68	1.42	8.00	0.09	58 - 56 - 54
PEAD-SM100JAL2	7.79	1.71	11.20	0.14	62 - 60 - 59
PEAD-SM125JAL2	9.75	2.75	14.00	0.20	66 - 65 - 63
PEAD-SM140JAL2	10.32	3.08	16.00	0.21	66 - 65 - 63

(EU)2016/2281