



ENERG

енергия · ενεργεια



Indoor unit EHST20C-**C(W)
Outdoor unit PUHZ-FRP71VHA2



A+++

A++

A+

A

B

C

D

A+



A+

A

B

C

D

E

F

A



40 dB



68 dB



04 kW

08 kW

08 kW

2019

811/2013

RG79Y768K02



		For medium-temperature application.																						For low-temperature application.																			
1	2	3	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
Outdoor unit	Indoor unit	Medium-temperature application	Seasonal space heating energy efficiency class	Water heating energy efficiency class	Rated heat output under average climate conditions	For space heating, annual energy consumption under average climate conditions	For water heating, annual electricity consumption under average climate conditions	Seasonal space heating energy efficiency under average climate conditions	Water heating energy efficiency under average climate conditions	Sound power level L _{wa} indoor	Work only during off-peak hours	Rated heat output under colder climate conditions	Rated heat output under warmer climate conditions	For space heating, annual energy consumption under colder climate conditions	For space heating, annual energy consumption under warmer climate conditions	For water heating, annual energy consumption under colder climate conditions	For water heating, annual energy consumption under warmer climate conditions	Seasonal space heating energy efficiency under colder climate conditions	Seasonal space heating energy efficiency under warmer climate conditions	Water heating energy efficiency under colder climate conditions	Water heating energy efficiency under warmer climate conditions	Sound power level L _{wa} outdoor	Low-temperature application	Seasonal space heating energy efficiency class	Water heating energy efficiency class	Rated heat output under average climate conditions	For space heating, annual energy consumption under average climate conditions	For water heating, annual electricity consumption under average climate conditions	Seasonal space heating energy efficiency under average climate conditions	Water heating energy efficiency under average climate conditions	Sound power level L _{wa} indoor	Work only during off-peak hours	Rated heat output under colder climate conditions	Rated heat output under warmer climate conditions	For space heating, annual energy consumption under colder climate conditions	For space heating, annual energy consumption under warmer climate conditions	For water heating, annual electricity consumption under colder climate conditions	For water heating, annual energy consumption under warmer climate conditions	Seasonal space heating energy efficiency under colder climate conditions	Seasonal space heating energy efficiency under warmer climate conditions	Water heating energy efficiency under colder climate conditions	Water heating energy efficiency under warmer climate conditions	Sound power level L _{wa} outdoor
PUHZ-FRP71VHA2	EHST20C-VM2C	✓	A+	A	7.5	4923	1055	121	98	40	-	4.4	7.5	4668	2595	1352	956	98	150	80	110	68	✓	A++	A	7.5	3667	1055	163	98	40	-	4.4	7.5	3554	1722	1352	956	134	226	80	110	68
	EHST20C-VM6C	✓	A+	A	7.5	4923	1055	121	98	40	-	4.4	7.5	4668	2595	1352	956	98	150	80	110	68	✓	A++	A	7.5	3667	1055	163	98	40	-	4.4	7.5	3554	1722	1352	956	134	226	80	110	68
	EHST20C-TM9C	✓	A+	A	7.5	4923	1055	121	98	40	-	4.4	7.5	4668	2595	1352	956	98	150	80	110	68	✓	A++	A	7.5	3667	1055	163	98	40	-	4.4	7.5	3554	1722	1352	956	134	226	80	110	68
	EHST20C-VM2EC	✓	A+	A	7.5	4923	1055	121	98	40	-	4.4	7.5	4668	2595	1352	956	98	150	80	110	68	✓	A++	A	7.5	3667	1055	163	98	40	-	4.4	7.5	3554	1722	1352	956	134	226	80	110	68
	EHST20C-VM6EC	✓	A+	A	7.5	4923	1055	121	98	40	-	4.4	7.5	4668	2595	1352	956	98	150	80	110	68	✓	A++	A	7.5	3667	1055	163	98	40	-	4.4	7.5	3554	1722	1352	956	134	226	80	110	68
	EHST20C-TM9EC	✓	A+	A	7.5	4923	1055	121	98	40	-	4.4	7.5	4668	2595	1352	956	98	150	80	110	68	✓	A++	A	7.5	3667	1055	163	98	40	-	4.4	7.5	3554	1722	1352	956	134	226	80	110	68
	EHST20C-MEC	✓	A+	A	7.5	4923	1055	121	98	40	-	4.4	7.5	4668	2595	1352	956	98	150	80	110	68	✓	A++	A	7.5	3667	1055	163	98	40	-	4.4	7.5	3554	1722	1352	956	134	226	80	110	68
	EHST20C-MHCW	✓	A+	A	7.5	4923	1055	121	98	40	-	4.4	7.5	4668	2595	1352	956	98	150	80	110	68	✓	A++	A	7.5	3667	1055	163	98	40	-	4.4	7.5	3554	1722	1352	956	134	226	80	110	68
	EHSC-VM2C	✓	A+	-	7.5	4923	-	121	-	40	-	4.4	7.5	4668	2595	-	-	98	150	-	-	68	✓	A++	-	7.5	3667	-	163	-	40	-	4.4	7.5	3554	1722	-	-	134	226	-	-	68
	EHSC-VM2EC	✓	A+	-	7.5	4923	-	121	-	40	-	4.4	7.5	4668	2595	-	-	98	150	-	-	68	✓	A++	-	7.5	3667	-	163	-	40	-	4.4	7.5	3554	1722	-	-	134	226	-	-	68
	EHSC-VM6C	✓	A+	-	7.5	4923	-	121	-	40	-	4.4	7.5	4668	2595	-	-	98	150	-	-	68	✓	A++	-	7.5	3667	-	163	-	40	-	4.4	7.5	3554	1722	-	-	134	226	-	-	68
	EHSC-VM6EC	✓	A+	-	7.5	4923	-	121	-	40	-	4.4	7.5	4668	2595	-	-	98	150	-	-	68	✓	A++	-	7.5	3667	-	163	-	40	-	4.4	7.5	3554	1722	-	-	134	226	-	-	68
	EHSC-YM9C	✓	A+	-	7.5	4923	-	121	-	40	-	4.4	7.5	4668	2595	-	-	98	150	-	-	68	✓	A++	-	7.5	3667	-	163	-	40	-	4.4	7.5	3554	1722	-	-	134	226	-	-	68
	EHSC-YM9EC	✓	A+	-	7.5	4923	-	121	-	40	-	4.4	7.5	4668	2595	-	-	98	150	-	-	68	✓	A++	-	7.5	3667	-	163	-	40	-	4.4	7.5	3554	1722	-	-	134	226	-	-	68
	EHSC-TM9C	✓	A+	-	7.5	4923	-	121	-	40	-	4.4	7.5	4668	2595	-	-	98	150	-	-	68	✓	A++	-	7.5	3667	-	163	-	40	-	4.4	7.5	3554	1722	-	-	134	226	-	-	68
	EHSC-MEC	✓	A+	-	7.5	4923	-	121	-	40	-	4.4	7.5	4668	2595	-	-	98	150	-	-	68	✓	A++	-	7.5	3667	-	163	-	40	-	4.4	7.5	3554	1722	-	-	134	226	-	-	68
	EHST20C-VM2D	✓	A+	A+	7.5	4923	786	121	138	40	-	4.4	7.5	4668	2595	893	698	98	150	121	156	68	✓	A++	A+	7.5	3667	786	163	138	40	-	4.4	7.5	3554	1722	893	698	134	226	121	156	68
	EHST20C-VM6D	✓	A+	A+	7.5	4923	786	121	138	40	-	4.4	7.5	4668	2595	893	698	98	150	121	156	68	✓	A++	A+	7.5	3667	786	163	138	40	-	4.4	7.5	3554	1722	893	698	134	226	121	156	68
	EHST20C-TM9D	✓	A+	A+	7.5	4923	786	121	138	40	-	4.4	7.5	4668	2595	893	698	98	150	121	156	68	✓	A++	A+	7.5	3667	786	163	138	40	-	4.4	7.5	3554	1722	893	698	134	226	121	156	68
	EHST20C-TM9ED	✓	A+	A+	7.5	4923	786	121	138	40	-	4.4	7.5	4668	2595	893	698	98	150	121	156	68	✓	A++	A+	7.5	3667	786	163	138	40	-	4.4	7.5	3554	1722	893	698	134	226	121	156	68
	EHST20C-MED	✓	A+	A+	7.5	4923	786	121	138	40	-	4.4	7.5	4668	2595	893	698	98	150	121	156	68	✓	A++	A+	7.5	3667	786	163	138	40	-	4.4	7.5	3554	1722	893	698	134	226	121	156	68
	EHSC-VM2D	✓	A+	-	7.5	4923	-	121	-	40	-	4.4	7.5	4668	2595	-	-	98	150	-	-	68	✓	A++	-	7.5	3667	-	163	-	40	-	4.4	7.5	3554	1722	-	-	134	226	-	-	68
	EHSC-VM6D	✓	A+	-	7.5	4923	-	121	-	40	-	4.4	7.5	4668	2595	-	-	98	150	-	-	68	✓	A++	-	7.5	3667	-	163	-	40	-	4.4	7.5	3554	1722	-	-	134	226	-	-	68
	EHSC-YM9D	✓	A+	-	7.5	4923	-	121	-	40	-	4.4	7.5	4668	2595	-	-	98	150	-	-	68	✓	A++	-	7.5	3667	-	163	-	40	-	4.4	7.5	3554	1722	-	-	134	226	-	-	68
	EHSC-YM9ED	✓	A+	-	7.5	4923	-	121	-	40	-	4.4	7.5	4668	2595	-	-	98	150	-	-	68	✓	A++	-	7.5	3667	-	163	-	40	-	4.4	7.5	3554	1722	-	-	134	226	-	-	68
	EHSC-TM9D	✓	A+	-	7.5	4923	-	121	-	40	-	4.4	7.5	4668	2595	-	-	98	150	-	-	68	✓	A++	-	7.5	3667	-	163	-	40	-	4.4	7.5	3554	1722	-	-	134	226	-	-	68
	EHSC-MED	✓	A+	-	7.5	4923	-	121	-	40	-	4.4	7.5	4668	2595	-	-	98	150	-	-	68	✓	A++	-	7.5	3667	-	163	-	40	-	4.4	7.5	3554	1722	-	-	134	226	-	-	68

	English	Deutsch	Français	Italiano	Español
	Netherlands	Svenska	Dansk	Português	Ελληνικά
	Suomi	Čeština	Български	Polski	-
	Outdoor unit	Außengerät	Unité extérieure	unità esterna	-
1	buiterunit	Utomhusenhet	Utdensers enhed	unidad exterior	Εξωτερική μονάδα
	Ulkoyksikkö	Venkovni jednotka	Вышнее тело	jednostka zewnętrzna	-
	indoor unit	Innengerät	Unité intérieure	unità interna	unidad interior
2	binenunit	Innenset	Indensers enhed	unidad interior	Εσωτερική μονάδα
	Sisäyksikkö	Vnitřní jednotka	Внутреннее тело	jednostka wewnętrzna	-
3	Medium-temperature application	Mitteltemperaturanwendung	l'application à moyenne température	le aplicación a media temperatura	la aplicación de media temperatura
	midtemperatuur-toepassing	midtemperatuurtoepassing	midtemperatuurtoepassing	a aplicação a média temperatura	η εφαρμογή σε μέση θερμοκρασία
	keskilämpötilan sovellus	sifidölöpitiin aplikac	среднетемпературного приложение	zastosowania w średnich temperaturach	-
4	Low-temperature application	Niedertemperaturanwendung	l'application à basse température	le aplicación a bassa temperatura	la aplicación de baja temperatura
	lagtemperatuur-toepassing	lagtemperatuurtoepassing	Niedertemperaturanwendung	a aplicação a baixa temperatura	η εφαρμογή σε χαμηλή θερμοκρασία
	alatalämpötilan sovellus	hitzölöpitiin aplikac	нижкотемпературн приложение	zastosowania w niskich temperaturach	-
5	Seasonal space heating energy efficiency class	die Klasse für die jahreszeitbedingte Raumheizungs-Energieeffizienz	la classe d'efficacité énergétique saisonnière, pour le chauffage des locaux	la classe di efficienza energetica stagionale del riscaldamento d'ambiente	la clase de eficiencia energética estacional de calefacción
	de seizoensegebonden energie-efficiëntieklasse voor ruimteverwarming	säsongsberedande energieeffektiviteitsklassa vid rumsuppvärmning	Klassen for årsvinklingsgrad ved rumopvarmning	A classe de eficiência energética do aquecimento ambiente sazonal	η τάξη ενεργειακής απόδοσης της εποχιακής θέρμανσης χώρου
	ilialämmityksen energiatehokkuusluokka	ilialämmityksen kausittainen energiatehokkuusluokka	Класс на сезонната отоплителна енергийна ефективност	Klasa sezonowej efektywności energetycznej ogrzewania pomieszczeń	-
6	Water heating energy efficiency class	die Klasse für die Warmwasserbereitungs-Energieeffizienz	la classe d'efficacité énergétique, pour le chauffage de l'eau	la classe di efficienza energetica del riscaldamento dell'acqua	la clase de eficiencia energética del caldeo de agua
	de energie-efficiëntieklasse voor waterverwarming	energietehtiviteitsklassa vid vattenuppvärmning	Klassen for årsvinklingsgrad ved vandopvarmning	A classe de eficiência energética do aquecimento de água	η τάξη ενεργειακής απόδοσης θέρμανσης νερού
	vedenlämmityksen energiatehokkuusluokka	frida energietickä klass för vattenuppvärmning	Класс на енергийната ефективност при подгряване на вода	Klasa efektywności energetycznej podgrzewania wody	-
7	Rated heat output under average climate conditions	die Wärmenennleistung bei durchschnittlichen Klimaverhältnissen	la puissance thermique nominale dans les conditions climatiques moyennes	la potencia termica nominale(in condizioi climatiche medie)	la potencia calorífica nominal(en condiciones climáticas medias)
	de nominale warmteafgifte onder gemiddelde klimaatomstandigheden	Den nominella värmefäkt (under genomsnittliga klimatförhållanden)	Den nominelle nyttelseffekt (under gemensnittlige klimatiske forhold)	A potência calorífica nominal(em condições climáticas médias)	η ονομαστική θερμική ισχύς(υπό μέσας κλιματικές συνθήκες)
	nimellislämpöteho(keskimääräisissä ilmastio-olosuhteissa)	imenoittu lämpöteho(vuorokauden keskimääräinen ilmastio-olosuhteissa)	номиналната топлинна мощност(при средни климатични условия)	znaniowna moc cieplna w warunkach klimatu umiarkowanego	-
	For space heating, annual energy consumption under average climate conditions	für die Raumheizung, den jährlichen Energieverbrauch bei durchschnittlichen Klimaverhältnissen	pour le chauffage des locaux, la consommation annuelle d'énergie(dans les conditions climatiques moyennes)	per il riscaldamento d'ambiente, il consumo annuo di energia(in condizioi climatiche medie)	para calentar espacios, el consumo anual de energía(en condiciones climáticas medias)
8	voor ruimteverwarming, het jaarlijkse energieverbruik onder gemiddelde klimaatomstandigheden	För rumsuppvärmning, årlig elförbrukning(vid genomsnittliga klimatförhållanden)	for rumopvarmning det årlige elforbrug(under gennemsnitlige klimaforhold)	Para o aquecimento ambiente, o consumo anual de energia(em condições climáticas medias)	για τη θέρμανση χώρου, η ετήσια κατανάλωση ενέργειας(υπό μέσας κλιματικές συνθήκες)
	ilialämmitykseenä vuotuinen energiansäilytys(keskimääräisissä ilmastio-olosuhteissa)	pro vyläpääni – roční spotřeba energie za průměrných klimatických podmínek	за отопление, годишното потребление на енергия(при средни климатични условия)	w odniesieniu do ogrzewania pomieszczeń, roczne zużycie energii(w warunkach klimatu umiarkowanego)	-
9	For water heating, annual electricity consumption under average climate conditions	für die Warmwasserbereitung, den jährlichen Stromverbrauch bei durchschnittlichen Klimaverhältnissen	pour le chauffage de l'eau, la consommation annuelle d'électricité(dans les conditions climatiques moyennes)	per il riscaldamento dell'acqua, il consumo annuo di energia(in condizioi climatiche medie)	para calentar agua, el consumo anual de electricidad(en condiciones climáticas medias)
	voor waterverwarming, het jaarlijkse elektriciteitsverbruik onder gemiddelde klimaatomstandigheden	För vattenuppvärmning, årlig elförbrukning(vid genomsnittliga klimatförhållanden)	for vandopvarmning det årlige elforbrug(under gennemsnitlige klimaforhold)	para o aquecimento de água, o consumo anual de electricidade(em condições climáticas médias)	για την θέρμανση νερού, η ετήσια κατανάλωση ηλεκτρικής ενέργειας(υπό μέσας κλιματικές συνθήκες)
10	vedenlämmitykseenä vuotuinen sähkökulutus(keskimääräisissä ilmastio-olosuhteissa)	pro ohjev vödy – roční spotřeba elektrické energie za průměrných klimatických podmínek	за подгряване на вода, годишното потребление(при средни климатични условия)	w odniesieniu do podgrzewania wody, roczne zużycie energii(elektrycznej w warunkach klimatu umiarkowanego)	η eficiencia energética estacional de calefacción(en condiciones climáticas medias)
	de energie-efficiëntie voor waterverwarming(onder gemiddelde klimaatomstandigheden)	Energieeffektivitet ved vandopvarmning(under gennemsnitlige klimaforhold)	а эффективность при подгряване на вода(при средни климатични условия)	A eficiência energética do aquecimento ambiente sazonal(em condições climáticas médias)	η ενεργειακή απόδοση θέρμανσης νερού(υπό μέσας κλιματικές συνθήκες)
	vedenlämmityksen energiatehokkuus(keskimääräisissä ilmastio-olosuhteissa)	energetická účinnost ohjeu vody za průměrných klimatických podmínek	енергийната ефективност при подгряване на вода(при средни климатични условия)	efektívnosť energetyczna podgrzewania wody(w warunkach klimatu umiarkowanego)	el nivel de potencia acústica L _{wa} en interiores
11	Sound power level L _{wa} indoor	der Schalleistungspegel L _{wa} in Gebäuden	le niveau de puissance acoustique L _{wa} à l'intérieur	el livello di potenza sonora L _{wa} all'interno	η ονομαστική θερμική ισχύς υπό χειρότερες κλιματικές συνθήκες
12	het geluidsvermogensniveau L _{wa} binnen	Ljudefektivnivå L _{wa} i inomhus	удефективнават L _{wa} i inde	O nivel de potencia sonora L _{wa} no interior	η στάθμη ηχητικής ισχύος L _{wa} εσωτερικού χώρου
	ääniteho L _{wa} sisällä	hädina akustického výkonu L _{wa} ve vnitřním prostoru	многото на звуковата мощност L _{wa} на закрито	poziom mocy akustycznej L _{wa} w pomieszczeniu	funcionar solamente durante las horas de baja demanda
13	Work only during off-peak hours	dass ein ausschließlicher Betrieb des Kombiheizgerätes zu Schwachlastzeiten	fonctionner qu'en heures creuses	funcionar únicamente fora das horas de pico	Λειτουργία μόνο εκτός των ωρών αιχμής
	werken uitsluitend in de daluren	drivas udelukkende under perioder med låg belastning	работи само в часовете извън взрховете натоварване	pracować jedynie w godzinach poza szczytowym obciążeniem	-
	toimimaan ainoastaan kuluushuippujen ukopuolella	provodu pouze mimo špičku	в работи само в часовете извън взрховете натоварване	pracać jedynie w godzinach poza szczytowym obciążeniem	la potencia calorífica nominal en condiciones climáticas más frías
14	Rated heat output under colder climate conditions	die Wärmenennleistung bei kälteren Klimaverhältnissen	la puissance thermique nominale, dans les conditions climatiques plus froides	la potencia termica nominale, in condizioi climatiche più fredde	la potencia calorífica nominal en condiciones climáticas más frías
	de nominale warmteafgifte, onder koude klimaatomstandigheden	Nominell afgiven värmefäkt vid kallare klimatförhållanden	den nominelle nyttelseffekt under koldere klimaforhold	A potencia calorífica nominal em condições climáticas mais frias	η ονομαστική θερμική ισχύς υπό χειρότερες κλιματικές συνθήκες
	nimellislämpöteho, kylmissä ilmastio-olosuhteissa	Nimennettävä lämpöteho kylmissä ilmastio-olosuhteissa	номиналната топлинна мощност при по-студени климатични условия	znaniowna moc cieplna w warunkach klimatu chłodnego	-
15	Rated heat output under warmer climate conditions	die Wärmenennleistung bei wärmeren Klimaverhältnissen	la puissance thermique nominale, dans les conditions climatiques plus chaudes	la potencia termica nominale, in condizioi climatiche più calde	la potencia calorífica nominal en condiciones climáticas más calidas
	de nominale warmteafgifte, onder warmere klimaatomstandigheden	Nominell afgiven värmefäkt vid varmare klimatförhållanden	den nominelle nyttelseffekt under varmere klimaforhold	A potencia calorífica nominal em condições climáticas mais quentes	η ονομαστική θερμική ισχύς υπό θερμότερες κλιματικές συνθήκες
	nimellislämpöteho, lämpimissä ilmastio-olosuhteissa	imennettävä lämpöteho, lämpimissä ilmastio-olosuhteissa	номиналната топлинна мощност при по-топли климатични условия	znaniowna moc cieplna w warunkach klimatu ciepłego	-
	For space heating, annual energy consumption under colder climate conditions	für die Raumheizung, der jährliche Energieverbrauch bei kälteren Klimaverhältnissen	pour le chauffage des locaux, la consommation annuelle d'énergie, dans les conditions climatiques plus froides	per il riscaldamento d'ambiente, il consumo annuo di energia, in condizioi climatiche più fredde	para calentar espacios, el consumo anual de energía en condiciones climáticas más frías
16	voor ruimteverwarming, het jaarlijkse energieverbruik onder koudere klimaatomstandigheden	För rumsuppvärmning, årlig energiförbrukning under koldere klimaforhold	for rumopvarmning det årlige energiforbrug under koldere klimaforhold	Para o aquecimento ambiente, o consumo anual de energia em condições climáticas mais frias	για θέρμανση χώρου, η ετήσια κατανάλωση ενέργειας υπό χειρότερες κλιματικές συνθήκες
	ilialämmitykseenä vuotuinen energiansäilytys(keskimääräisissä ilmastio-olosuhteissa)	pro vyläpääni – roční spotřeba energie za chladnějších klimatických podmínek	за отопление, годишното потребление на енергия при по-студени климатични условия	w odniesieniu do ogrzewania pomieszczeń, roczne zużycie energii w warunkach klimatu chłodnego	-
17	For space heating, annual energy consumption under warmer climate conditions	für die Raumheizung, der jährliche Energieverbrauch bei wärmeren Klimaverhältnissen	pour le chauffage des locaux, la consommation annuelle d'énergie, dans les conditions climatiques plus chaudes	per il riscaldamento d'ambiente, il consumo annuo di energia, in condizioi climatiche più calde	para calentar espacios, el consumo anual de energía en condiciones climáticas más calidas
	voor ruimteverwarming, het jaarlijkse energieverbruik onder warmere klimaatomstandigheden	För rumsuppvärmning, årlig energiförbrukning under varmare klimaforhold	for rumopvarmning det årlige energiforbrug under varmere klimaforhold	Para o aquecimento ambiente, o consumo anual de energia em condições climáticas mais quentes	για θέρμανση χώρου, η ετήσια κατανάλωση ενέργειας υπό θερμότερες κλιματικές συνθήκες
	ilialämmitykseenä vuotuinen energiansäilytys(keskimääräisissä ilmastio-olosuhteissa)	pro vyläpääni – roční spotřeba energie za teplejších klimatických podmínek	за отопление, годишното потребление на енергия при по-топли климатични условия	w odniesieniu do ogrzewania pomieszczeń, roczne zużycie energii w warunkach klimatu ciepłego	-
18	For water heating, annual energy consumption under colder climate conditions	für die Warmwasserbereitung, der jährliche Stromverbrauch bei kälteren Klimaverhältnissen	pour le chauffage de l'eau, la consommation annuelle d'électricité, dans les conditions climatiques plus froides	per il riscaldamento dell'acqua, il consumo annuo di energia, in condizioi climatiche più fredde e più calde	para calentar agua, el consumo anual de electricidad en condiciones climáticas más frías
	voor waterverwarming, het jaarlijkse elektriciteitsverbruik onder koudere klimaatomstandigheden	För vattenuppvärmning, årlig elförbrukning under kallare klimatförhållanden	for vandopvarmning det årlige elforbrug under koldere klimaforhold	para o aquecimento de água, o consumo anual de electricidade em condições climáticas mais frias	για θέρμανση νερού, η ετήσια κατανάλωση ηλεκτρικής ενέργειας υπό χειρότερες κλιματικές συνθήκες
	vedenlämmitykseenä vuotuinen sähkökulutus(keskimääräisissä ilmastio-olosuhteissa)	pro ohjev vödy – roční spotřeba elektrické energie za chladnějších klimatických podmínek	за подгряване на вода, годишното потребление на електроенергия при по-студени климатични условия	w odniesieniu do podgrzewania wody, roczne zużycie energii elektrycznej w warunkach klimatu chłodnego	-
19	For water heating, annual energy consumption under warmer climate conditions	für die Warmwasserbereitung, der jährliche Stromverbrauch bei wärmeren Klimaverhältnissen	pour le chauffage de l'eau, la consommation annuelle d'électricité, dans les conditions climatiques plus chaudes	per il riscaldamento dell'acqua, il consumo annuo di energia, in condizioi climatiche più fredde e più calde	para calentar agua, el consumo anual de electricidad en condiciones climáticas más calidas
20	de seizoensegebonden energie-efficiëntie voor ruimteverwarming onder koudere klimaatomstandigheden	ilialämmityksen kausittainen energiatehokkuus(keskimääräisissä ilmastio-olosuhteissa)	for vandopvarmning det årlige elforbrug under varmere klimaforhold	para o aquecimento de água, o consumo anual de electricidade em condições climáticas mais quentes	η ενεργειακή απόδοση της εποχιακής θέρμανσης χώρου υπό χειρότερες κλιματικές συνθήκες
	ilialämmityksen kausittainen energiatehokkuus(keskimääräisissä ilmastio-olosuhteissa)	ilialämmityksen kausittainen energiatehokkuus(keskimääräisissä ilmastio-olosuhteissa)	for vandopvarmning det årlige elforbrug under varmere klimaforhold	para o aquecimento de água, o consumo anual de electricidade em condições climáticas mais quentes	η ενεργειακή απόδοση της εποχιακής θέρμανσης χώρου υπό θερμότερες κλιματικές συνθήκες
21	de seizoensegebonden energie-efficiëntie voor ruimteverwarming onder warmere klimaatomstandigheden	ilialämmityksen kausittainen energiatehokkuus(keskimääräisissä ilmastio-olosuhteissa)	for vandopvarmning det årlige elforbrug under varmere klimaforhold	para o aquecimento de água, o consumo anual de electricidade em condições climáticas mais quentes	η ενεργειακή απόδοση της εποχιακής θέρμανσης χώρου υπό θερμότερες κλιματικές συνθήκες
	ilialämmityksen kausittainen energiatehokkuus(keskimääräisissä ilmastio-olosuhteissa)	ilialämmityksen kausittainen energiatehokkuus(keskimääräisissä ilmastio-olosuhteissa)	for vandopvarmning det årlige elforbrug under varmere klimaforhold	para o aquecimento de água, o consumo anual de electricidade em condições climáticas mais quentes	η ενεργειακή απόδοση της εποχιακής θέρμανσης χώρου υπό θερμότερες κλιματικές συνθήκες
22	de energie-efficiëntie voor waterverwarming onder koudere klimaatomstandigheden	Energieeffektivitet ved vandopvarmning under koldere klimaforhold	for vandopvarmning det årlige elforbrug under koldere klimaforhold	para o aquecimento de água, o consumo anual de electricidade em condições climáticas mais frias	η ενεργειακή απόδοση της θέρμανσης νερού υπό χειρότερες κλιματικές συνθήκες
	vedenlämmityksen energiatehokkuus(keskimääräisissä ilmastio-olosuhteissa)	energetická účinnost ohjeu vody za průměrných klimatických podmínek	енергийната ефективност при подгряване на вода при по-студени климатични условия	efektívnosť energetyczna podgrzewania wody w warunkach klimatu chłodnego	-
	Water heating energy efficiency under warmer climate conditions	die Warmwasserbereitungs-Energieeffizienz bei wärmeren Klimaverhältnissen	l'efficacité énergétique pour le chauffage des locaux, dans les conditions climatiques plus chaudes	l'efficienza energetica stagionale di riscaldamento d'ambiente in condizioi climatiche più calde	la eficiencia energética estacional de calefacción en condiciones climáticas más calidas
23	de energie-efficiëntie voor waterverwarming onder warmere klimaatomstandigheden	Energieeffektivitet ved vandopvarmning under varmere klimaforhold	for vandopvarmning det årlige elforbrug under varmere klimaforhold	para o aquecimento de água, o consumo anual de electricidade em condições climáticas mais quentes	η ενεργειακή απόδοση της θέρμανσης νερού υπό θερμότερες κλιματικές συνθήκες
	vedenlämmityksen energiatehokkuus(keskimääräisissä ilmastio-olosuhteissa)	energetická účinnost ohjeu vody za průměrných klimatických podmínek	енергийната ефективност при подгряване на вода при по-топли климатични условия	efektívnosť energetyczna podgrzewania wody w warunkach klimatu ciepłego	-
	Sound power level L _{wa} outdoor	der Schalleistungspegel L _{wa} im Freien	le niveau de puissance acoustique L _{wa} à l'extérieur	el livello di potenza sonora L _{wa} all'esterno	η ονομαστική θερμική ισχύς L _{wa} εν εξωτερικό
24	ääniteho L _{wa} ulkona	hädina akustického výkonu L _{wa} na venkovním prostoru	многото на звуковата мощност L _{wa} на открито	poziom mocy akustycznej L _{wa} na zewnątrz	η στάθμη ηχητικής ισχύος L _{wa} εξωτερικού χώρου

Model(s):	Outdoor unit:	PUHZ-FRP71VHA2
	Indoor unit:	EHST20C-****C
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		medium-temperature application.
Parameters for		average climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	7.5	kW	Seasonal space heating energy efficiency	η_s	121	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	P _{dh}	6.9	kW	T _j = - 7 °C	COP _d	2.04	-
Degradation co-efficient (**)	C _{dh}	0.99	-				
T _j = + 2 °C	P _{dh}	4.1	kW	T _j = + 2 °C	COP _d	3.04	-
Degradation co-efficient (**)	C _{dh}	0.98	-				
T _j = + 7 °C	P _{dh}	2.8	kW	T _j = + 7 °C	COP _d	3.99	-
Degradation co-efficient (**)	C _{dh}	0.97	-				
T _j = +12 °C	P _{dh}	1.6	kW	T _j = +12 °C	COP _d	4.59	-
Degradation co-efficient (**)	C _{dh}	0.94	-				
T _j = bivalent temperature	P _{dh}	6.9	kW	T _j = bivalent temperature	COP _d	2.03	-
T _j = operation limit temperature	P _{dh}	4.1	kW	T _j = operation limit temperature	COP _d	1.31	-
T _j = - 15 °C (if TOL < - 20 °C)	P _{dh}	-	kW	T _j = - 15 °C (if TOL < - 20 °C)	COP _d	-	-
Bivalent temperature	T _{biv}	-7	°C	Operation limit temperature	TOL	-20	°C
				Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.020	kW	Rated heat output (*)	P _{sup}	1.2	kW
Thermostat-off mode	P _{TO}	0.020	kW				
Standby mode	P _{SB}	0.020	kW	Type of energy input			
Crankcase heater mode	P _{CK}	0.005	kW				

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L _{WA}	40/68	dBA
Annual energy consumption	Q _{HE}	4923	kWh
Rated air flow rate, outdoors			
	-	3300	m ³ /h

For heat pump combination heater:			
Declared load profile	L		
Daily electricity consumption	Q _{elec}	4.800	kW/h
Annual electricity consumption	AEC	1055	kW/h
Water heating energy efficiency			
	η_{wh}	98	%

Contact details

MITSUBISHI ELECTRIC AIR CODITIONING SYSTEM EUROPE LTD. Nettlehill Road, Houston Industrial Estate, Livingston, EH54 5EQ, Scotland, U.K.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Model(s):	Outdoor unit:	PUHZ-FRP71VHA2
	Indoor unit:	EHST20C-****C
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		low-temperature application.
Parameters for		average climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	7.5	kW	Seasonal space heating energy efficiency	η_s	163	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	P _{dh}	6.6	kW	T _j = - 7 °C	COP _d	2.54	-
Degradation co-efficient (**)	C _{dh}	0.99	-				
T _j = + 2 °C	P _{dh}	4.7	kW	T _j = + 2 °C	COP _d	4.20	-
Degradation co-efficient (**)	C _{dh}	0.98	-				
T _j = + 7 °C	P _{dh}	5.4	kW	T _j = + 7 °C	COP _d	5.32	-
Degradation co-efficient (**)	C _{dh}	0.98	-				
T _j = +12 °C	P _{dh}	6.2	kW	T _j = +12 °C	COP _d	7.16	-
Degradation co-efficient (**)	C _{dh}	0.97	-				
T _j = bivalent temperature	P _{dh}	6.6	kW	T _j = bivalent temperature	COP _d	2.54	-
T _j = operation limit temperature	P _{dh}	4.1	kW	T _j = operation limit temperature	COP _d	1.33	-
T _j = - 15 °C (if TOL < - 20 °C)	P _{dh}	-	kW	T _j = - 15 °C (if TOL < - 20 °C)	COP _d	-	-
Bivalent temperature	T _{biv}	-7	°C	Operation limit temperature	TOL	-20	°C
				Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.020	kW	Rated heat output (*)	P _{sup}	1.4	kW
Thermostat-off mode	P _{TO}	0.020	kW				
Standby mode	P _{SB}	0.020	kW	Type of energy input			
Crankcase heater mode	P _{CK}	0.005	kW				

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L _{WA}	40/68	dBA
Annual energy consumption	Q _{HE}	3667	kWh
Rated air flow rate, outdoors			
		-	3300 m ³ /h

For heat pump combination heater:			
Declared load profile	L		
Daily electricity consumption	Q _{elec}	4.800	kW/h
Annual electricity consumption	AEC	1055	kW/h
Water heating energy efficiency			
	η_{wh}	98	%

Contact details

MITSUBISHI ELECTRIC AIR CODITIONING SYSTEM EUROPE LTD. Nettlehill Road, Houston Industrial Estate, Livingston, EH54 5EQ, Scotland, U.K.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Model(s):	Outdoor unit:	PUHZ-FRP71VHA2
	Indoor unit:	EHST20C-****C
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		medium-temperature application.
Parameters for		colder climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	4.4	kW	Seasonal space heating energy efficiency	ηs	98	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7 °C	Pdh	3.0	kW	Tj = - 7 °C	COPd	1.91	-
Degradation co-efficient (**)	Cdh	0.98	-				
Tj = + 2 °C	Pdh	4.4	kW	Tj = + 2 °C	COPd	2.64	-
Degradation co-efficient (**)	Cdh	0.98	-				
Tj = + 7 °C	Pdh	5.3	kW	Tj = + 7 °C	COPd	3.94	-
Degradation co-efficient (**)	Cdh	0.98	-				
Tj = +12 °C	Pdh	6.1	kW	Tj = +12 °C	COPd	4.79	-
Degradation co-efficient (**)	Cdh	0.98	-				
Tj = bivalent temperature	Pdh	4.1	kW	Tj = bivalent temperature	COPd	0.90	-
Tj = operation limit temperature	Pdh	4.1	kW	Tj = operation limit temperature	COPd	1.33	-
Tj = – 15 °C (if TOL < – 20 °C)	Pdh	-	kW	Tj = – 15 °C (if TOL < – 20 °C)	COPd	-	-
Bivalent temperature	Tbiv	-20	°C	Operation limit temperature	TOL	-20	°C
				Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.020	kW	Rated heat output (*)	P _{sup}	4.4	kW
Thermostat-off mode	P _{TO}	0.020	kW				
Standby mode	P _{SB}	0.020	kW				
Crankcase heater mode	P _{CK}	0.005	kW				
				Type of energy input			

Capacity control	variable			Rated air flow rate, outdoors	-	3300	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	40/68	dBA				
Annual energy consumption	Q _{HE}	4668	kWh				

For heat pump combination heater:

Declared load profile	L			Water heating energy efficiency	η_{wh}	80	%
Daily electricity consumption	Q _{elec}	6.100	kW/h				
Annual electricity consumption	AEC	1352	kW/h				

Contact details

MITSUBISHI ELECTRIC AIR CODITIONING SYSTEM EUROPE LTD. Nettlehill Road, Houston Industrial Estate, Livingston, EH54 5EQ, Scotland, U.K.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Model(s):	Outdoor unit:	PUHZ-FRP71VHA2
	Indoor unit:	EHST20C-****C
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		low-temperature application.
Parameters for		colder climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	4.4	kW	Seasonal space heating energy efficiency	η_s	134	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	P _{dh}	3.4	kW	T _j = - 7 °C	COP _d	2.76	-
Degradation co-efficient (**)	C _{dh}	0.98	-				
T _j = + 2 °C	P _{dh}	4.7	kW	T _j = + 2 °C	COP _d	4.60	-
Degradation co-efficient (**)	C _{dh}	0.98	-				
T _j = + 7 °C	P _{dh}	5.5	kW	T _j = + 7 °C	COP _d	2.35	-
Degradation co-efficient (**)	C _{dh}	0.99	-				
T _j = +12 °C	P _{dh}	6.5	kW	T _j = +12 °C	COP _d	3.05	-
Degradation co-efficient (**)	C _{dh}	0.99	-				
T _j = bivalent temperature	P _{dh}	4.1	kW	T _j = bivalent temperature	COP _d	1.31	-
T _j = operation limit temperature	P _{dh}	4.1	kW	T _j = operation limit temperature	COP _d	1.33	-
T _j = - 15 °C (if TOL < - 20 °C)	P _{dh}	-	kW	T _j = - 15 °C (if TOL < - 20 °C)	COP _d	-	-
Bivalent temperature	T _{biv}	-20	°C	Operation limit temperature	TOL	-20	°C
				Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.020	kW	Rated heat output (*)	P _{sup}	4.4	kW
Thermostat-off mode	P _{TO}	0.020	kW				
Standby mode	P _{SB}	0.020	kW	Type of energy input			
Crankcase heater mode	P _{CK}	0.005	kW				

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L _{WA}	40/68	dBA
Annual energy consumption	Q _{HE}	3554	kWh
Rated air flow rate, outdoors			
	-	3300	m ³ /h

For heat pump combination heater:			
Declared load profile	L		
Daily electricity consumption	Q _{elec}	6.100	kW/h
Annual electricity consumption	AEC	1352	kW/h
Water heating energy efficiency			
	η_{wh}	80	%

Contact details

MITSUBISHI ELECTRIC AIR CODITIONING SYSTEM EUROPE LTD. Nettlehill Road, Houston Industrial Estate, Livingston, EH54 5EQ, Scotland, U.K.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Model(s):	Outdoor unit:	PUHZ-FRP71VHA2
	Indoor unit:	EHST20C-****C
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		medium-temperature application.
Parameters for		warmer climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	7.5	kW	Seasonal space heating energy efficiency	η_s	150	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	P _{dh}	-	kW	T _j = - 7 °C	COP _d	-	-
Degradation co-efficient (**)	C _{dh}	-	-				
T _j = + 2 °C	P _{dh}	7.5	kW	T _j = + 2 °C	COP _d	1.87	-
Degradation co-efficient (**)	C _{dh}	0.99	-				
T _j = + 7 °C	P _{dh}	4.8	kW	T _j = + 7 °C	COP _d	3.00	-
Degradation co-efficient (**)	C _{dh}	0.98	-				
T _j = +12 °C	P _{dh}	2.1	kW	T _j = +12 °C	COP _d	5.42	-
Degradation co-efficient (**)	C _{dh}	0.94	-				
T _j = bivalent temperature	P _{dh}	7.5	kW	T _j = bivalent temperature	COP _d	1.87	-
T _j = operation limit temperature	P _{dh}	4.1	kW	T _j = operation limit temperature	COP _d	1.33	-
T _j = - 15 °C (if TOL < - 20 °C)	P _{dh}	-	kW	T _j = - 15 °C (if TOL < - 20 °C)	COP _d	-	-
Bivalent temperature	T _{biv}	2	°C	Operation limit temperature	TOL	-20	°C
				Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.020	kW	Rated heat output (*)	P _{sup}	0.0	kW
Thermostat-off mode	P _{TO}	0.020	kW				
Standby mode	P _{SB}	0.020	kW	Type of energy input			
Crankcase heater mode	P _{CK}	0.005	kW				

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L _{WA}	40/68	dBA
Annual energy consumption	Q _{HE}	2595	kWh
Rated air flow rate, outdoors			
	-	3300	m ³ /h

For heat pump combination heater:			
Declared load profile	L		
Daily electricity consumption	Q _{elec}	4.300	kW/h
Annual electricity consumption	AEC	956	kW/h
Water heating energy efficiency			
	η_{wh}	110	%

Contact details

MITSUBISHI ELECTRIC AIR CODITIONING SYSTEM EUROPE LTD. Nettlehill Road, Houston Industrial Estate, Livingston, EH54 5EQ, Scotland, U.K.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Model(s):	Outdoor unit:	PUHZ-FRP71VHA2
	Indoor unit:	EHST20C-****C
Air-to-water heat pump:		yes
Water-to-water heat pump:		no
Brine-to-water heat pump:		no
Low-temperature heat pump:		no
Equipped with a supplementary heater:		yes
Heat pump combination heater:		yes
Parameters for		low-temperature application.
Parameters for		warmer climate conditions.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	7.5	kW	Seasonal space heating energy efficiency	η_s	226	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	P _{dh}	-	kW	T _j = - 7 °C	COP _d	-	-
Degradation co-efficient (**)	C _{dh}	-	-				
T _j = + 2 °C	P _{dh}	7.5	kW	T _j = + 2 °C	COP _d	2.41	-
Degradation co-efficient (**)	C _{dh}	0.99	-				
T _j = + 7 °C	P _{dh}	4.8	kW	T _j = + 7 °C	COP _d	4.56	-
Degradation co-efficient (**)	C _{dh}	0.98	-				
T _j = +12 °C	P _{dh}	2.1	kW	T _j = +12 °C	COP _d	8.17	-
Degradation co-efficient (**)	C _{dh}	0.92	-				
T _j = bivalent temperature	P _{dh}	7.5	kW	T _j = bivalent temperature	COP _d	2.41	-
T _j = operation limit temperature	P _{dh}	4.1	kW	T _j = operation limit temperature	COP _d	1.33	-
T _j = - 15 °C (if TOL < - 20 °C)	P _{dh}	-	kW	T _j = - 15 °C (if TOL < - 20 °C)	COP _d	-	-
Bivalent temperature	T _{biv}	2	°C	Operation limit temperature	TOL	-20	°C
				Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.020	kW	Rated heat output (*)	P _{sup}	0.0	kW
Thermostat-off mode	P _{TO}	0.020	kW				
Standby mode	P _{SB}	0.020	kW	Type of energy input			
Crankcase heater mode	P _{CK}	0.005	kW				

Other items							
Capacity control	variable			Rated air flow rate, outdoors	-	3300	m ³ /h
Sound power level, indoors/outdoors	L _{WA}	40/68	dBA				
Annual energy consumption	Q _{HE}	1722	kWh				

For heat pump combination heater:							
Declared load profile	L			Water heating energy efficiency	η_{wh}	110	%
Daily electricity consumption	Q _{elec}	4.300	kW/h				
Annual electricity consumption	AEC	956	kW/h				

Contact details

MITSUBISHI ELECTRIC AIR CODITIONING SYSTEM EUROPE LTD. Nettlehill Road, Houston Industrial Estate, Livingston, EH54 5EQ, Scotland, U.K.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.