




ENERG
енергия · ενεργεια


Y IJA
IE IA



Indoor unit EHST30D-****D
Outdoor unit SUZ-SHWM60VAH(-SC)



A++



A+



41 dB



60 dB



06 kW
06 kW
06 kW

[illegible][illegible]

| | | | | | |
|----|---|---|--|--|--|
| | English Nederlands suomi | Deutsch Svenska Čeština | Français Dansk Български | Italiano Português Polski | Español Ελληνικά - |
| 1 | Outdoor unit buitenunit Ulkoyksikkö | Außengerät Utomhusenhet Venkovní jednotka | unité extérieure Udendørs enhed Външно тяло | unità esterna unidade exterior jednostka zewnętrzna | unidad exterior Εξωτερική μονάδα - |
| | Indoor unit binnenunit Sisäyksikkö | Innengerät Inomhusenhet Vnitřní jednotka | unité intérieure Indendørs enhed Вътрешно тяло | unità interna unidade interior jednostka wewnętrzna | unidad interior Εσωτερική μονάδα - |
| 3 | Medium-temperature application middentemperatuur-toepassing keskilämpötilan sovellus | Mitteltemperaturanwendung mediumtemperaturanvendelsen střednéteplotní aplikace | l'application à moyenne température middeltemperaturanvendelsen среднотемпературното приложение | le applicazioni a media temperatura a aplicação a média temperatura zastosowania w średnich temperaturach | la aplicación de media temperatura η εφαρμογή σε μέση θερμοκρασία - |
| | Low-temperature application lagetemperatuur-toepassing matalanlämpötilan sovellus | Niedertemperaturanwendung lågtemperaturanvendelsen nízkoteplotní aplikace | l'application à basse température lavtemperaturanvendelsen нискотемпературни приложения | le applicazioni a bassa temperatura a aplicação a baixa temperatura zastosowania w niskich temperaturach | la aplicación de baja temperatura η εφαρμογή σε χαμηλή θερμοκρασία - |
| 5 | Declared load profile Opgegeven capaciteitsprofiel Ilmoitettu kuormitusprofiili | Angegebenes Lastprofil Deklarerad belastningsprofil Deklarovaný zátěžový profil | Profil de soultirage déclaré Angivet forbrugsprofil Объявен товаров профил | Profilo di carico dichiarato Perfil de carga declarado Deklarowany profil obciążen | Perfil de carga declarado Δηλωμένο προφίλ φορτίου - |
| | Seasonal space heating energy efficiency class de seizoensgebonden energie-efficiëntieklasse voor ruimteverwarming tilalämmityksen kausittainen energiatehokkuusluokka | die Klasse für die jahreszeitbedingte Raumheizungs-Energieeffizienz säsongsbaserade energieeffektivitetsklass vid rumsuppvärmning třída sezonní energetické účinnosti vytápění | la classe d'efficacité énergétique saisonnière, pour le chauffage des locaux klassen for årsvirkningsgrad ved rumopvarmning класът на сезонната отоплителна енергийна ефективност | la classe di efficienza energetica stagionale del riscaldamento d'ambiente A classe de eficiência energética do aquecimento ambiente sazonal klasa sezonowej efektywności energetycznej ogrzewania pomieszczeń | la clase de eficiencia energética estacional de calefacción η τάξη ενεργειακής απόδοσης της εποχιακής θέρμανσης χώρου - |
| 7 | Water heating energy efficiency class de energie-efficiëntieklasse voor waterverwarming vedenlämmityksen energiatehokkuusluokka | die Klasse für die Warmwasserbereitungs-Energieeffizienz energieeffektivitetsklass vid vattenuppvärmning třída energetické účinnosti ohřevu vody | la classe d'efficacité énergétique, pour le chauffage de l'eau klassen for årsvirkningsgrad ved vandopvarmning класът на енергийната ефективност при подгряване на вода | la classe di efficienza energetica del riscaldamento dell'acqua A classe de eficiência energética do aquecimento de água klasa efektywności energetycznej podgrzewania wody | la clase de eficiencia energética del caldeo de agua η τάξη ενεργειακής απόδοσης θέρμανσης νερού - |
| | Rated heat output under average climate conditions de nominale warmteafgifte(onder gemiddelde klimaatomstandigheden) nimellislämpöteho(keskimääräisissä ilmastoloosuhteissa) | die Wärmenenleistung bei durchschnittlichen Klimaverhältnissen Den nominella avgivna värmeeffekten(under genomsnittliga klimatförhållanden) jmenovitě tepelný výkon(za průměrných klimatických podmínek) | la puissance thermique nominale dans les conditions climatiques moyennes den nominelle nytteeffekt(under gennemsnitlige klimaforhold) номиналната топлинна мощност(при средни климатични условия) | la potenza termica nominale(in condizioni climatiche medie) A potência calorífica nominal(em condições climáticas médias) znacznoscwa moc cieplna(w warunkach klimatu umiarkowanego) | la potencia calorífica nominal(en condiciones climáticas medias) η ονομαστική θερμική ισχύς(υπό μέσες κλιματικές συνθήκες) - |
| 9 | For space heating, annual energy consumption under average climate conditions voor ruimteverwarming, het jaarlijkse energieverbruik(onder gemiddelde klimaatomstandigheden) tilalämmityksestä vuotuinen energiankulutus(keskimääräisissä ilmastoloosuhteissa) | für die Raumheizung, den jährlichen Energieverbrauch bei durchschnittlichen Klimaverhältnissen För rumsuppvärmning, årlig energiförbrukning(vid genomsnittliga klimatförhållanden) pro vytápění – roční spotřeba energie za průměrných klimatických podmínek | pour le chauffage des locaux, la consommation annuelle d'énergie(dans les conditions climatiques moyennes) for rumopvarmning det årlige energiforbrug(under gennemsnitlige klimaforhold) за отопление, годишното потребление на енергия(при средни климатични условия) | per il riscaldamento d'ambiente, il consumo annuo di energia(in condizioni climatiche medie) Para o aquecimento ambiente, o consumo anual de energia(em condições climáticas médias) w odniesieniu do ogrzewania pomieszczeń, roczne zużycie energii(w warunkach klimatu umiarkowanego) | para calentar espacios, el consumo anual de energia(en condiciones climáticas medias) για τη θέρμανση χώρου, η ετήσια κατανάλωση ενέργειας(υπό μέσες κλιματικές συνθήκες) - |
| 10 | For water heating, annual electricity consumption under average climate conditions voor waterverwarming, het jaarlijkse elektriciteitsverbruik(onder gemiddelde klimaatomstandigheden) vedenlämmityksestä vuotuinen sähkönkulutus(keskimääräisissä ilmastoloosuhteissa) | für die Warmwasserbereitung, den jährlichen Stromverbrauch bei durchschnittlichen Klimaverhältnissen För vattenuppvärmning, årlig elförbrukning(vid genomsnittliga klimatförhållanden) pro ohřev vody – roční spotřeba elektrické energie za průměrných klimatických podmínek | pour le chauffage de l'eau, la consommation annuelle d'électricité(dans les conditions climatiques moyennes) for vandopvarmning det årlige elforbrug(under gennemsnitlige klimaforhold) за подгряване на вода, годишното потребление(при средни климатични условия) | per il riscaldamento dell'acqua, il consumo annuo di energia(in condizioni climatiche medie) para o aquecimento de água, o consumo anual de eletricidade(em condições climáticas médias) w odniesieniu do podgrzewania wody, roczne zużycie energii elektrycznej(w warunkach klimatu umiarkowanego) | para calentar agua, el consumo anual de electricidad(en condiciones climáticas medias) η ετήσια κατανάλωση ηλεκτρικής ενέργειας(υπό μέσες κλιματικές συνθήκες) - |
| 11 | Seasonal space heating energy efficiency under average climate conditions de seizoensgebonden energie-efficiëntie voor ruimteverwarming(onder gemiddelde klimaatomstandigheden) tilalämmityksen kausittainen energiatehokkuus(keskimääräisissä ilmastoloosuhteissa) | die jahreszeitbedingte Raumheizungs-Energieeffizienz bei durchschnittlichen Klimaverhältnissen Säsongsmedelverkningsgrad för rumsuppvärmning(vid genomsnittliga klimatförhållanden) sezonní energetická účinnost vytápění za průměrných klimatických podmínek | l'efficacité énergétique saisonnière pour le chauffage des locaux(dans les conditions climatiques moyennes) årsvirkningsgraden ved rumopvarmning(under gennemsnitlige klimaforhold) сезонната енергийна ефективност при отопление(при средни климатични условия) | l'efficienza energetica stagionale di riscaldamento d'ambiente(in condizioni climatiche medie) A eficiência energética do aquecimento ambiente sazonal(em condições climáticas médias) sezonowa efektywność energetyczna ogrzewania pomieszczeń(w warunkach klimatu umiarkowanego) | la eficiencia energética estacional de calefacción(en condiciones climáticas medias) η ενεργειακή απόδοση της εποχιακής θέρμανσης χώρου(υπό μέσες κλιματικές συνθήκες) - |
| 12 | Water heating energy efficiency under average climate conditions de energie-efficiëntie voor waterverwarming(onder gemiddelde klimaatomstandigheden) vedenlämmityksen energiatehokkuus(keskimääräisissä ilmastoloosuhteissa) | die Warmwasserbereitungs-Energieeffizienz bei durchschnittlichen Klimaverhältnissen Energieeffektivitet ved vattenuppvärmning(vid genomsnittliga klimatförhållanden) energetická účinnost ohřevu vody za průměrných klimatických podmínek | l'efficacité énergétique pour le chauffage de l'eau(dans les conditions climatiques moyennes) energieeffektiviteten ved vandopvarmning(under gennemsnitlige klimaforhold) енергийната ефективност при подгряване на вода(при средни климатични условия) | l'efficienza energetica di riscaldamento dell'acqua(in condizioni climatiche medie) a eficiência energética do aquecimento de água(em condições climáticas médias) efektywność energetyczna podgrzewania wody(w warunkach klimatu umiarkowanego) | la eficiencia energética del caldeo de agua(en condiciones climáticas medias) η ενεργειακή απόδοση θέρμανσης νερού(υπό μέσες κλιματικές συνθήκες) - |
| 13 | Sound power level L _{WA} indoor het geluidsvermogensniveau L _{WA} binnen äänitehotaso L _{WA} sisällä | der Schalleistungspegel L _{WA} in Gebäuden Ljudeffektnivå L _{WA} i inomhus hladina akustického výkonu L _{WA} ve vnitřním prostoru | le niveau de puissance acoustique L _{WA} , à l'intérieur lydeeffektniveauet L _{WA} i inde ниводо на звуковата мощност L _{WA} на закрито | il livello di potenza sonora L _{WA} all'interno O nível de potência sonora L _{WA} no interior poziom mocy akustycznej L _{WA} w pomieszczeniu | el nivel de potencia acústica L _{WA} en interiores η στάθμη ηχητικής ισχύος L _{WA} εσωτερικού χώρου - |
| 14 | Work only during off-peak hours werken uitsluitend in de daluren toimimaan ainoastaan kuluushuipujen ulkopuolella | dass ein ausschließlicher Betrieb des Kombiheizgerätes zu Schwachlastzeiten drivas uteslutande under perioder med låg belastning provodu pouze mimo špičku | fonctionner qu'en heures creuses fungere uden for spidsbelastningsperioder работи само в часовете извън върховото натоварване | funzione soltanto durante le ore morte de funcionar unicamente fora das horas de pico pracować jedynie w godzinach poza szczytowym obciążeniem | funcionar solamente durante las horas de baja demanda λειτουργία μόνο εκτός των ωρών αιχμής - |
| 15 | Rated heat output under colder climate conditions de nominale warmteafgifte, onder koudere klimaatomstandigheden nimellislämpöteho, kylmissä ilmastoloosuhteissa | die Wärmenenleistung bei kälteren Klimaverhältnissen Nominell avgiven värmeeffekt vid kallare klimatförhållanden jmenovitě tepelný výkon za chladnějších klimatických podmínek | la puissance thermique nominale, dans les conditions climatiques plus froides den nominelle nytteeffekt under koldere klimaforhold номиналната топлинна мощност при по-студени климатични условия | la potenza termica nominale, in condizioni climatiche più fredde A potência calorífica nominal em condições climáticas mais frias znacznoscwa moc cieplna w warunkach klimatu chłodnego | la potencia calorífica nominal en condiciones climáticas más frías η ονομαστική θερμική ισχύς υπό ψυχρότερες κλιματικές συνθήκες - |
| 16 | Rated heat output under warmer climate conditions de nominale warmteafgifte, onder warmere klimaatomstandigheden nimellislämpöteho, lämpimissä ilmastoloosuhteissa | die Wärmenenleistung bei wärmeren Klimaverhältnissen Nominell avgiven värmeeffekt vid varmare klimatförhållanden jmenovitě tepelný výkon za teplejších klimatických podmínek | la puissance thermique nominale, dans les conditions climatiques plus chaudes den nominelle nytteeffekt under varmere klimaforhold номиналната топлинна мощност при по-топли климатични условия | la potenza termica nominale, in condizioni climatiche più calde A potência calorífica nominal em condições climáticas mais quentes znacznoscwa moc cieplna w warunkach klimatu ciepłego | la potencia calorífica nominal en condiciones climáticas más cálidas η ονομαστική θερμική ισχύς υπό θερμότερες κλιματικές συνθήκες - |
| 17 | For space heating, annual energy consumption under colder climate conditions voor ruimteverwarming, het jaarlijkse energieverbruik onder koudere klimaatomstandigheden tilalämmityksestä vuotuinen energiankulutus kylmissä ilmastoloosuhteissa | für die Raumheizung, der jährliche Energieverbrauch bei kälteren Klimaverhältnissen För rumsuppvärmning, årlig energiförbrukning under kallare klimatförhållanden pro vytápění – roční spotřeba energie za chladnější klimatických podmínek | pour le chauffage des locaux, la consommation annuelle d'énergie, dans les conditions climatiques plus froides for rumopvarmning det årlige energiforbrug under koldere klimaforhold за отопление, годишното потребление на енергия при по-студени климатични условия | per il riscaldamento d'ambiente, il consumo annuo di energia, in condizioni climatiche più fredde Para o aquecimento ambiente, o consumo anual de energia em condições climáticas mais frias w odniesieniu do ogrzewania pomieszczeń, roczne zużycie energii w warunkach klimatu chłodnego | para calentar espacios, el consumo anual de energia en condiciones climáticas más frías για θέρμανση χώρου, η ετήσια κατανάλωση ενέργειας υπό ψυχρότερες κλιματικές συνθήκες - |
| 18 | For space heating, annual energy consumption under warmer climate conditions voor ruimteverwarming, het jaarlijkse energieverbruik onder warmere klimaatomstandigheden tilalämmityksestä vuotuinen energiankulutus lämpimissä ilmastoloosuhteissa | für die Raumheizung, der jährliche Energieverbrauch bei wärmeren Klimaverhältnissen För rumsuppvärmning, årlig energiförbrukning under varmare klimatförhållanden pro vytápění – roční spotřeba energie za teplejších klimatických podmínek | pour le chauffage des locaux, la consommation annuelle d'énergie, dans les conditions climatiques plus chaudes for rumopvarmning det årlige energiforbrug under varmere klimaforhold за отопление, годишното потребление на енергия при по-топли климатични условия | per il riscaldamento d'ambiente, il consumo annuo di energia, in condizioni climatiche più calde Para o aquecimento ambiente, o consumo anual de energia em condições climáticas mais quentes w odniesieniu do ogrzewania pomieszczeń, roczne zużycie energii w warunkach klimatu ciepłego | para calentar espacios, el consumo anual de energia en condiciones climáticas más cálidas για θέρμανση χώρου, η ετήσια κατανάλωση ενέργειας υπό θερμότερες κλιματικές συνθήκες - |
| 19 | For water heating, annual energy consumption under colder climate conditions voor waterverwarming, het jaarlijkse elektriciteitsverbruik onder koudere klimaatomstandigheden vedenlämmityksestä vuotuinen sähkönkulutus kylmissä ilmastoloosuhteissa | für die Warmwasserbereitung, der jährliche Stromverbrauch bei kälteren Klimaverhältnissen För vattenuppvärmning, årlig elförbrukning under kallare klimatförhållanden pro ohřev vody – roční spotřeba elektrické energie za chladnějších klimatických podmínek | pour le chauffage de l'eau, la consommation annuelle d'électricité, dans les conditions climatiques plus froides for vandopvarmning det årlige elforbrug under koldere klimaforhold за подгряване на вода, годишното потребление на електроенергия при по-студени климатични условия | per il riscaldamento dell'acqua, il consumo annuo di energia, in condizioni climatiche più fredde para o aquecimento de água, o consumo anual de eletricidade em condições climáticas mais frias w odniesieniu do podgrzewania wody, roczne zużycie energii elektrycznej w warunkach klimatu chłodnego | para calentar agua, el consumo anual de electricidad en condiciones climáticas más frías για θέρμανση νερού, η ετήσια κατανάλωση ηλεκτρικής ενέργειας υπό ψυχρότερες κλιματικές συνθήκες - |
| 20 | For water heating, annual energy consumption under warmer climate conditions voor waterverwarming, het jaarlijkse elektriciteitsverbruik onder warmere klimaatomstandigheden vedenlämmityksestä vuotuinen sähkönkulutus lämpimissä ilmastoloosuhteissa | für die Warmwasserbereitung, der jährliche Stromverbrauch bei wärmeren Klimaverhältnissen För vattenuppvärmning, årlig elförbrukning under varmare klimatförhållanden pro ohřev vody – roční spotřeba elektrické energie za teplejších klimatických podmínek | pour le chauffage de l'eau, la consommation annuelle d'électricité, dans les conditions climatiques plus chaudes for vandopvarmning det årlige elforbrug under varmere klimaforhold за подгряване на вода, годишното потребление на електроенергия при по-топли климатични условия | per il riscaldamento dell'acqua, il consumo annuo di energia, in condizioni climatiche più calde para o aquecimento de água, o consumo anual de eletricidade em condições climáticas mais quentes w odniesieniu do podgrzewania wody, roczne zużycie energii elektrycznej w warunkach klimatu ciepłego | para calentar agua, el consumo anual de electricidad en condiciones climáticas más cálidas για θέρμανση νερού, η ετήσια κατανάλωση ηλεκτρικής ενέργειας υπό θερμότερες κλιματικές συνθήκες - |
| 21 | Seasonal space heating energy efficiency under colder climate conditions de seizoensgebonden energie-efficiëntie voor ruimteverwarming onder koudere klimaatomstandigheden tilalämmityksen kausittainen energiatehokkuus kylmissä ilmastoloosuhteissa | die jahreszeitbedingte Raumheizungs-Energieeffizienz bei kälteren Klimaverhältnissen Säsongsmedelverkningsgrad för rumsuppvärmning under kallare klimatförhållanden sezonní energetická účinnost vytápění za chladnějších klimatických podmínek | l'efficacité énergétique saisonnière pour le chauffage des locaux, dans les conditions climatiques plus froides årsvirkningsgraden ved rumopvarmning under koldere klimaforhold сезонната енергийна ефективност при отопление при по-студени климатични условия | l'efficienza energetica stagionale di riscaldamento d'ambiente in condizioni climatiche più fredde A eficiência energética do aquecimento ambiente sazonal em condições climáticas mais frias sezonowa efektywność energetyczna ogrzewania pomieszczeń w warunkach klimatu chłodnego | la eficiencia energética estacional de calefacción en condiciones climáticas más frías η ενεργειακή απόδοση της εποχιακής θέρμανσης χώρου υπό ψυχρότερες κλιματικές συνθήκες - |
| 22 | Seasonal space heating energy efficiency under warmer climate conditions de seizoensgebonden energie-efficiëntie voor ruimteverwarming onder warmere klimaatomstandigheden tilalämmityksen kausittainen energiatehokkuus lämpimissä ilmastoloosuhteissa | die jahreszeitbedingte Raumheizungs-Energieeffizienz bei wärmeren Klimaverhältnissen Säsongsmedelverkningsgrad för rumsuppvärmning under varmare klimatförhållanden sezonní energetická účinnost vytápění za teplejších klimatických podmínek | l'efficacité énergétique saisonnière pour le chauffage des locaux, dans les conditions climatiques plus chaudes årsvirkningsgraden ved rumopvarmning under varmere klimaforhold сезонната енергийна ефективност при отопление при по-топли климатични условия | l'efficienza energetica stagionale di riscaldamento d'ambiente in condizioni climatiche più calde A eficiência energética do aquecimento ambiente sazonal em condições climáticas mais quentes sezonowa efektywność energetyczna ogrzewania pomieszczeń w warunkach klimatu ciepłego | la eficiencia energética estacional de calefacción en condiciones climáticas más cálidas η ενεργειακή απόδοση της εποχιακής θέρμανσης χώρου υπό θερμότερες κλιματικές συνθήκες - |
| 23 | Water heating energy efficiency under colder climate conditions de energie-efficiëntie voor waterverwarming onder koudere klimaatomstandigheden vedenlämmityksen energiatehokkuus kylmissä ilmastoloosuhteissa | die Warmwasserbereitungs-Energieeffizienz bei kälteren Klimaverhältnissen Energieeffektivitet ved vattenuppvärmning under kallare klimatförhållanden energetická účinnost ohřevu vody za chladnějších klimatických podmínek | l'efficacité énergétique pour le chauffage de l'eau, dans les conditions climatiques plus froides energieeffektiviteten ved vandopvarmning under koldere klimaforhold енергийната ефективност при подгряване на вода при по-студени климатични условия | l'efficienza energetica di riscaldamento dell'acqua in condizioni climatiche più fredde a eficiência energética do aquecimento de água em condições climáticas mais frias efektywność energetyczna podgrzewania wody w warunkach klimatu chłodnego | la eficiencia energética de caldeo de agua en condiciones climáticas más frías η ενεργειακή απόδοση της θέρμανσης νερού υπό ψυχρότερες κλιματικές συνθήκες - |
| 24 | Water heating energy efficiency under warmer climate conditions de energie-efficiëntie voor waterverwarming onder warmere klimaatomstandigheden vedenlämmityksen energiatehokkuus lämpimissä ilmastoloosuhteissa | die Warmwasserbereitungs-Energieeffizienz bei wärmeren Klimaverhältnissen Energieeffektivitet ved vattenuppvärmning under varmare klimatförhållanden energetická účinnost ohřevu vody za teplejších klimatických podmínek | l'efficacité énergétique pour le chauffage de l'eau, dans les conditions climatiques plus chaudes energieeffektiviteten ved vandopvarmning under varmere klimaforhold енергийната ефективност при подгряване на вода при по-топли климатични условия | l'efficienza energetica di riscaldamento dell'acqua in condizioni climatiche più calde a eficiência energética do aquecimento de água em condições climáticas mais quentes efektywność energetyczna podgrzewania wody w warunkach klimatu ciepłego | la eficiencia energética de caldeo de agua en condiciones climáticas más cálidas η ενεργειακή απόδοση της θέρμανσης νερού υπό θερμότερες κλιματικές συνθήκες - |
| 25 | Sound power level L _{WA} outdoor het geluidsvermogensniveau L _{WA} buiten äänitehotaso L _{WA} ulkona | der Schalleistungspegel L _{WA} im Freien Ljudeffektnivå L _{WA} i utomhus hladina akustického výkonu L _{WA} ve venkovním prostoru | le niveau de puissance acoustique L _{WA} à l'extérieur lydeeffektniveauet L _{WA} i ude ниводо на звуковата мощност L _{WA} на открито | il livello di potenza sonora L _{WA} all'esterno O nível de potência sonora L _{WA} no exterior poziom mocy akustycznej L _{WA} na zewnątrz | el nivel de potencia acústica L _{WA} en exteriores η στάθμη ηχητικής ισχύος L _{WA} εξωτερικού χώρου - |

PRODUCT INFORMATION / TECHNICAL DOCUMENTATION

| | | |
|---------------------------------------|---------------|---------------------------------|
| Model(s): | Outdoor unit: | SUZ-SHWM60VAH(-SC) |
| | Indoor unit: | EHST30D-****D |
| Air-to-water heat pump: | | yes |
| Water-to-water heat pump: | | no |
| Brine-to-water heat pump: | | no |
| Low-temperature heat pump: | | no |
| Equipped with a supplementary heater: | | yes |
| Heat pump combination heater: | | yes |
| Parameters for | | medium-temperature application. |
| Parameters for | | average climate conditions. |

| Item | Symbol | Value | Unit | Item | Symbol | Value | Unit | | |
|--|------------------|-------|------|--|------------|-------|------|--|--|
| Rated heat output (*) | Prated | 6.0 | kW | Seasonal space heating energy efficiency | ηs | 126 | % | | |
| Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | | |
| Tj = - 7 °C | Pdh | 5.3 | kW | Tj = - 7 °C | COPd | 1.85 | - | | |
| Degradation co-efficient (**) | Cdh | 1.00 | - | | | | | | |
| Tj = + 2 °C | Pdh | 3.7 | kW | Tj = + 2 °C | COPd | 3.13 | - | | |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | | | |
| Tj = + 7 °C | Pdh | 3.1 | kW | Tj = + 7 °C | COPd | 4.66 | - | | |
| Degradation co-efficient (**) | Cdh | 0.98 | - | | | | | | |
| Tj = +12 °C | Pdh | 3.9 | kW | Tj = +12 °C | COPd | 6.53 | - | | |
| Degradation co-efficient (**) | Cdh | 0.98 | - | | | | | | |
| Tj = bivalent temperature | Pdh | 5.3 | kW | Tj = bivalent temperature | COPd | 1.85 | - | | |
| Tj = operation limit temperature (***) | Pdh | 5.8 | kW | Tj = operation limit temperature (***) | COPd | 1.64 | - | | |
| | | | | | | | | | |
| Bivalent temperature | Tbiv | -7 | °C | Operation limit temperature | TOL | -25 | °C | | |
| Reference design conditions for space heating | Tdesignh | -10 | °C | Heating water operating limit temperature | WTOL | 60 | °C | | |
| Power consumption in modes other than active mode | | | | Supplementary heater | | | | | |
| Off mode | P _{OFF} | 0.015 | kW | Rated heat output (*) | Psup | 0.2 | kW | | |
| Thermostat-off mode | P _{TO} | 0.015 | kW | | | | | | |
| Standby mode | P _{SB} | 0.015 | kW | Type of energy input | Electrical | | | | |
| Crankcase heater mode | P _{CK} | 0.000 | kW | | | | | | |

| | | | | | | | |
|-------------------------------------|-----------------|---------|-----|-------------------------------|---|------|------|
| Other items | | | | | | | |
| Capacity control | variable | | | Rated air flow rate, outdoors | - | 2500 | m³/h |
| Sound power level, indoors/outdoors | L _{WA} | 41 / 60 | dBA | | | | |
| Annual energy consumption | Q _{HE} | 3850 | kWh | | | | |

| | | | | | | | |
|-----------------------------------|-------|-------|-----|---------------------------------|-----|-----|---|
| For heat pump combination heater: | | | | | | | |
| Declared load profile | XL | | | Water heating energy efficiency | ηwh | 139 | % |
| Daily electricity consumption | Qelec | 5.650 | kWh | | | | |
| Annual electricity consumption | AEC | 1243 | kWh | | | | |

| | | | | | | | |
|---|--|--|--|---|--|--|--|
| Contact details | | | | | | | |
| MITSUBISHI ELECTRIC CONSUMER PRODUCTS (THAILAND) CO., LTD. | | | | 700/406 moo 7, Tambon don hua roh, Amphur muang, chonburi 20000, Thailand | | | |
| The identification and signature of the person empowered to bind the supplier: | | | | | | | |
|  | | | | Tadashi SAITO | | | |
| | | | | Manager, Quality Assurance Department | | | |
| | | | | THAILAND | | | |

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(***) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

PRODUCT INFORMATION / TECHNICAL DOCUMENTATION

| | | |
|---------------------------------------|------------------------------|--------------------|
| Model(s): | Outdoor unit: | SUZ-SHWM60VAH(-SC) |
| | Indoor unit: | EHST30D-****D |
| Air-to-water heat pump: | yes | |
| Water-to-water heat pump: | no | |
| Brine-to-water heat pump: | no | |
| Low-temperature heat pump: | no | |
| Equipped with a supplementary heater: | yes | |
| Heat pump combination heater: | yes | |
| Parameters for | low-temperature application. | |
| Parameters for | average climate conditions. | |

| Item | Symbol | Value | Unit | Item | Symbol | Value | Unit | | |
|--|------------------|-------|------|--|------------|-------|------|--|--|
| Rated heat output (*) | Prated | 6.1 | kW | Seasonal space heating energy efficiency | ηs | 175 | % | | |
| Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | | |
| Tj = - 7 °C | Pdh | 5.4 | kW | Tj = - 7 °C | COPd | 2.78 | - | | |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | | | |
| Tj = + 2 °C | Pdh | 4.1 | kW | Tj = + 2 °C | COPd | 4.43 | - | | |
| Degradation co-efficient (**) | Cdh | 0.98 | - | | | | | | |
| Tj = + 7 °C | Pdh | 3.4 | kW | Tj = + 7 °C | COPd | 6.27 | - | | |
| Degradation co-efficient (**) | Cdh | 0.97 | - | | | | | | |
| Tj = +12 °C | Pdh | 3.7 | kW | Tj = +12 °C | COPd | 7.11 | - | | |
| Degradation co-efficient (**) | Cdh | 0.97 | - | | | | | | |
| Tj = bivalent temperature | Pdh | 6.1 | kW | Tj = bivalent temperature | COPd | 2.26 | - | | |
| Tj = operation limit temperature (***) | Pdh | 6.1 | kW | Tj = operation limit temperature (***) | COPd | 2.26 | - | | |
| | | | | | | | | | |
| Bivalent temperature | Tbiv | -10 | °C | Operation limit temperature | TOL | -25 | °C | | |
| Reference design conditions for space heating | Tdesignh | -10 | °C | Heating water operating limit temperature | WTOL | 60 | °C | | |
| Power consumption in modes other than active mode | | | | Supplementary heater | | | | | |
| Off mode | P _{OFF} | 0.015 | kW | Rated heat output (*) | Psup | 0.0 | kW | | |
| Thermostat-off mode | P _{TO} | 0.015 | kW | | | | | | |
| Standby mode | P _{SB} | 0.015 | kW | Type of energy input | Electrical | | | | |
| Crankcase heater mode | P _{CK} | 0.000 | kW | | | | | | |

| | | | | | | | |
|-------------------------------------|-----------------|---------|-----|-------------------------------|---|------|------|
| Other items | | | | | | | |
| Capacity control | variable | | | Rated air flow rate, outdoors | - | 2500 | m³/h |
| Sound power level, indoors/outdoors | L _{WA} | 41 / 60 | dBA | | | | |
| Annual energy consumption | Q _{HE} | 2838 | kWh | | | | |

| | | | | | | | |
|-----------------------------------|-------|-------|-----|---------------------------------|-----|-----|---|
| For heat pump combination heater: | | | | | | | |
| Declared load profile | XL | | | Water heating energy efficiency | ηwh | 139 | % |
| Daily electricity consumption | Qelec | 5.650 | kWh | | | | |
| Annual electricity consumption | AEC | 1243 | kWh | | | | |

| | | | | | | | |
|--|--|--|--|---|--|--|--|
| Contact details | | | | | | | |
| MITSUBISHI ELECTRIC CONSUMER PRODUCTS (THAILAND) CO., LTD. | | | | 700/406 moo 7, Tambon don hua roh, Amphur muang, chonburi 20000, Thailand | | | |
| The identification and signature of the person empowered to bind the supplier; | | | | Tadashi SAITO | | | |
| The signature is signed in the average climate / medium-temperature section. | | | | Manager, Quality Assuarance Department | | | |
| | | | | THAILAND | | | |

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(***) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

PRODUCT INFORMATION / TECHNICAL DOCUMENTATION

| | | |
|---------------------------------------|---------------------------------|--------------------|
| Model(s): | Outdoor unit: | SUZ-SHWM60VAH(-SC) |
| | Indoor unit: | EHST30D-****D |
| Air-to-water heat pump: | yes | |
| Water-to-water heat pump: | no | |
| Brine-to-water heat pump: | no | |
| Low-temperature heat pump: | no | |
| Equipped with a supplementary heater: | yes | |
| Heat pump combination heater: | yes | |
| Parameters for | medium-temperature application. | |
| Parameters for | colder climate conditions. | |

| Item | Symbol | Value | Unit | Item | Symbol | Value | Unit | |
|--|------------------|-------|------|--|------------|-------|------|--|
| Rated heat output (*) | Prated | 5.5 | kW | Seasonal space heating energy efficiency | ηs | 100 | % | |
| Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | |
| Tj = - 7 °C | Pdh | 3.4 | kW | Tj = - 7 °C | COPd | 2.17 | - | |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | | |
| Tj = + 2 °C | Pdh | 3.4 | kW | Tj = + 2 °C | COPd | 3.31 | - | |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | | |
| Tj = + 7 °C | Pdh | 3.3 | kW | Tj = + 7 °C | COPd | 5.15 | - | |
| Degradation co-efficient (**) | Cdh | 0.98 | - | | | | | |
| Tj = +12 °C | Pdh | 3.6 | kW | Tj = +12 °C | COPd | 6.27 | - | |
| Degradation co-efficient (**) | Cdh | 0.97 | - | | | | | |
| Tj = bivalent temperature | Pdh | 4.5 | kW | Tj = bivalent temperature | COPd | 1.15 | - | |
| Tj = operation limit temperature (***) | Pdh | 4.0 | kW | Tj = operation limit temperature (***) | COPd | 1.08 | - | |
| Tj = – 15 °C (if TOL < – 20 °C) | Pdh | 4.5 | kW | Tj = – 15 °C (if TOL < – 20 °C) | COPd | 1.15 | - | |
| Bivalent temperature | Tbiv | -15 | °C | Operation limit temperature | TOL | -25 | °C | |
| Reference design conditions for space heating | Tdesignh | -22 | °C | Heating water operating limit temperature | WTOL | 60 | °C | |
| Power consumption in modes other than active mode | | | | Supplementary heater | | | | |
| Off mode | P _{OFF} | 0.015 | kW | Rated heat output (*) | Psup | 5.5 | kW | |
| Thermostat-off mode | P _{TO} | 0.015 | kW | | | | | |
| Standby mode | P _{SB} | 0.015 | kW | Type of energy input | Electrical | | | |
| Crankcase heater mode | P _{CK} | 0.000 | kW | | | | | |

| | | | | | | | |
|-------------------------------------|-----------------|---------|-----|-------------------------------|---|------|------|
| Other items | | | | | | | |
| Capacity control | variable | | | Rated air flow rate, outdoors | - | 2500 | m³/h |
| Sound power level, indoors/outdoors | L _{WA} | 41 / 60 | dBa | | | | |
| Annual energy consumption | Q _{HE} | 5265 | kWh | | | | |

| | | | | | | | |
|-----------------------------------|-------|-------|-----|---------------------------------|-----|-----|---|
| For heat pump combination heater: | | | | | | | |
| Declared load profile | XL | | | Water heating energy efficiency | ηwh | 117 | % |
| Daily electricity consumption | Qelec | 6.710 | kWh | | | | |
| Annual electricity consumption | AEC | 1476 | kWh | | | | |

| | | | | | | | |
|--|--|--|--|---|--|--|--|
| Contact details | | | | | | | |
| MITSUBISHI ELECTRIC CONSUMER PRODUCTS (THAILAND) CO., LTD. | | | | 700/406 moo 7, Tambon don hua roh, Amphur muang, chonburi 20000, Thailand | | | |
| The identification and signature of the person empowered to bind the supplier; | | | | | | | |
| | | | | Tadashi SAITO | | | |
| The signature is signed in the average climate / medium-temperature section. | | | | Manager, Quality Assuarance Department | | | |
| | | | | THAILAND | | | |

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(***) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

PRODUCT INFORMATION / TECHNICAL DOCUMENTATION

| | | |
|---------------------------------------|------------------------------|--------------------|
| Model(s): | Outdoor unit: | SUZ-SHWM60VAH(-SC) |
| | Indoor unit: | EHST30D-****D |
| Air-to-water heat pump: | yes | |
| Water-to-water heat pump: | no | |
| Brine-to-water heat pump: | no | |
| Low-temperature heat pump: | no | |
| Equipped with a supplementary heater: | yes | |
| Heat pump combination heater: | yes | |
| Parameters for | low-temperature application. | |
| Parameters for | colder climate conditions. | |

| Item | Symbol | Value | Unit | Item | Symbol | Value | Unit |
|--|------------------|-------|------|--|------------|-------|------|
| Rated heat output (*) | Prated | 5.5 | kW | Seasonal space heating energy efficiency | ηs | 147 | % |
| Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj | | | |
| Tj = - 7 °C | Pdh | 3.4 | kW | Tj = - 7 °C | COPd | 3.31 | - |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | |
| Tj = + 2 °C | Pdh | 3.6 | kW | Tj = + 2 °C | COPd | 4.56 | - |
| Degradation co-efficient (**) | Cdh | 0.98 | - | | | | |
| Tj = + 7 °C | Pdh | 3.4 | kW | Tj = + 7 °C | COPd | 6.55 | - |
| Degradation co-efficient (**) | Cdh | 0.97 | - | | | | |
| Tj = +12 °C | Pdh | 3.7 | kW | Tj = +12 °C | COPd | 7.33 | - |
| Degradation co-efficient (**) | Cdh | 0.97 | - | | | | |
| Tj = bivalent temperature | Pdh | 4.5 | kW | Tj = bivalent temperature | COPd | 1.92 | - |
| Tj = operation limit temperature (***) | Pdh | 5.5 | kW | Tj = operation limit temperature (***) | COPd | 1.71 | - |
| Tj = – 15 °C (if TOL < – 20 °C) | Pdh | 4.5 | kW | Tj = – 15 °C (if TOL < – 20 °C) | COPd | 1.92 | - |
| Bivalent temperature | Tbiv | -15 | °C | Operation limit temperature | TOL | -25 | °C |
| Reference design conditions for space heating | Tdesignh | -22 | °C | Heating water operating limit temperature | WTOL | 60 | °C |
| Power consumption in modes other than active mode | | | | Supplementary heater | | | |
| Off mode | P _{OFF} | 0.015 | kW | Rated heat output (*) | Psup | 0.0 | kW |
| Thermostat-off mode | P _{TO} | 0.015 | kW | | | | |
| Standby mode | P _{SB} | 0.015 | kW | Type of energy input | Electrical | | |
| Crankcase heater mode | P _{CK} | 0.000 | kW | | | | |

| | | | | | | | |
|-------------------------------------|-----------------|---------|-----|-------------------------------|---|------|------|
| Other items | | | | | | | |
| Capacity control | variable | | | Rated air flow rate, outdoors | - | 2500 | m³/h |
| Sound power level, indoors/outdoors | L _{WA} | 41 / 60 | dBa | | | | |
| Annual energy consumption | Q _{HE} | 3616 | kWh | | | | |

| | | | | | | | |
|-----------------------------------|-------|-------|-----|---------------------------------|-----|-----|---|
| For heat pump combination heater: | | | | | | | |
| Declared load profile | XL | | | Water heating energy efficiency | ηwh | 117 | % |
| Daily electricity consumption | Qelec | 6.710 | kWh | | | | |
| Annual electricity consumption | AEC | 1476 | kWh | | | | |

| | | | | | | | |
|--|--|--|--|---|--|--|--|
| Contact details | | | | | | | |
| MITSUBISHI ELECTRIC CONSUMER PRODUCTS (THAILAND) CO., LTD. | | | | 700/406 moo 7, Tambon don hua roh, Amphur muang, chonburi 20000, Thailand | | | |
| The identification and signature of the person empowered to bind the supplier; | | | | | | | |
| | | | | Tadashi SAITO | | | |
| The signature is signed in the average climate / medium-temperature section. | | | | Manager, Quality Assuarance Department | | | |
| | | | | THAILAND | | | |

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(***) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

PRODUCT INFORMATION / TECHNICAL DOCUMENTATION

| | | |
|---------------------------------------|---------------------------------|--------------------|
| Model(s): | Outdoor unit: | SUZ-SHWM60VAH(-SC) |
| | Indoor unit: | EHST30D-****D |
| Air-to-water heat pump: | yes | |
| Water-to-water heat pump: | no | |
| Brine-to-water heat pump: | no | |
| Low-temperature heat pump: | no | |
| Equipped with a supplementary heater: | yes | |
| Heat pump combination heater: | yes | |
| Parameters for | medium-temperature application. | |
| Parameters for | warmer climate conditions. | |

| Item | Symbol | Value | Unit | Item | Symbol | Value | Unit | | |
|--|------------------|-------|------|--|------------|-------|------|--|--|
| Rated heat output (*) | Prated | 6.0 | kW | Seasonal space heating energy efficiency | ηs | 167 | % | | |
| Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | | |
| Tj = - 7 °C | Pdh | - | kW | Tj = - 7 °C | COPd | - | - | | |
| Degradation co-efficient (**) | Cdh | - | - | | | | | | |
| Tj = + 2 °C | Pdh | 6.0 | kW | Tj = + 2 °C | COPd | 2.47 | - | | |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | | | |
| Tj = + 7 °C | Pdh | 3.9 | kW | Tj = + 7 °C | COPd | 3.95 | - | | |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | | | |
| Tj = +12 °C | Pdh | 3.6 | kW | Tj = +12 °C | COPd | 5.50 | - | | |
| Degradation co-efficient (**) | Cdh | 0.98 | - | | | | | | |
| Tj = bivalent temperature | Pdh | 6.0 | kW | Tj = bivalent temperature | COPd | 2.51 | - | | |
| Tj = operation limit temperature (***) | Pdh | 6.0 | kW | Tj = operation limit temperature (***) | COPd | 2.51 | - | | |
| | | | | | | | | | |
| Bivalent temperature | Tbiv | 2 | °C | Operation limit temperature | TOL | -25 | °C | | |
| Reference design conditions for space heating | Tdesignh | 2 | °C | Heating water operating limit temperature | WTOL | 60 | °C | | |
| Power consumption in modes other than active mode | | | | Supplementary heater | | | | | |
| Off mode | P _{OFF} | 0.015 | kW | Rated heat output (*) | Psup | 0.0 | kW | | |
| Thermostat-off mode | P _{TO} | 0.015 | kW | | | | | | |
| Standby mode | P _{SB} | 0.015 | kW | Type of energy input | Electrical | | | | |
| Crankcase heater mode | P _{CK} | 0.000 | kW | | | | | | |

| | | | | | | | |
|-------------------------------------|-----------------|---------|-----|-------------------------------|---|------|------|
| Other items | | | | | | | |
| Capacity control | variable | | | Rated air flow rate, outdoors | - | 2500 | m³/h |
| Sound power level, indoors/outdoors | L _{WA} | 41 / 60 | dBA | | | | |
| Annual energy consumption | Q _{HE} | 1884 | kWh | | | | |

| | | | | | | | |
|-----------------------------------|-------|-------|-----|---------------------------------|-----|-----|---|
| For heat pump combination heater: | | | | | | | |
| Declared load profile | XL | | | Water heating energy efficiency | ηwh | 167 | % |
| Daily electricity consumption | Qelec | 4.720 | kWh | | | | |
| Annual electricity consumption | AEC | 1038 | kWh | | | | |

| | | | | | | | |
|--|--|--|--|---|--|--|--|
| Contact details | | | | | | | |
| MITSUBISHI ELECTRIC CONSUMER PRODUCTS (THAILAND) CO., LTD. | | | | 700/406 moo 7, Tambon don hua roh, Amphur muang, chonburi 20000, Thailand | | | |
| The identification and signature of the person empowered to bind the supplier; | | | | | | | |
| | | | | Tadashi SAITO | | | |
| The signature is signed in the average climate / medium-temperature section. | | | | Manager, Quality Assuarance Department | | | |
| | | | | THAILAND | | | |

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(***) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

PRODUCT INFORMATION / TECHNICAL DOCUMENTATION

| | | |
|---------------------------------------|------------------------------|--------------------|
| Model(s): | Outdoor unit: | SUZ-SHWM60VAH(-SC) |
| | Indoor unit: | EHST30D-****D |
| Air-to-water heat pump: | yes | |
| Water-to-water heat pump: | no | |
| Brine-to-water heat pump: | no | |
| Low-temperature heat pump: | no | |
| Equipped with a supplementary heater: | yes | |
| Heat pump combination heater: | yes | |
| Parameters for | low-temperature application. | |
| Parameters for | warmer climate conditions. | |

| Item | Symbol | Value | Unit | Item | Symbol | Value | Unit | | |
|--|------------------|-------|------|--|------------|-------|------|--|--|
| Rated heat output (*) | Prated | 6.0 | kW | Seasonal space heating energy efficiency | ηs | 230 | % | | |
| Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | | |
| Tj = - 7 °C | Pdh | - | kW | Tj = - 7 °C | COPd | - | - | | |
| Degradation co-efficient (**) | Cdh | - | - | | | | | | |
| Tj = + 2 °C | Pdh | 6.0 | kW | Tj = + 2 °C | COPd | 3.67 | - | | |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | | | |
| Tj = + 7 °C | Pdh | 3.9 | kW | Tj = + 7 °C | COPd | 5.92 | - | | |
| Degradation co-efficient (**) | Cdh | 0.98 | - | | | | | | |
| Tj = +12 °C | Pdh | 3.7 | kW | Tj = +12 °C | COPd | 7.10 | - | | |
| Degradation co-efficient (**) | Cdh | 0.97 | - | | | | | | |
| Tj = bivalent temperature | Pdh | 6.0 | kW | Tj = bivalent temperature | COPd | 3.67 | - | | |
| Tj = operation limit temperature (***) | Pdh | 6.0 | kW | Tj = operation limit temperature (***) | COPd | 3.67 | - | | |
| | | | | | | | | | |
| Bivalent temperature | Tbiv | 2 | °C | Operation limit temperature | TOL | -25 | °C | | |
| Reference design conditions for space heating | Tdesignh | 2 | °C | Heating water operating limit temperature | WTOL | 60 | °C | | |
| Power consumption in modes other than active mode | | | | Supplementary heater | | | | | |
| Off mode | P _{OFF} | 0.015 | kW | Rated heat output (*) | Psup | 0.0 | kW | | |
| Thermostat-off mode | P _{TO} | 0.015 | kW | | | | | | |
| Standby mode | P _{SB} | 0.015 | kW | Type of energy input | Electrical | | | | |
| Crankcase heater mode | P _{CK} | 0.000 | kW | | | | | | |

| | | | | | | | |
|-------------------------------------|-----------------|---------|-----|-------------------------------|---|------|------|
| Other items | | | | | | | |
| Capacity control | variable | | | Rated air flow rate, outdoors | - | 2500 | m³/h |
| Sound power level, indoors/outdoors | L _{WA} | 41 / 60 | dBA | | | | |
| Annual energy consumption | Q _{HE} | 1378 | kWh | | | | |

| | | | | | | | |
|-----------------------------------|-------|-------|-----|---------------------------------|-----|-----|---|
| For heat pump combination heater: | | | | | | | |
| Declared load profile | XL | | | Water heating energy efficiency | ηwh | 167 | % |
| Daily electricity consumption | Qelec | 4.720 | kWh | | | | |
| Annual electricity consumption | AEC | 1038 | kWh | | | | |

| | | | | | | | |
|--|--|--|--|---|--|--|--|
| Contact details | | | | | | | |
| MITSUBISHI ELECTRIC CONSUMER PRODUCTS (THAILAND) CO., LTD. | | | | 700/406 moo 7, Tambon don hua roh, Amphur muang, chonburi 20000, Thailand | | | |
| The identification and signature of the person empowered to bind the supplier; | | | | | | | |
| | | | | Tadashi SAITO | | | |
| The signature is signed in the average climate / medium-temperature section. | | | | Manager, Quality Assuarance Department | | | |
| | | | | THAILAND | | | |

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(***) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

PRODUCT INFORMATION / TECHNICAL DOCUMENTATION

| | | |
|---------------------------------------|---------------------------------|--------------------|
| Model(s): | Outdoor unit: | SUZ-SHWM60VAH(-SC) |
| | Indoor unit: | EHST30D-MED |
| Air-to-water heat pump: | yes | |
| Water-to-water heat pump: | no | |
| Brine-to-water heat pump: | no | |
| Low-temperature heat pump: | no | |
| Equipped with a supplementary heater: | no | |
| Heat pump combination heater: | yes | |
| Parameters for | medium-temperature application. | |
| Parameters for | average climate conditions. | |

| Item | Symbol | Value | Unit | Item | Symbol | Value | Unit | | |
|--|------------------|-------|------|--|------------|-------|------|--|--|
| Rated heat output (*) | Prated | 6.0 | kW | Seasonal space heating energy efficiency | ηs | 126 | % | | |
| Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | | |
| Tj = - 7 °C | Pdh | 5.3 | kW | Tj = - 7 °C | COPd | 1.85 | - | | |
| Degradation co-efficient (**) | Cdh | 1.00 | - | | | | | | |
| Tj = + 2 °C | Pdh | 3.7 | kW | Tj = + 2 °C | COPd | 3.13 | - | | |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | | | |
| Tj = + 7 °C | Pdh | 3.1 | kW | Tj = + 7 °C | COPd | 4.66 | - | | |
| Degradation co-efficient (**) | Cdh | 0.98 | - | | | | | | |
| Tj = +12 °C | Pdh | 3.9 | kW | Tj = +12 °C | COPd | 6.53 | - | | |
| Degradation co-efficient (**) | Cdh | 0.98 | - | | | | | | |
| Tj = bivalent temperature | Pdh | 5.3 | kW | Tj = bivalent temperature | COPd | 1.85 | - | | |
| Tj = operation limit temperature (***) | Pdh | 5.8 | kW | Tj = operation limit temperature (***) | COPd | 1.64 | - | | |
| | | | | | | | | | |
| Bivalent temperature | Tbiv | -7 | °C | Operation limit temperature | TOL | -25 | °C | | |
| Reference design conditions for space heating | Tdesignh | -10 | °C | Heating water operating limit temperature | WTOL | 60 | °C | | |
| Power consumption in modes other than active mode | | | | Supplementary heater | | | | | |
| Off mode | P _{OFF} | 0.015 | kW | Rated heat output (*) | Psup | 0.2 | kW | | |
| Thermostat-off mode | P _{TO} | 0.015 | kW | | | | | | |
| Standby mode | P _{SB} | 0.015 | kW | Type of energy input | Electrical | | | | |
| Crankcase heater mode | P _{CK} | 0.000 | kW | | | | | | |

| | | | | | | | |
|-------------------------------------|-----------------|---------|-----|-------------------------------|---|------|------|
| Other items | | | | | | | |
| Capacity control | variable | | | Rated air flow rate, outdoors | - | 2500 | m³/h |
| Sound power level, indoors/outdoors | L _{WA} | 41 / 60 | dBa | | | | |
| Annual energy consumption | Q _{HE} | 3850 | kWh | | | | |

| | | | | | | | |
|-----------------------------------|-------|-------|-----|---------------------------------|-----|-----|---|
| For heat pump combination heater: | | | | | | | |
| Declared load profile | XL | | | Water heating energy efficiency | ηwh | 139 | % |
| Daily electricity consumption | Qelec | 5.650 | kWh | | | | |
| Annual electricity consumption | AEC | 1243 | kWh | | | | |

| | | | | | | | |
|---|--|--|--|---|--|--|--|
| Contact details | | | | | | | |
| MITSUBISHI ELECTRIC CONSUMER PRODUCTS (THAILAND) CO., LTD. | | | | 700/406 moo 7, Tambon don hua roh, Amphur muang, chonburi 20000, Thailand | | | |
| The identification and signature of the person empowered to bind the supplier: | | | | | | | |
|  | | | | Tadashi SAITO Manager, Quality Assurance Department THAILAND | | | |

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(***) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

PRODUCT INFORMATION / TECHNICAL DOCUMENTATION

| | | |
|---------------------------------------|------------------------------|--------------------|
| Model(s): | Outdoor unit: | SUZ-SHWM60VAH(-SC) |
| | Indoor unit: | EHST30D-MED |
| Air-to-water heat pump: | yes | |
| Water-to-water heat pump: | no | |
| Brine-to-water heat pump: | no | |
| Low-temperature heat pump: | no | |
| Equipped with a supplementary heater: | no | |
| Heat pump combination heater: | yes | |
| Parameters for | low-temperature application. | |
| Parameters for | average climate conditions. | |

| Item | Symbol | Value | Unit | Item | Symbol | Value | Unit | | |
|--|------------------|-------|------|--|------------|-------|------|--|--|
| Rated heat output (*) | Prated | 6.1 | kW | Seasonal space heating energy efficiency | ηs | 175 | % | | |
| Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | | |
| Tj = - 7 °C | Pdh | 5.4 | kW | Tj = - 7 °C | COPd | 2.78 | - | | |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | | | |
| Tj = + 2 °C | Pdh | 4.1 | kW | Tj = + 2 °C | COPd | 4.43 | - | | |
| Degradation co-efficient (**) | Cdh | 0.98 | - | | | | | | |
| Tj = + 7 °C | Pdh | 3.4 | kW | Tj = + 7 °C | COPd | 6.27 | - | | |
| Degradation co-efficient (**) | Cdh | 0.97 | - | | | | | | |
| Tj = +12 °C | Pdh | 3.7 | kW | Tj = +12 °C | COPd | 7.11 | - | | |
| Degradation co-efficient (**) | Cdh | 0.97 | - | | | | | | |
| Tj = bivalent temperature | Pdh | 6.1 | kW | Tj = bivalent temperature | COPd | 2.26 | - | | |
| Tj = operation limit temperature (***) | Pdh | 6.1 | kW | Tj = operation limit temperature (***) | COPd | 2.26 | - | | |
| | | | | | | | | | |
| Bivalent temperature | Tbiv | -10 | °C | Operation limit temperature | TOL | -25 | °C | | |
| Reference design conditions for space heating | Tdesignh | -10 | °C | Heating water operating limit temperature | WTOL | 60 | °C | | |
| Power consumption in modes other than active mode | | | | Supplementary heater | | | | | |
| Off mode | P _{OFF} | 0.015 | kW | Rated heat output (*) | Psup | 0.0 | kW | | |
| Thermostat-off mode | P _{TO} | 0.015 | kW | | | | | | |
| Standby mode | P _{SB} | 0.015 | kW | Type of energy input | Electrical | | | | |
| Crankcase heater mode | P _{CK} | 0.000 | kW | | | | | | |

| | | | | | | | |
|-------------------------------------|-----------------|---------|-----|-------------------------------|---|------|------|
| Other items | | | | | | | |
| Capacity control | variable | | | Rated air flow rate, outdoors | - | 2500 | m³/h |
| Sound power level, indoors/outdoors | L _{WA} | 41 / 60 | dBa | | | | |
| Annual energy consumption | Q _{HE} | 2838 | kWh | | | | |

| | | | | | | | |
|-----------------------------------|-------|-------|-----|---------------------------------|-----|-----|---|
| For heat pump combination heater: | | | | | | | |
| Declared load profile | XL | | | Water heating energy efficiency | ηwh | 139 | % |
| Daily electricity consumption | Qelec | 5.650 | kWh | | | | |
| Annual electricity consumption | AEC | 1243 | kWh | | | | |

| | | | | | | | |
|--|--|--|--|---|--|--|--|
| Contact details | | | | | | | |
| MITSUBISHI ELECTRIC CONSUMER PRODUCTS (THAILAND) CO., LTD. | | | | 700/406 moo 7, Tambon don hua roh, Amphur muang, chonburi 20000, Thailand | | | |
| The identification and signature of the person empowered to bind the supplier; | | | | | | | |
| | | | | Tadashi SAITO | | | |
| The signature is signed in the average climate / medium-temperature section. | | | | Manager, Quality Assuarance Department | | | |
| | | | | THAILAND | | | |

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(***) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

PRODUCT INFORMATION / TECHNICAL DOCUMENTATION

| | | |
|---------------------------------------|---------------------------------|--------------------|
| Model(s): | Outdoor unit: | SUZ-SHWM60VAH(-SC) |
| | Indoor unit: | EHST30D-MED |
| Air-to-water heat pump: | yes | |
| Water-to-water heat pump: | no | |
| Brine-to-water heat pump: | no | |
| Low-temperature heat pump: | no | |
| Equipped with a supplementary heater: | no | |
| Heat pump combination heater: | yes | |
| Parameters for | medium-temperature application. | |
| Parameters for | colder climate conditions. | |

| Item | Symbol | Value | Unit | Item | Symbol | Value | Unit |
|--|------------------|-------|------|--|--------|------------|------|
| Rated heat output (*) | Prated | 5.5 | kW | Seasonal space heating energy efficiency | ηs | 100 | % |
| Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj | | | |
| Tj = - 7 °C | Pdh | 3.4 | kW | Tj = - 7 °C | COPd | 2.17 | - |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | |
| Tj = + 2 °C | Pdh | 3.4 | kW | Tj = + 2 °C | COPd | 3.31 | - |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | |
| Tj = + 7 °C | Pdh | 3.3 | kW | Tj = + 7 °C | COPd | 5.15 | - |
| Degradation co-efficient (**) | Cdh | 0.98 | - | | | | |
| Tj = +12 °C | Pdh | 3.6 | kW | Tj = +12 °C | COPd | 6.27 | - |
| Degradation co-efficient (**) | Cdh | 0.97 | - | | | | |
| Tj = bivalent temperature | Pdh | 4.5 | kW | Tj = bivalent temperature | COPd | 1.15 | - |
| Tj = operation limit temperature (***) | Pdh | 4.0 | kW | Tj = operation limit temperature (***) | COPd | 1.08 | - |
| Tj = – 15 °C (if TOL < – 20 °C) | Pdh | 4.5 | kW | Tj = – 15 °C (if TOL < – 20 °C) | COPd | 1.15 | - |
| Bivalent temperature | Tbiv | -15 | °C | Operation limit temperature | TOL | -25 | °C |
| Reference design conditions for space heating | Tdesignh | -22 | °C | Heating water operating limit temperature | WTOL | 60 | °C |
| Power consumption in modes other than active mode | | | | Supplementary heater | | | |
| Off mode | P _{OFF} | 0.015 | kW | Rated heat output (*) | Psup | 5.5 | kW |
| Thermostat-off mode | P _{TO} | 0.015 | kW | | | | |
| Standby mode | P _{SB} | 0.015 | kW | Type of energy input | | Electrical | |
| Crankcase heater mode | P _{CK} | 0.000 | kW | | | | |

| | | | | | | | |
|-------------------------------------|-----------------|---------|-----|-------------------------------|---|------|------|
| Other items | | | | | | | |
| Capacity control | variable | | | Rated air flow rate, outdoors | - | 2500 | m³/h |
| Sound power level, indoors/outdoors | L _{WA} | 41 / 60 | dBa | | | | |
| Annual energy consumption | Q _{HE} | 5265 | kWh | | | | |

| | | | | | | | |
|-----------------------------------|-------|-------|-----|---------------------------------|-----|-----|---|
| For heat pump combination heater: | | | | | | | |
| Declared load profile | XL | | | Water heating energy efficiency | ηwh | 117 | % |
| Daily electricity consumption | Qelec | 6.710 | kWh | | | | |
| Annual electricity consumption | AEC | 1476 | kWh | | | | |

| | | | | | | | |
|--|--|--|--|---|--|--|--|
| Contact details | | | | | | | |
| MITSUBISHI ELECTRIC CONSUMER PRODUCTS (THAILAND) CO., LTD. | | | | 700/406 moo 7, Tambon don hua roh, Amphur muang, chonburi 20000, Thailand | | | |
| The identification and signature of the person empowered to bind the supplier; | | | | | | | |
| | | | | Tadashi SAITO | | | |
| The signature is signed in the average climate / medium-temperature section. | | | | Manager, Quality Assuarance Department | | | |
| | | | | THAILAND | | | |

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(***) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

PRODUCT INFORMATION / TECHNICAL DOCUMENTATION

| | | |
|---------------------------------------|------------------------------|--------------------|
| Model(s): | Outdoor unit: | SUZ-SHWM60VAH(-SC) |
| | Indoor unit: | EHST30D-MED |
| Air-to-water heat pump: | yes | |
| Water-to-water heat pump: | no | |
| Brine-to-water heat pump: | no | |
| Low-temperature heat pump: | no | |
| Equipped with a supplementary heater: | no | |
| Heat pump combination heater: | yes | |
| Parameters for | low-temperature application. | |
| Parameters for | colder climate conditions. | |

| Item | Symbol | Value | Unit | Item | Symbol | Value | Unit |
|--|------------------|-------|------|--|------------|-------|------|
| Rated heat output (*) | Prated | 5.5 | kW | Seasonal space heating energy efficiency | ηs | 147 | % |
| Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj | | | |
| Tj = - 7 °C | Pdh | 3.4 | kW | Tj = - 7 °C | COPd | 3.31 | - |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | |
| Tj = + 2 °C | Pdh | 3.6 | kW | Tj = + 2 °C | COPd | 4.56 | - |
| Degradation co-efficient (**) | Cdh | 0.98 | - | | | | |
| Tj = + 7 °C | Pdh | 3.4 | kW | Tj = + 7 °C | COPd | 6.55 | - |
| Degradation co-efficient (**) | Cdh | 0.97 | - | | | | |
| Tj = +12 °C | Pdh | 3.7 | kW | Tj = +12 °C | COPd | 7.33 | - |
| Degradation co-efficient (**) | Cdh | 0.97 | - | | | | |
| Tj = bivalent temperature | Pdh | 4.5 | kW | Tj = bivalent temperature | COPd | 1.92 | - |
| Tj = operation limit temperature (***) | Pdh | 5.5 | kW | Tj = operation limit temperature (***) | COPd | 1.71 | - |
| Tj = – 15 °C (if TOL < – 20 °C) | Pdh | 4.5 | kW | Tj = – 15 °C (if TOL < – 20 °C) | COPd | 1.92 | - |
| Bivalent temperature | Tbiv | -15 | °C | Operation limit temperature | TOL | -25 | °C |
| Reference design conditions for space heating | Tdesignh | -22 | °C | Heating water operating limit temperature | WTOL | 60 | °C |
| Power consumption in modes other than active mode | | | | Supplementary heater | | | |
| Off mode | P _{OFF} | 0.015 | kW | Rated heat output (*) | Psup | 0.0 | kW |
| Thermostat-off mode | P _{TO} | 0.015 | kW | | | | |
| Standby mode | P _{SB} | 0.015 | kW | Type of energy input | Electrical | | |
| Crankcase heater mode | P _{CK} | 0.000 | kW | | | | |

| | | | | | | | |
|-------------------------------------|-----------------|---------|-----|-------------------------------|---|------|------|
| Other items | | | | | | | |
| Capacity control | variable | | | Rated air flow rate, outdoors | - | 2500 | m³/h |
| Sound power level, indoors/outdoors | L _{WA} | 41 / 60 | dBa | | | | |
| Annual energy consumption | Q _{HE} | 3616 | kWh | | | | |

| | | | | | | | |
|-----------------------------------|-------|-------|-----|---------------------------------|-----|-----|---|
| For heat pump combination heater: | | | | | | | |
| Declared load profile | XL | | | Water heating energy efficiency | ηwh | 117 | % |
| Daily electricity consumption | Qelec | 6.710 | kWh | | | | |
| Annual electricity consumption | AEC | 1476 | kWh | | | | |

| | | | | | | | |
|--|--|--|--|---|--|--|--|
| Contact details | | | | | | | |
| MITSUBISHI ELECTRIC CONSUMER PRODUCTS (THAILAND) CO., LTD. | | | | 700/406 moo 7, Tambon don hua roh, Amphur muang, chonburi 20000, Thailand | | | |
| The identification and signature of the person empowered to bind the supplier; | | | | Tadashi SAITO | | | |
| The signature is signed in the average climate / medium-temperature section. | | | | Manager, Quality Assuarance Department | | | |
| | | | | THAILAND | | | |

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(***) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

PRODUCT INFORMATION / TECHNICAL DOCUMENTATION

| | | |
|---------------------------------------|---------------------------------|--------------------|
| Model(s): | Outdoor unit: | SUZ-SHWM60VAH(-SC) |
| | Indoor unit: | EHST30D-MED |
| Air-to-water heat pump: | yes | |
| Water-to-water heat pump: | no | |
| Brine-to-water heat pump: | no | |
| Low-temperature heat pump: | no | |
| Equipped with a supplementary heater: | no | |
| Heat pump combination heater: | yes | |
| Parameters for | medium-temperature application. | |
| Parameters for | warmer climate conditions. | |

| Item | Symbol | Value | Unit | Item | Symbol | Value | Unit |
|--|------------------|-------|------|--|--------|------------|------|
| Rated heat output (*) | Prated | 6.0 | kW | Seasonal space heating energy efficiency | ηs | 167 | % |
| Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj | | | |
| Tj = - 7 °C | Pdh | - | kW | Tj = - 7 °C | COPd | - | - |
| Degradation co-efficient (**) | Cdh | - | - | | | | |
| Tj = + 2 °C | Pdh | 6.0 | kW | Tj = + 2 °C | COPd | 2.47 | - |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | |
| Tj = + 7 °C | Pdh | 3.9 | kW | Tj = + 7 °C | COPd | 3.95 | - |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | |
| Tj = +12 °C | Pdh | 3.6 | kW | Tj = +12 °C | COPd | 5.50 | - |
| Degradation co-efficient (**) | Cdh | 0.98 | - | | | | |
| Tj = bivalent temperature | Pdh | 6.0 | kW | Tj = bivalent temperature | COPd | 2.51 | - |
| Tj = operation limit temperature (***) | Pdh | 6.0 | kW | Tj = operation limit temperature (***) | COPd | 2.51 | - |
| | | | | | | | |
| Bivalent temperature | Tbiv | 2 | °C | Operation limit temperature | TOL | -25 | °C |
| Reference design conditions for space heating | Tdesignh | 2 | °C | Heating water operating limit temperature | WTOL | 60 | °C |
| Power consumption in modes other than active mode | | | | Supplementary heater | | | |
| Off mode | P _{OFF} | 0.015 | kW | Rated heat output (*) | Psup | 0.0 | kW |
| Thermostat-off mode | P _{TO} | 0.015 | kW | | | | |
| Standby mode | P _{SB} | 0.015 | kW | Type of energy input | | Electrical | |
| Crankcase heater mode | P _{CK} | 0.000 | kW | | | | |

| | | | | | | | |
|-------------------------------------|-----------------|---------|-----|-------------------------------|---|------|------|
| Other items | | | | | | | |
| Capacity control | variable | | | Rated air flow rate, outdoors | - | 2500 | m³/h |
| Sound power level, indoors/outdoors | L _{WA} | 41 / 60 | dBa | | | | |
| Annual energy consumption | Q _{HE} | 1884 | kWh | | | | |

| | | | | | | | |
|-----------------------------------|-------|-------|-----|---------------------------------|-----|-----|---|
| For heat pump combination heater: | | | | | | | |
| Declared load profile | XL | | | Water heating energy efficiency | ηwh | 167 | % |
| Daily electricity consumption | Qelec | 4.720 | kWh | | | | |
| Annual electricity consumption | AEC | 1038 | kWh | | | | |

| | | | | | | | |
|--|--|--|--|---|--|--|--|
| Contact details | | | | | | | |
| MITSUBISHI ELECTRIC CONSUMER PRODUCTS (THAILAND) CO., LTD. | | | | 700/406 moo 7, Tambon don hua roh, Amphur muang, chonburi 20000, Thailand | | | |
| The identification and signature of the person empowered to bind the supplier; | | | | | | | |
| | | | | Tadashi SAITO | | | |
| The signature is signed in the average climate / medium-temperature section. | | | | Manager, Quality Assuarance Department | | | |
| | | | | THAILAND | | | |

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(***) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.

PRODUCT INFORMATION / TECHNICAL DOCUMENTATION

| | | |
|---------------------------------------|------------------------------|--------------------|
| Model(s): | Outdoor unit: | SUZ-SHWM60VAH(-SC) |
| | Indoor unit: | EHST30D-MED |
| Air-to-water heat pump: | yes | |
| Water-to-water heat pump: | no | |
| Brine-to-water heat pump: | no | |
| Low-temperature heat pump: | no | |
| Equipped with a supplementary heater: | no | |
| Heat pump combination heater: | yes | |
| Parameters for | low-temperature application. | |
| Parameters for | warmer climate conditions. | |

| Item | Symbol | Value | Unit | Item | Symbol | Value | Unit | | |
|--|------------------|-------|------|--|------------|-------|------|--|--|
| Rated heat output (*) | Prated | 6.0 | kW | Seasonal space heating energy efficiency | ηs | 230 | % | | |
| Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj | | | | | |
| Tj = - 7 °C | Pdh | - | kW | Tj = - 7 °C | COPd | - | - | | |
| Degradation co-efficient (**) | Cdh | - | - | | | | | | |
| Tj = + 2 °C | Pdh | 6.0 | kW | Tj = + 2 °C | COPd | 3.67 | - | | |
| Degradation co-efficient (**) | Cdh | 0.99 | - | | | | | | |
| Tj = + 7 °C | Pdh | 3.9 | kW | Tj = + 7 °C | COPd | 5.92 | - | | |
| Degradation co-efficient (**) | Cdh | 0.98 | - | | | | | | |
| Tj = +12 °C | Pdh | 3.7 | kW | Tj = +12 °C | COPd | 7.10 | - | | |
| Degradation co-efficient (**) | Cdh | 0.97 | - | | | | | | |
| Tj = bivalent temperature | Pdh | 6.0 | kW | Tj = bivalent temperature | COPd | 3.67 | - | | |
| Tj = operation limit temperature (***) | Pdh | 6.0 | kW | Tj = operation limit temperature (***) | COPd | 3.67 | - | | |
| | | | | | | | | | |
| Bivalent temperature | Tbiv | 2 | °C | Operation limit temperature | TOL | -25 | °C | | |
| Reference design conditions for space heating | Tdesignh | 2 | °C | Heating water operating limit temperature | WTOL | 60 | °C | | |
| Power consumption in modes other than active mode | | | | Supplementary heater | | | | | |
| Off mode | P _{OFF} | 0.015 | kW | Rated heat output (*) | Psup | 0.0 | kW | | |
| Thermostat-off mode | P _{TO} | 0.015 | kW | | | | | | |
| Standby mode | P _{SB} | 0.015 | kW | Type of energy input | Electrical | | | | |
| Crankcase heater mode | P _{CK} | 0.000 | kW | | | | | | |

| | | | | | | | |
|-------------------------------------|-----------------|---------|-----|-------------------------------|---|------|------|
| Other items | | | | | | | |
| Capacity control | variable | | | Rated air flow rate, outdoors | - | 2500 | m³/h |
| Sound power level, indoors/outdoors | L _{WA} | 41 / 60 | dBa | | | | |
| Annual energy consumption | Q _{HE} | 1378 | kWh | | | | |

| | | | | | | | |
|-----------------------------------|-------|-------|-----|---------------------------------|-----|-----|---|
| For heat pump combination heater: | | | | | | | |
| Declared load profile | XL | | | Water heating energy efficiency | ηwh | 167 | % |
| Daily electricity consumption | Qelec | 4.720 | kWh | | | | |
| Annual electricity consumption | AEC | 1038 | kWh | | | | |

| | | | | | | | |
|--|--|--|--|---|--|--|--|
| Contact details | | | | | | | |
| MITSUBISHI ELECTRIC CONSUMER PRODUCTS (THAILAND) CO., LTD. | | | | 700/406 moo 7, Tambon don hua roh, Amphur muang, chonburi 20000, Thailand | | | |
| The identification and signature of the person empowered to bind the supplier; | | | | | | | |
| | | | | Tadashi SAITO | | | |
| The signature is signed in the average climate / medium-temperature section. | | | | Manager, Quality Assuarance Department | | | |
| | | | | THAILAND | | | |

· Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

· Details and precautions on recycling and/or disposal at end-of-life can be found in the installation and or operation manuals.

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

(***) If the declared TOL is lower than the T designh of the considered climate then the outdoor dry bulb temperature Tj is equal to T designh.