



ENERG

енергия · ενέργεια

Y IJA
IE IA



Model


Outdoor unit **MXZ-4F72VF4**
Indoor unit 1/2/3 **MSZ-LN18/18/18VG2**
Indoor unit 4 **MSZ-LN18VG2**

SEER



kW **7,2**
SEER **8,1**
kWh/annum **311**

SCOP



kW	X	7,0	X
SCOP	X	4,1	X
kWh/annum	X	2389	X



Indoor unit 1/2/3/4
58dB



Outdoor unit
63dB



ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI
626/2011

BH79N257H50

PRODUCT INFORMATION (*1)

ROOM AIR CONDITIONER	INDOOR MODEL 1/2/3 INDOOR MODEL 4/5/6 OUTDOOR MODEL	MSZ-LN18VG2 / MSZ-LN18VG2 / MSZ-LN18VG2 MSZ-LN18VG2 / - / - MXZ-4F72VF4
----------------------	---	---

Function (indicate if present)	
cooling	Y
heating	Y

If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.	
Average (mandatory)	Y
Warmer (if designated)	N
Colder (if designated)	N

Item	symbol	value	unit
Design load			
cooling	Pdesignc	7,2	kW
heating/Average	Pdesignh	7,0	kW
heating/Warmer	Pdesignh	x	kW
heating/Colder	Pdesignh	x	kW

Item	symbol	value	unit
Seasonal efficiency			
cooling	SEER	8,1	-
heating/Average	SCOP/A	4,1	-
heating/Warmer	SCOP/W	x	-
heating/Colder	SCOP/C	x	-

Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C	Pdc	7,20	kW
Tj=30°C	Pdc	5,40	kW
Tj=25°C	Pdc	3,41	kW
Tj=20°C	Pdc	2,65	kW

Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C	EERd	3,89	-
Tj=30°C	EERd	6,50	-
Tj=25°C	EERd	9,93	-
Tj=20°C	EERd	13,65	-

Declared capacity for heating/Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	6,20	kW
Tj=2°C	Pdh	4,00	kW
Tj=7°C	Pdh	2,60	kW
Tj=12°C	Pdh	1,75	kW
Tj=bivalent temperature	Pdh	6,20	kW
Tj=operating limit	Pdh	4,80	kW

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	COPd	2,70	-
Tj=2°C	COPd	4,07	-
Tj=7°C	COPd	5,20	-
Tj=12°C	COPd	6,30	-
Tj=bivalent temperature	COPd	2,70	-
Tj=operating limit	COPd	2,20	-

Declared capacity for heating/Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	Pdh	x	kW
Tj=7°C	Pdh	x	kW
Tj=12°C	Pdh	x	kW
Tj=bivalent temperature	Pdh	x	kW
Tj=operating limit	Pdh	x	kW

Declared coefficient of performance/Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	COPd	x	-
Tj=7°C	COPd	x	-
Tj=12°C	COPd	x	-
Tj=bivalent temperature	COPd	x	-
Tj=operating limit	COPd	x	-

Declared capacity for heating/Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	x	kW
Tj=2°C	Pdh	x	kW
Tj=7°C	Pdh	x	kW
Tj=12°C	Pdh	x	kW
Tj=bivalent temperature	Pdh	x	kW
Tj=operating limit	Pdh	x	kW
Tj=-15°C	Pdh	x	kW

Declared coefficient of performance/Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	COPd	x	-
Tj=2°C	COPd	x	-
Tj=7°C	COPd	x	-
Tj=12°C	COPd	x	-
Tj=bivalent temperature	COPd	x	-
Tj=operating limit	COPd	x	-
Tj=-15°C	COPd	x	-

Bivalent temperature			
heating/Average	Tbiv	-7	°C
heating/Warmer	Tbiv	x	°C
heating/Colder	Tbiv	x	°C

Operating limit temperature			
heating/Average	Tol	-15	°C
heating/Warmer	Tol	x	°C
heating/Colder	Tol	x	°C

Cycling interval capacity			
for cooling	Pccyc	x	kW
for heating	Pchyc	x	kW
Degradation co-efficient	Cdc	0,25	-

Cycling interval efficiency			
for cooling	EERcyc	x	-
for heating	COPcyc	x	-
Degradation co-efficient	Cdh	0,25	-

Electric power input in power modes other than 'active mode'			
off mode	POFF	4	W
standby mode	PSB	4	W
thermostat - off mode	PTO	21	W
crankcase heater mode	PCK	0	W

Annual electricity consumption			
cooling	QCE	311	kWh/a
heating/Average	QHE	2389	kWh/a
heating/Warmer	QHE	x	kWh/a
heating/Colder	QHE	x	kWh/a

Capacity control (indicate one of three options)	
fixed	N
staged	N
variable	Y

Other items			
Sound power level (indoor1-4/outdoor)	LWA	58/63	dB(A)
Global warming potential	GWP (*2)	675	kgCO2eq.
Rated air flow (indoor1-4/outdoor)	-	666/2124	m³/h

Contact details for obtaining more information	MITSUBISHI ELECTRIC CORPORATION SHIZUOKA WORKS 3-18-1, Oshika, Suruga-ku, Shizuoka 422-8528, Japan E-mail: melshierp@nb.MitsubishiElectric.co.jp
--	--

(*1) This information is based on the "product information requirement" in COMMISSION REGULATION (EU) No206/2012,

(*2) This GWP value is based on Regulation (EU) No.517/2014 from IPCC 4th Assessment Report.

For Regulation (EU) No.626/2011, which cites the IPCC Third Assessment Report, Climate Change 2001, the GWP is 550.

TECHNICAL DOCUMENTATION (1)

ROOM AIR CONDITIONER	INDOOR MODEL 1	MSZ-LN18VG2	307H890W233D (mm)
	INDOOR MODEL 2	MSZ-LN18VG2	307H890W233D (mm)
	INDOOR MODEL 3	MSZ-LN18VG2	307H890W233D (mm)
	INDOOR MODEL 4	MSZ-LN18VG2	307H890W233D (mm)
	INDOOR MODEL 5	-	-
	INDOOR MODEL 6	-	-
	OUTDOOR MODEL	MXZ-4F72VF4	710H840W330D (mm)

Function		
cooling		Y
heating		Y


The heating season		
Average (mandatory)		Y
Warmer (if designated)		N
Colder (if designated)		N

Capacity control		
fixed		N
staged		N
variable		Y

Item	symbol	value	unit
Seasonal efficiency (2)			
cooling	SEER	8,1	-
heating/Average	SCOP/A	4,1	-
heating/Warmer	SCOP/W	x	-
heating/Colder	SCOP/C	x	-

Energy efficiency class			
cooling	SEER	A++	-
heating/Average	SCOP/A	A+	-
heating/Warmer	SCOP/W	x	-
heating/Colder	SCOP/C	x	-

Other items			
Sound power level (indoor1-4/outdoor)	LWA	58/63	dB(A)
Refrigerant	-	R32	-
Global warming potential	GWP (3)	675	kgCO2eq.

identification and signature of the person empowered to bind the supplier	Yukihito Kitamura	
	Department Manager, Quality Assurance Department MITSUBISHI ELECTRIC CONSUMER PRODUCTS(THAILAND) CO.,LTD	

(1) This information is based on COMMISSION DELEGATED REGULATION (EU)No626/2011,

(2) SEER/SCOP values are measured based on FprEN 14825:2016: Testing and rating at part load conditions and calculation of seasonal performance.

(3) This GWP value is based on Regulation (EU) No.517/2014 from IPCC 4th Assessment Report.

For Regulation (EU) No.626/2011, which cites the IPCC Third Assessment Report, Climate Change 2001, the GWP is 550.