



ENERG
енергия · ενέργεια

Y IJA
IE IA



MITSUBISHI
ELECTRIC

Model

Indoor unit
Outdoor unit

PLA-M100EA
PUZ-ZM100YKA

SEER



A++



kW 9,5

SEER 7,4

kWh/annum 446

SCOP



A+



kW X

SCOP X

kWh/annum X

7,8

4,3

2521

X

X

X



61dB



69dB



ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

626/2011

PRODUCT INFORMATION (*)

PACKAGED AIR CONDITIONER INDOOR MODEL OUTDOOR MODEL	PLA-M100EA PUZ-ZM100YKA
Function (indicate if present)	If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.
cooling Y heating Y	Average (mandatory) Y Warmer (if designated) N Colder (if designated) N
Item symbol value unit	Item symbol value unit
Design load	Seasonal efficiency
cooling Pdesignc 9.5 kW heating/Average Pdesignh 7.8 kW heating/Warmer Pdesignh x kW heating/Colder Pdesignh x kW	cooling SEER 7.4 - heating/Average SCOP/A 4.3 - heating/Warmer SCOP/W x - heating/Colder SCOP/C x -
Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj	Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj
Tj=35°C Pdc 9.50 kW Tj=30°C Pdc 7.00 kW Tj=25°C Pdc 4.50 kW Tj=20°C Pdc 4.50 kW	Tj=35°C EERd 4.56 - Tj=30°C EERd 6.12 - Tj=25°C EERd 9.96 - Tj=20°C EERd 12.52 -
Declared capacity for heating/Average season, at indoor temperature 20°C and outdoor temperature Tj	Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj
Tj=-7°C Pdh 6.90 kW Tj=2°C Pdh 4.20 kW Tj=7°C Pdh 3.20 kW Tj=12°C Pdh 3.80 kW Tj=bivalent temperature Pdh 7.80 kW Tj=operating limit Pdh 5.80 kW	Tj=-7°C COPd 2.94 - Tj=2°C COPd 4.17 - Tj=7°C COPd 5.86 - Tj=12°C COPd 7.08 - Tj=bivalent temperature COPd 2.58 - Tj=operating limit COPd 1.90 -
Declared capacity for heating/Warmer season, at indoor temperature 20°C and outdoor temperature Tj	Declared coefficient of performance/Warmer season, at indoor temperature 20°C and outdoor temperature Tj
Tj=2°C Pdh x kW Tj=7°C Pdh x kW Tj=12°C Pdh x kW Tj=bivalent temperature Pdh x kW Tj=operating limit Pdh x kW	Tj=2°C COPd x - Tj=7°C COPd x - Tj=12°C COPd x - Tj=bivalent temperature COPd x - Tj=operating limit COPd x -
Declared capacity for heating/Colder season, at indoor temperature 20°C and outdoor temperature Tj	Declared coefficient of performance/Colder season, at indoor temperature 20°C and outdoor temperature Tj
Tj=-7°C Pdh x kW Tj=2°C Pdh x kW Tj=7°C Pdh x kW Tj=12°C Pdh x kW Tj=bivalent temperature Pdh x kW Tj=operating limit Pdh x kW Tj=-15°C Pdh x kW	Tj=-7°C COPd x - Tj=2°C COPd x - Tj=7°C COPd x - Tj=12°C COPd x - Tj=bivalent temperature COPd x - Tj=operating limit COPd x - Tj=-15°C COPd x -
Bivalent temperature	Operating limit temperature
heating/Average Tbiv -10 °C heating/Warmer Tbiv x °C heating/Colder Tbiv x °C	heating/Average Tol -20 °C heating/Warmer Tol x °C heating/Colder Tol x °C
Cycling interval capacity	Cycling interval efficiency
for cooling Pcycc x kW for heating Pcych x kW Degradation co-efficient cooling Cdc 0.25 -	for cooling EERcyc x - for heating COPcyc x - Degradion co-efficient heating Cdh 0.25 -
Electric power input in power modes other than 'active mode'	Annual electricity consumption
off mode POFF 20 W standby mode PSB 20 W thermostat - off mode PTO(c/h) 3/15 W crankcase heater mode PCK 0 W	cooling QCE 446 kWh/a heating/Average QHE 2521 kWh/a heating/Warmer QHE x kWh/a heating/Colder QHE x kWh/a
Capacity control (indicate one of three options)	Other items
fixed N staged N variable Y	Sound power level (indoor/outdoor) LWA 61/69 dB(A) Global warming potential GWP 550 kgCO ₂ eq Rated air flow (indoor/outdoor) - 1740/6600 m ³ /h
Contact details for obtaining more information	MITSUBISHI ELECTRIC CORPORATION SHIZUOKA WORKS 3-18-1, Oshika, Suruga-ku, Shizuoka 422-8528, Japan E-mail: melshierp@MitsubishiElectric.co.jp

(*) This information is based on the "product information requirement" in COMMISSION REGULATION (EU) No206/2012.

TECHNICAL DOCUMENTATION (¹)

PACKAGED AIR CONDITIONER	INDOOR MODEL OUTDOOR MODEL	PLA-M100EA PUZ-ZM100YKA	298H840W840D (mm) 981H1050W330D (mm)
--------------------------	-------------------------------	----------------------------	---

Function	
cooling	Y
heating	Y


The heating season	
Average (mandatory)	Y
Warmer (if designated)	N
Colder (if designated)	N

Capacity control	
fixed	N
staged	N
variable	Y

Item	symbol	value	unit
Seasonal efficiency (²)			
cooling	SEER	7.4	-
heating/Average	SCOP/A	4.3	-
heating/Warmer	SCOP/W	x	-
heating/Colder	SCOP/C	x	-

Energy efficiency class			
cooling	SEER	A++	-
heating/Average	SCOP/A	A+	-
heating/Warmer	SCOP/W	x	-
heating/Colder	SCOP/C	x	-

Other items			
Sound power level (indoor/outdoor)	LWA	61/69	dB(A)
Refrigerant	-	R32	-
Global warming potential	GWP	550	kgCO2eq.

identification and signature of the person empowered to bind the supplier	 Takashi Tanabe Manager, Quality Assurance Department Mitsubishi Electric Air Conditioning Systems Europe Ltd.
---	--

(1) This information is based on COMMISSION DELEGATED REGULATION (EU)No626/2011.

(2) SEER/SCOP values are measured based on FprEN 14825:2011: Testing and rating at part load conditions and calculation of seasonal performance